



TruVu

i-Vu® Building Automation System TruVu™ Dual IP Bypass Controller

Part Number: TV-VVTBP-E2



The TruVu dual IP VVT bypass controller is used to regulate the supply duct static pressure for a variety of pressure-dependent VVT applications and allows constant volume HVAC equipment to provide zone level temperature control. This completely programmable advanced controller features an integrated actuator for easy installation onto bypass dampers. It ships with Carrier factory engineered and tested applications for bypass control. The daisy chained BACnet IP communications deliver plug-and-play connectivity to the Carrier i-Vu building automation system.

Application Features

- Sophisticated factory-engineered and tested control programs provide reliability and energy efficiency
- Temperature protection minimizes the occurrence of air source heating and/or cooling lockouts based on unacceptable discharge temperatures
- Provides automatic pressure sensor calibration
- Can drive multiple damper actuators
- VFD support via 0-10VDC analog output to provide drive speed modulation
- Supports two simultaneous application control programs, for customized application solutions
- Programmable control of dampers, VFDs and other auxiliary equipment using Snap graphical programming
- Supports Carrier communicating sensors which are available in a variety of zone and equipment sensing combinations
- Supports Carrier TruVu touchscreen interfaces for managing and troubleshooting the connected equipment easily and for occupant engagement
- Conforms to the BACnet Advanced Application Controller (B-AAC) Standard Device and BACnet Broadcast Management Device (B-BMD), as defined in BACnet 135-2001 2012 Annex L and tested to Protocol Revision 15

Hardware Features

- Integrated 45 in-lb 154 second actuator for reliability and longevity
- Dual 10/100 Mbps, BACnet IP and DHCP IP addressing
- Native BACnet IP or MS/TP communications
- Supports home run, daisy chain and ring IP network topologies
- Capacitor-backed real-time clock keeps time in the event of power failure or network interruption for up to three days
- Controls up to 9 points (3 binary outputs, 4 universal inputs and 2 analog output) plus up to 2 Act Net Smart Actuators
- USB port for local device updates, hard-wired, and wireless service connections
- Reversible airflow connections allows for error free tube installation

System Benefits

- Integrated Carrier airside linkage algorithm for plug-and-play integration with Carrier air sources
- Fully plug-and-play with the i-Vu building automation system

i-Vu Building Automation System

TruVu Dual IP Bypass Controller



Part Number: TV-VVTBP-E2



Specifications

BACnet Support	Conforms to the BACnet Advanced Application Controller (B-AAC) and BACnet Broadcast Management Device (B-BBMD) standard device profiles, as defined in BACnet 135-2012 Annex L Protocol rev. 15
Power Requirements	24Vac +/- 15% , 50 - 60Hz, 50VA 24Vdc +/- 10%, 18W. (75VA / 35W if additional Act Net devices are connected)
Communication	<p>BAS Primary Port Dual 10/100 BaseT Ethernet ports with built-in fail safe, supporting direct connection or daisy chain topology natively using BACnet/IP (non-routing)</p> <p>Serial Port 1 EIA-485 port for BACnet MS/TP communications (9600 bps to 115.2 kbps)</p> <p>Rnet Port 12Vdc @ 260mA supports the following: Up to 10 ZS sensors (mix ZS zone, ZS duct, ZS immersion and ZS outdoor sensors), i-Vu Equipment Touch, or TruVu ET Displays (external power required)</p> <p>Act Net Port Supports up to 2 Act Net communicating i-Vu smart valves</p> <p>2 USB Ports For TruVu ET Display support configuration wireless service access firmware updates and controller recovery via USB drive</p>
Inputs	Universal 4 Universal Inputs electronically configurable to any of the following types: Dry Pulse Counting Thermistor 0-10 Vdc
Outputs	<p>Analog 2 Analog Outputs 10Vdc @ (D/A Resolution 12 bits) PWM 12Vdc @ 80Hz</p> <p>Digital 3 Digital outputs (Dry Contact) Rated @30Vac/Vdc @ 1.4 Amp. Configured normally open</p>
Actuator	Brushless DC motor, torque 45 inch-pounds (5Nm), runtime 154 seconds for 90 degree travel during control
Integral Pressure Sensor	Precision low flow AWM series 0-2 in. H ₂ O, sensitive down to ±0.001 in. H ₂ O. Barbed tapered airflow connections accept 3/16 in. (4.75 mm) I.D. tubing. Allows for readings across the 0-2 in. H ₂ O range, accurate to ±3% of reading. Reversible connections
Real Time Clock	Real-time clock keeps track of time in the event of a power failure for at least 3 days
Status Indicators	LED status indicators for IP and S1 communications, run status, error, power, all outputs, and locator LEDs for controller identification and actuator rotation feedback
Memory	4 GBs eMMC Flash memory and 256 MB DDR3 DRAM. User data is archived to non-volatile flash memory when parameters are changed every 90 seconds
Compliance	United States: FCC compliant to Title CFR47, Part 15, Subpart B, Class A; UL Listed, File E143900; CCN PAZX, UL 916, Energy Management Equipment; ANZ: RCM Mark AS/NZS 61000-6-3; Canada: UL Listed File E143900, CCN PAZX7, CAN/CSA C22.2 No. 205 Signal Equip., Industry Canada Compliant ICES-003, Class A; CE Mark Compliant with 2014/30/EU, and RoHS Compliant: 2015/863/EU; UKCA Mark compliant with Electromagnetic Compatibility Regulations 2016 – Gov.UK and RoHS for Electrical and Electronic Equipment 2012.
Environmental Operating Range	Operating: 32 to 122°F (0 to 50°C) 10 to 95% RH, non-condensing Storage: -24 to 140°F (-30 to 60°C) 0 to 90% RH, non-condensing
Plastic	Fire-retardant plastic ABS, UL94-5VA

Dimensions

Width: 8.367 in. (21.25 cm)
Length: 5.95 in. (15.11 cm)
Depth: 3.828 in. (9.72 cm)
Weight: 1.8 lbs (0.82 kg)

Minimum Shaft Diameter: 3/8 in. (.95 cm)
Maximum Shaft Diameter: 1/2 in. (1.27 cm)
Minimum Shaft Length: 1 3/4 in. (4.45 cm)



For more information, contact your local Carrier Controls Expert.

Controls Expert Locator:
www.carrier.com/controls-experts