

VRF Indoor Unit 45VMF024---3---4-Way Cassette



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Delivers air in all four directions
- Knock out for OA opening
- Louver control (fixed or swing)
- Three fan speeds - high, medium, and low
- Built-in condensate lift mechanism
- Built in EXV (Electronic Expansion Valve) for installation ease

INDOOR UNIT MODEL		45VMF024---3
PERFORMANCE		
Total Cooling Rated Capacity	Btu/h	24,000
Total Heating Rated Capacity	Btu/h	27,000
Airflow (H / M / L)	CFM	751 / 657 / 562
Sound Pressure (H / M / L)	dBA	44 / 42 / 40
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Indoor Fan Motor Rated Motor (Output)	W	125
Minimum Circuit Amps (MCA)	A	1.49
Maximum Overcurrent Protection	A	15.0
Motor Type		DC

PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	1/4 (OD)
Pipe Connection Size - Suction	in.	1/2 (OD)
Pipe Connection Size - Drain	in.	1 (OD)
Refrigerant		R-454B
Unit Width	in.	33-1/8
Unit Height	in.	9-3/4
Unit Depth	in.	33-1/8
Unit Net Weight	lbs.	57.3
Panel Width	in.	37-3/8
Panel Height	in.	3
Panel Depth	in.	37-3/8
Panel Net Weight	lbs.	12.8

ACCESSORIES

- ☐ Wireless Remote Controller 45VM900001
- ☐ Wired Remote Controller - Non-Prog. 45VM900002
- ☐ Grille 45VM0001---

[illegible]

A	B	C	D	E	F
288 (11-5/16)	190 (7-1/2)	103 (4-1/16)	56.5 (2-1/4)	Φ 15.9 (5/8)	Φ 9.52 (3/8)

