

VRF Indoor Unit 45VMW005---3 — High Wall



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Dual Guided Air Design Provides Smoother and More Comfortable Air Flow
- Three Fan Speeds - High, Medium and Low
- Front Panel Lifts Up 65 Degrees Providing Ease of Maintenance
- Heating Mode, Swing Angle for Louver is 68 to 110 Degrees in Auto Mode
- Non-Heating Mode, Swing Angle for Louver is 61 to 93 Degrees in Auto Mode
- Manual Setting for Louver, Swing Angle Between 61 and 110 Degrees
- Multi-Refrigerant Outlet Piping Methods - Left, Right or Rear
- Built in EXV (Electronic Expansion Valve) for Installation Ease
- Internally Installed A2L Refrigerant Leak Sensor

Indoor Unit Model		45VMW005---3
PERFORMANCE		
Total Cooling Rated Capacity	Btu/h	5,000
Total Heating Rated Capacity	Btu/h	6,000
Airflow (H / M / L)	CFM	249 / 225 / 201
Sound Pressure (H / M / L)	dBA	31 / 29.6 / 28
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Indoor Fan Motor Rated Motor (Output)	W	20
Minimum Circuit Amps	A	0.55
Maximum Overcurrent Protection	A	15
Motor Type		DC

PHYSICAL DATA

Pipe Connection Size - Liquid	in.	1/4
Pipe Connection Size - Suction	in.	1/2
Pipe Connection Size - Drain	in.	5/8
Refrigerant		R-454B
Unit Width	in.	29-1/2
Unit Height	in.	11-5/8
Unit Depth	in.	10-7/16
Unit Net Weight	lb	23

ACCESSORIES (Optional)

- ☐ Wireless Remote Controller 45VM900001
☐ Wired Remote Controller - Non-Prog. 45VM900002

DIMENSIONAL DRAWING

INDOOR UNIT HIGH WALL 45VMW005---3

