

# SMMSu / SHRMu VRF Indoor Unit MMK-UP0241HP-UL—HIGH WALL

**TOSHIBA**  
*Carrier*

## Submittal Data

Job Name \_\_\_\_\_ Location \_\_\_\_\_  
Tag \_\_\_\_\_



### SMMSu / SHRMu VRF High Wall Features

- R-410A refrigerant
- Eight sizes from 7,500 to 36,000 Btu/h
- Quiet operation, as low as 27 dBA
- Vertical airflow can be set to swing or fixed position
- Air throw up to 23 feet
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMK-UP0241HP-UL
PERFORMANCE		
Cooling Rated Capacity	Btu/h	24,000
Heating Rated Capacity	Btu/h	27,000
Fan Type (Qty)	Cross-Flow (1)	
Airflow (H / M / L)	CFM	700 / 530 / 355
Sound Pressure (H / M / L)	dBA	45 / 39 / 33
FILTER (Standard)		
Type	Washable	
Quantity	2	
MERV Corresponding Value	5	
Dimensions (W x L x D)	in.	15-3/4 x 16-3/8 x 1/16
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.05
Full Load Amps (FLA)	A	0.48
Minimum Circuit Amps (MCA)	A	0.60
Maximum Overcurrent Protection (MOCP)	A	15.0
MOTOR		
Motor Type	DC Inverter Driven	
Motor Watts	W	30

PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	7/8
Pipe Connection Size - Drain (ID)	in.	5/8
Refrigerant	R-410A	
External Finish	Munsell 2.5GY9.0/0.5	
Unit Width	in.	41-3/8
Unit Height	in.	12-5/8
Unit Depth	in.	9-7/8
Net Weight	lb	36
CONTROLS		
Wireless Remote Controller (Standard)		

### ACCESSORIES

- ☐ Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control - RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Condensate Drain Pump Kit 53DS-900---118

# DIMENSIONAL DRAWING INDOOR UNIT HIGH WALL MMK-UP0241HP-UL

