

SMMSu / SHRMu VRF Indoor Unit MMK-UP0301HP-UL—HIGH WALL

TOSHIBA
Carrier

Submittal Data

Job Name _____ Location _____
Tag _____



SMMSu / SHRMu VRF High Wall Features

- R-410A refrigerant
- Eight sizes from 7,500 to 36,000 Btu/h
- Quiet operation, as low as 27 dBA
- Vertical airflow can be set to swing or fixed position
- Air throw up to 23 feet
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMK-UP0301HP-UL
PERFORMANCE		
Cooling Rated Capacity	Btu/h	30,000
Heating Rated Capacity	Btu/h	34,000
Fan Type (Qty)	Centrifugal Fan (1)	
Airflow (H / M / L)	CFM	940 / 825 / 705
Sound Pressure (H / M / L)	dBA	48 / 44 / 41
FILTER (Standard)		
Type	Washable	
Quantity	2	
MERV Corresponding Value	5	
Dimensions	16-1/2 x 19-5/8 x 1/16	
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.058
Full Load Amps (FLA)	A	0.66
Minimum Circuit Amps (MCA)	A	0.83
Maximum Overcurrent Protection (MOCP)	A	15.0
MOTOR		
Motor Type	DC	
Motor Watts	W	61

PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	7/8
Pipe Connection Size - Drain (ID)	in.	5/8
Refrigerant	R-410A	
External Finish	Munsell 2.5GY9.0/0.5	
Unit Width	in.	47-1/4
Unit Height	in.	13-3/4
Unit Depth	in.	11
Net Weight	lb	46.3
CONTROLS		
Wireless Remote Controller (Standard)		

ACCESSORIES

- ☐ Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control - RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Condensate Drain Pump Kit 53DS-900---118

DIMENSIONAL DRAWING INDOOR UNIT HIGH WALL MMK-UP0301HP-UL

