

4 - Way Cassette Type

MMU-UP0071HP-UL

MMU-UP0091HP-UL

MMU-UP0121HP-UL

MMU-UP0151HP-UL

MMU-UP0181HP-UL

MMU-UP0241HP-UL


MMU-UP0301HP-UL

MMU-UP0361HP-UL


MMU-UP0421HP-UL

MMU-UP0481HP-UL


MMU-UP0541HP-UL



RBC-U32PGP-UL



RBC-U33P-UL



RBC-U33PB-UL

Contents

1.	Specifications	3
2.	Dimensions	5
3.	Center of gravity	7
4.	Piping diagram	8
5.	Wiring diagram	9
6.	Electrical current characteristics	10
7.	Sensible capacity table	11
8.	Air throw distance chart	15
9.	Sound data	17
10.	Accessories	19
	Appendix	20

1. Specifications

Model name			MMU-	UP0071HP-UL	UP0091HP-UL	UP0121HP-UL	UP0151HP-UL	UP0181HP-UL
Power supply			1 ph 60Hz 230V (208 / 230V)					
Cooling capacity (*1)			kBtu/h	7.5	9.5	12.0	15.4	18.0
Sensible cooling capacity (*1)			kBtu/h	5.8	7.1	9.4	12.0	12.8
Heating capacity (*1)			kBtu/h	8.5	10.5	13.5	17.0	20.0
Power consumption			(kW)	0.021	0.021	0.023	0.026	0.026
FCU dimension	Main unit	Height (in)		10.1	10.1	10.1	10.1	10.1
		Width (in)		33.1	33.1	33.1	33.1	33.1
		Depth (in)		33.1	33.1	33.1	33.1	33.1
Total weight	Main unit	(lbs)		45	45	51	51	51
Heat exchanger			Finned tube					
Soundproof / Heat-insulation material			Polyethylene foam					
Fan			Turbo fan					
Air flow volume	Indoor unit (H/M/L)	(cfm)		470 / 430 / 400	470 / 430 / 400	550 / 480 / 440	550 / 480 / 440	550 / 480 / 440
Sound pressure	Indoor unit (H/M/L)	dB(A)		32.5 / 30.5 / 29	32.5 / 30.5 / 29	35 / 33 / 31	35 / 33 / 31	35 / 33 / 31
Motor output			(W)	60	60	60	60	60
Flare Connections	Gas side	(in)		3/8	3/8	3/8	1/2	1/2
	Liquid side	(in)		1/4	1/4	1/4	1/4	1/4
	Drain pipe	(in)		VP25 (Polyvinyl Chloride Tube: External Dia. 1-1/4 Internal Dia. 1)				
Operating Range (*2)	Cooling	(°F)		41 ~ 109				
	Heating	(°F)		14 ~ 109				

(*1) Rated testing conditions Cooling : Indoor air temperature 80°F Dry Bulb / 67°F Wet Bulb, Outdoor 95°F Dry Bulb

Heating : Indoor air temperature 70°F Dry Bulb, Outdoor 47°F Dry Bulb / 43°F Wet Bulb

(*2) Refer to outdoor unit databook for operating range of outdoor units

Model name		MMU-	UP0241HP-UL	UP0301HP-UL	UP0361HP-UL	UP0421HP-UL	UP0481HP-UL	UP0541HP-UL
Power supply			1 ph 60Hz 230V (208 / 230V)					
Cooling capacity (*1)		kBtu/h	24.0	30.0	36.0	42.0	48.0	54.0
Sensible cooling capacity (*1)		kBtu/h	16.5	20.6	24.7	29.4	33.6	37.8
Heating capacity (*1)		kBtu/h	27.0	34.0	40.0	47.5	54.0	60.0
Power consumption		(kW)	0.036	0.043	0.088	0.112	0.112	0.112
FCU dimension	Main unit	Height (in)	10.1	10.1	12.6	12.6	12.6	12.6
		Width (in)	33.1	33.1	33.1	33.1	33.1	33.1
		Depth (in)	33.1	33.1	33.1	33.1	33.1	33.1
Total weight	Main unit	(lbs)	51	51	60	60	60	60
Heat exchanger			Finned tube					
Soundproof / Heat-insulation material			Polyethylene foam					
Fan			Turbo fan					
Air flow volume	Indoor unit (H/M/L)	(cfm)	670 / 540 / 490	730 / 630 / 510	1160 / 840 / 630	1250 / 840 / 670	1250 / 840 / 670	1250 / 890 / 720
Sound pressure	Indoor unit (H/M/L)	dB(A)	38 / 33 / 31	41 / 36.5 / 34	46 / 40.5 / 36.5	48.5 / 40.5 / 37.5	48.5 / 40.5 / 37.5	48.5 / 40.5 / 37.5
Motor output		(W)	60	60	150	150	150	150
Flare Connections	Gas side	(in)	5/8	5/8	5/8	5/8	5/8	5/8
	Liquid side	(in)	3/8	3/8	3/8	3/8	3/8	3/8
	Drain pipe	(in)	VP25 (Polyvinyl Chloride Tube: External Dia. 1-1/4 Internal Dia. 1)					
Operating Range (*2)	Cooling	(°F)	41 ~ 109					
	Heating	(°F)	14 ~ 109					


(*1) Rated testing conditions Cooling : Indoor air temperature 80°F Dry Bulb / 67°F Wet Bulb, Outdoor 95°F Dry Bulb

Heating : Indoor air temperature 70°F Dry Bulb, Outdoor 47°F Dry Bulb / 43°F Wet Bulb


(*2) Refer to outdoor unit databook for operating range of outdoor units

2. Dimension

MMU-UP*__1HP-UL (*007 / 009 / 012 / 015 / 018 / 024 / 030)




MMU-UP*__1HP-UL (*036 / 042 / 048 / 054)




3. Center of gravity

Model name	X (in)	Y (in)	Z (in)	Total weight	
				Main unit (lbs)	Ceiling panel (lbs)
MMU-UP0071HP-UL	18.5	17.9	6.1	45	9
MMU-UP0091HP-UL					
MMU-UP0121HP-UL	18.5	17.9	6.1	51	
MMU-UP0151HP-UL					
MMU-UP0181HP-UL					
MMU-UP0241HP-UL					
MMU-UP0301HP-UL					
MMU-UP0361HP-UL	18.5	17.7	7.2	60	
MMU-UP0421HP-UL					
MMU-UP0481HP-UL					
MMU-UP0541HP-UL					



4. Piping diagram


MMU-UP*__1HP-UL (*007 / 009 / 012 / 015 / 018 / 024 / 030 / 036 / 042 / 048 / 054)



Functional part name		Functional outline
Pulse Motor Valve	PMV	(Connector CN082 (6P): Blue) 1) Controls super heat in cooling operation 2) Controls under cool in heating operation 3) Recovers refrigerant oil in cooling operation 4) Recovers refrigerant oil in heating operation
Temp. sensor	1. TA	(Connector CN104 (2P): Yellow) 1) Detects indoor suction temperature
	2. TC1	(Connector CN100 (3P): Brown) 1) Controls PMV super heat in cooling operation
	3. TC2	(Connector CN101 (2P): Black) 1) Controls PMV under cool in heating operation
	4. TCJ	(Connector CN102 (2P): Red) 1) Controls PMV super heat in cooling operation

5. Wiring diagram

MMU-UP*__1HP-UL (*007 / 009 / 012 / 015 / 018 / 024 / 030 / 036 / 042 / 048 / 054)



6. Electrical current characteristic

Indoor unit power supply

Type	Model name	Normal Voltage (V-Ph-Hz)	Voltage Range (V)		FLA A	MCA A	MOCP A
			Min.	Max.			
4-Way Cassette Type	MMU-UP0071HP-UL	208/230-1-60	187	253	0.63	0.79	15
	MMU-UP0091HP-UL	208/230-1-60	187	253	0.63	0.79	15
	MMU-UP0121HP-UL	208/230-1-60	187	253	0.80	1.00	15
	MMU-UP0151HP-UL	208/230-1-60	187	253	0.80	1.00	15
	MMU-UP0181HP-UL	208/230-1-60	187	253	0.80	1.00	15
	MMU-UP0241HP-UL	208/230-1-60	187	253	0.87	1.09	15
	MMU-UP0301HP-UL	208/230-1-60	187	253	0.87	1.09	15
	MMU-UP0361HP-UL	208/230-1-60	187	253	1.15	1.44	15
	MMU-UP0421HP-UL	208/230-1-60	187	253	1.15	1.44	15
	MMU-UP0481HP-UL	208/230-1-60	187	253	1.15	1.44	15
	MMU-UP0541HP-UL	208/230-1-60	187	253	1.15	1.44	15

MCA : Minimum Circuit (Amps)

MOCP : Maximum Overcurrent Protection (Amps)

FLA : Full load (Amps)

7. Sensible capacity table

4-way cassette type (MMU-UP*__1HP-UL)

unit size	outdoor air temp. FDB	Indoor air temp.													
		59 ° FWB		61 ° FWB		64 ° FWB		67 ° FWB		68 ° FWB		72 ° FWB		75 ° FWB	
		71 ° FDB		73 ° FDB		77 ° FDB		80 ° FDB		82 ° FDB		86 ° FDB		90 ° FDB	
		TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
007	41	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	45	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	50	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	54	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	57	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	61	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	64	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	68	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	70	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	73	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	77	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	81	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	84	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	88	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	91	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	95	6160	5140	6810	5480	7280	5820	7500	5800	7730	5800	8180	5750	8550	5610
	99	5980	4990	6610	5320	7070	5650	7280	5630	7510	5630	7940	5580	8300	5450
102	5840	4870	6460	5200	6900	5520	7110	5500	7330	5500	7750	5450	8110	5320	
106	5680	4740	6280	5050	6710	5370	6920	5350	7130	5350	7540	5300	7880	5170	
109	5530	4610	6110	4920	6530	5220	6730	5200	6930	5200	7340	5160	7670	5030	

009	41	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	45	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	50	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	54	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	57	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	61	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	64	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	68	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	70	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	73	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	77	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	81	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	84	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	88	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	91	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	95	7800	6300	8630	6710	9220	7130	9500	7100	9790	7100	10360	7040	10830	6870
	99	7570	6120	8380	6520	8950	6920	9220	6890	9510	6890	10060	6840	10520	6670
102	7390	5970	8180	6360	8740	6760	9010	6730	9280	6730	9820	6670	10270	6510	
106	7190	5810	7960	6190	8500	6570	8760	6550	9030	6550	9550	6490	9990	6330	
109	7000	5650	7740	6020	8270	6400	8520	6370	8780	6370	9290	6310	9710	6160	

012	41	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	45	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	50	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	54	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	57	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	61	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	64	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	68	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	70	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	73	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	77	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	81	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	84	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	88	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	91	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	95	9850	8350	10900	8900	11640	9450	12000	9420	12360	9420	13080	9330	13680	9120
	99	9560	8110	10580	8640	11300	9180	11650	9150	12000	9150	12700	9060	13280	8860
102	9340	7920	10330	8440	11030	8960	11380	8930	11720	8930	12400	8840	12970	8650	
106	9080	7700	10050	8210	10730	8710	11060	8690	11400	8690	12060	8600	12610	8410	
109	8840	7490	9780	7980	10440	8480	10760	8450	11090	8450	11730	8370	12270	8180	

TC: Total Capacity [Btu/h]

SHC: Sensible Heat Capacity [Btu/h]

4 way cassette Type (MMU-UP*_1HP-UL)

unit size	outdoor air temp. ° FDB	Indoor air temp.													
		59 ° FWB		61 ° FWB		64 ° FWB		67 ° FWB		68 ° FWB		72 ° FWB		75 ° FWB	
		71 ° FDB		73 ° FDB		77 ° FDB		80 ° FDB		82 ° FDB		86 ° FDB		90 ° FDB	
		TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
015	41	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	45	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	50	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	54	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	57	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	61	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	64	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	68	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	70	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	73	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	77	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	81	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	84	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	88	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	91	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	95	12640	10640	13980	11330	14940	12040	15400	12000	15860	12000	16790	11890	17560	11620
	99	12270	10330	13570	11000	14510	11690	14950	11650	15400	11650	16300	11550	17050	11280
	102	11980	10090	13250	10740	14160	11410	14600	11380	15040	11380	15920	11270	16650	11020
106	11650	9810	12890	10450	13770	11100	14200	11060	14620	11060	15480	10960	16190	10710	
109	11340	9540	12540	10160	13400	10800	13810	10760	14230	10760	15060	10670	15750	10420	
018	41	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	45	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	50	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	54	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	57	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	61	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	64	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	68	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	70	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	73	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	77	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	81	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	84	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	88	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	91	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	95	15320	11600	16030	11920	17040	12410	18000	12800	18310	12840	19470	12670	20270	12200
	99	14880	11260	15570	11570	16550	12050	17480	12430	17780	12470	18910	12300	19680	11850
	102	14520	11000	15200	11300	16150	11760	17060	12130	17360	12170	18460	12010	19220	11570
106	14130	10700	14780	10990	15710	11440	16600	11800	16880	11840	17950	11680	18690	11250	
109	13740	10410	14380	10690	15280	11130	16150	11480	16420	11520	17460	11360	18180	10940	
024	41	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	45	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	50	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	54	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	57	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	61	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	64	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	68	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	70	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	73	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	77	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	81	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	84	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	88	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	91	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	95	20430	14960	21370	15370	22730	16000	24000	16500	24410	16550	25960	16340	27020	15720
	99	19838	14526	20750	14924	22071	15536	23304	16022	23702	16070	25207	15866	26236	15264
	102	19368	14182	20259	14571	21548	15168	22752	15642	23141	15689	24610	15490	25615	14903
106	18840	13790	19700	14170	20960	14750	22130	15210	22510	15260	23940	15070	24910	14490	
109	18330	13420	19170	13790	20390	14350	21530	14800	21900	14850	23290	14660	24240	14100	
030	41	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	45	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	50	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	54	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	57	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	61	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	64	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	68	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	70	25530	18670	26720	19190	28410	19970	30000	20600	30510	20650	32450	20400	33780	19630
	73	25530	18670												

4 way cassette Type (MMU-UP*__1HP-UL)

unit size	outdoor air temp. ° FDB	Indoor air temp.													
		59 ° FWB		61 ° FWB		64 ° FWB		67 ° FWB		68 ° FWB		72 ° FWB		75 ° FWB	
		71 ° FDB	73 ° FDB	73 ° FDB	73 ° FDB	77 ° FDB	77 ° FDB	80 ° FDB	80 ° FDB	82 ° FDB	82 ° FDB	86 ° FDB	86 ° FDB	90 ° FDB	90 ° FDB
		TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
036	41	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	45	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	50	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	54	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	57	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	61	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	64	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	68	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	70	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	73	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	77	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	81	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	84	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	88	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	91	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	95	30640	22390	32060	23010	34090	23950	36000	24700	36620	24770	38930	24450	40540	23540
	99	29750	21740	31130	22340	33100	23260	34960	23980	35560	24050	37800	23740	39360	22860
	102	29050	21230	30390	21810	32320	22700	34130	23420	34720	23480	36910	23180	38430	22320
106	28250	20640	29560	21220	31430	22080	33190	22770	33760	22840	35890	22540	37380	21700	
109	27480	20080	28760	20640	30580	21480	32290	22160	32850	22220	34920	21930	36360	21120	
042	41	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	45	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	50	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	54	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	57	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	61	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	64	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	68	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	70	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	73	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	77	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	81	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	84	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	88	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	91	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	95	35750	26660	37400	27380	39770	28500	42000	29400	42720	29480	45420	29100	47290	28020
	99	34710	25890	36320	26590	38620	27670	40780	28550	41480	28630	44100	28260	45920	27210
	102	33890	25270	35460	25960	37700	27020	39820	27870	40500	27950	43060	27590	44830	26560
106	32960	24580	34480	25240	36670	26280	38720	27110	39390	27180	41880	26830	43600	25830	
109	32070	23910	33550	24560	35670	25560	37670	26370	38320	26440	40740	26100	42420	25130	
048	41	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	45	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	50	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	54	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	57	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	61	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	64	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	68	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	70	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	73	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	77	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	81	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	84	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	88	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	91	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	95	40850	30460	42740	31290	45450	32580	48000	33600	48820	33690	51910	33260	54050	32020
	99	39670	29580	41500	30380	44130	31640	46610	32630	47400	32710	50400	32300	52480	31090
	102	38730	28880	40520	29660	43090	30890	45500	31850	46280	31940	49210	31530	51240	30350
106	37660	28080	39410	28850	41900	30040	44260	30980	45010	31060	47860	30670	49830	29520	
109	36640	27320	38340	28070	40770	29220	43060	30140	43790	30220	46560	29830	48480	28720	
054	41	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	45	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	50	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	54	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	57	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	61	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	64	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	68	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	36020
	70	45960	34270	48090	35210	51130	36650	54000	37800	54920	37900	58400	37420	60800	3

Heating capacity table


	Indoor air temp. °FDB					
Fahrenheit (°F)	62	65	68	70	72	75
Celsius (°C)	16.7	18.3	20	21.1	22.2	23.9
	Total capacity (TC) (kBtu/h)					
MMU-UP0071HP-UL	8.9	8.8	8.6	8.5	8.4	8.2
MMU-UP0091HP-UL	11.0	10.8	10.6	10.5	10.4	10.1
MMU-UP0121HP-UL	14.1	13.9	13.7	13.5	13.3	13.0
MMU-UP0151HP-UL	17.8	17.5	17.2	17.0	16.8	16.4
MMU-UP0181HP-UL	20.9	20.6	20.2	20.0	19.7	19.3
MMU-UP0241HP-UL	28.2	27.8	27.3	27.0	26.6	26.1
MMU-UP0301HP-UL	35.5	35.0	34.4	34.0	33.6	32.9
MMU-UP0361HP-UL	41.8	41.2	40.5	40.0	39.5	38.6
MMU-UP0421HP-UL	49.6	48.9	48.1	47.5	46.9	45.9
MMU-UP0481HP-UL	56.4	55.6	54.7	54.0	53.3	52.2
MMU-UP0541HP-UL	62.7	61.8	60.7	60.0	59.2	58.0

Notes: 1. These capacity tables can be used when selecting a VRF indoor unit. The actual capacity of the VRF system depends on factors such as the selected model of outdoor units, outdoor air temperature and piping length. Please confirm that the corrected capacity of the VRF system satisfies the required heat load.


Notes: 2. This is the capacity table of rated heating test condition of Outdoor 47°F Dry Bulb / 43°F Wet Bulb.

8. Air throw distance chart


MMU-UP*__1HPUL (*007 / 009)




MMU-UP*__1HP-UL (*012 / 015 / 018)




MMU-UP*__1HP-UL (*024 / 030)



MMU-UP0361HP-UL




MMU-UP*__1HP-UL (*042 / 048 / 054)




9. Sound data


Sound pressure spectrum




MMU-UP0071HP-UL / UP0091HP-UL




MMU-UP0121HP-UL / UP0151HP-UL / UP0181HP-UL




MMU-UP0241HP-UL




MMU-UP0301HP-UL



MMU-UP0361HP-UL




MMU-UP0421HP-UL / UP0481HP-UL / AP0541HP-UL




10. Accessories

Optional parts for 4-Way Cassette type



(Unit : in(mm))




No	Type	Model name	Qty/unit	Note
1	1.1 Ceiling panel	RBC-U32PGP-UL	1	White (2.5GY9.0/0.5)
	1.2 Ceiling panel (smart design)	RBC-U33P-UL	1	White (5PB9/1)
	1.3 Ceiling panel (smart design)	RBC-U33PB-UL	1	Black (RAL9005)
2	Spacer for height adjustment	TCB-SP1602UUL	1	2.0" (50)
3	Fresh-air chamber	TCB-GFC1602UUL	1	Use with TCB-GB1602UUL
4	Fresh-air inlet box	TCB-GB1602UUL	1	Connection = Dia. 3.9" (100)
5	Air-discharge direction kit	TCB-BC1602UUL	1	6-direction patterns
6	Auxiliary fresh air flange	TCB-FF101URUL	1	Connection = Dia.3.9" (100)

Combination pattern			Ceiling panel RBC-U32PGP-UL	Ceiling panel (smart design) RBC-U33P-UL	Ceiling panel (smart design, black) RBC-U33PB-UL	Wireless remote control kit RBC-AXU31UP-UL	Wireless remote control kit RBC-AXU33UP-UL	Wireless remote control kit RBC-AXU33UPB-UL	Spacer for height adjustment TCB-SP1602UUL	Fresh-air inlet box + Fresh-air chamber TCB-GB1602UUL + TCB-GFC1602UUL	Air-discharge direction kit TCB-BC1602UUL	Auxiliary fresh air flange TCB-FF101URUL	Occupancy sensor TCB-SIR33UP-UL
Panel	Ceiling panel	RBC-U32PGP-UL				OK			OK	OK	OK	OK	
	Ceiling panel (smart design)	RBC-U33P-UL					OK					OK	OK
	Ceiling panel (smart design,black)	RBC-U33PB-UL						OK				OK	
Wireless remote control kit		RBC-AXU31UP-UL	OK						OK	OK	OK	OK	
Wireless remote control kit		RBC-AXU33UP-UL		OK								OK	OK
Wireless remote control kit		RBC-AXU33UPB-UL			OK							OK	
Optional parts	Spacer for height adjustment	TCB-SP1602UUL	OK			OK				OK	OK	OK	
	Fresh-air inlet box + Fresh-air chamber	TCB-GB1602UUL + TCB-GFC1602UUL	OK			OK			OK		OK	OK	
	Air-discharge direction kit	TCB-BC1602UUL	OK			OK			OK	OK		OK	
	Auxiliary fresh air flange	TCB-FF101URUL	OK	OK	OK	OK	OK	OK	OK	OK	OK		OK
	Occupancy sensor	TCB-SIR33UP-UL		OK			OK					OK	

Appendix

1. Fresh-air chamber (TCB-GFC1602UUL)

Unit: in (mm)



Space required for installation

	A
007 to 030 type	14.0" (356)
036 to 054 type	16.5" (419)

2. Fresh-air inlet box (TCB-GB1602UUL)


Accessories

(The following parts are included.)


No.	Name		Qty	Remark
(1)	Outside air introduction port		1	
(2)	Outside air introduction port fixing metal part		1	
(3)	Duct flange Ø3.9" (100 mm)		1	
(4)	Mounting screws 0.16" × 0.4" (4 × 10 mm)		16	
(5)	Heat insulating material A		2	
(6)	Heat insulating material B		2	
(7)	Wind shield		1	
(8)	Installation manual		1	
(9)	Wire		1	

Installation


(Fig. 1)




(Fig. 2)



(Fig. 3)




Dimension



	A
007 to 030 type	14.1" (358)
036 to 054 type	16.6" (421)

Unit: in (mm)



NOTE

This inlet box shall be used with the fresh-air chamber.



3. Fresh Air Intake

Usage

Fresh air is taken by using Fresh-air chamber and Fresh-air inlet box. And also is subsidiarily taken by using Auxiliary fresh air flange through the knock-out hole of the indoor unit body.

Caution

1. Be sure to provide air return.
2. The fresh air shall be treated by heat reclaim ventilator or the like.
3. Recommended treated air temperature is 54 °F to 86 °F.
4. Be sure to decide the fresh air volume so that mixed suction air with fresh air keep operating temperature.
Provide an air filter in fresh air way to prevent sucking dust.
5. Be sure to insulate the fresh air duct.
In order to accelerate starting up in heating mode, implement pre-heating operation by cutting off Fresh Air Intake.
6. The operating sound might increase when fresh air intake.




Characteristics between air volume of branching duct and static pressure

Following fresh air intake ratio is available by using the booster fan.

1. Fresh-air inlet box with Fresh-air chamber
Up to 88 cfm and 10% of rated air volume
2. Auxiliary fresh air flange through the knock-out hole of the indoor unit body
Up to 24 cfm

Inter - lock circuit


1. Connect the driving relay of the duct fan (DC 12 V) between 1 and 6 on the indoor P.C.board.
Part indicated with a bold line is the connecting circuit.
After installation, implement a test run to check that the duct fan of the indoor unit start / stop simultaneously.
(Implement the test run following to the installation manual of the indoor unit.)



4. Auxiliary fresh air flange (TCB-FF101URUL)

Installation


- Using the knockout of the indoor unit main body, as a marker, cut off the flange with the heat insulator (styrol) with cutting pliers or cutter.




NOTE

When cutting off the styrol inside, be careful not to insert the cutter blade deeper than 1.2" (30mm). (Damage to the drain pan inside can cause water leakage.) Wear safety globes to carry out these works. Do not attempt with bare hands.


- A gap between the styrol and steel plate may cause a trouble such as condensation. Be sure to attach the attached heat insulator A first with it aligned to the screw hole, and then attach B, according to the right figure.
- Install the auxiliary fresh air flange to the indoor unit main body with attached 4 fixing screws.






Dimension



Fixing hole of indoor unit



Unit : in (mm)




Installation status of indoor unit


Duct fan

In order to take fresh air, provide the duct fan separately.

- Install the filter for fresh air
- Provide the check port beneath the duct fan for maintenance.
- Connect the duct fan and the indoor unit with interlock wiring.
- Provide the silencer to prevent the effect of noise.




5. Spacer for height adjustment (TCB-SP1602UUL)



	A
007 to 030 type	8.1" (206)
036 to 054 type	10.6" (269)


6. Air discharge direction kit (TCB-BC1602UUL)



Limited models only				
3-way air flow				
	Available for all models	Available for all models	Available only for 007 to 030 type	Available only for 036 to 054 type
2-way air flow				
	Available for all models	Available for all models	Available for all models	


7. Branching duct

Characteristics between air volume of branching duct and static pressure
In case of connecting dia.= 5.91 inch (150 mm) branching duct, static pressure is as follows.





	Model
①	007 to 018 type : 3 directions + 1 branch
②	024, 030 type : 3 directions + 1 branch
③	036 type : 3 directions + 1 branch
④	042, 48, 54 type : 3 directions + 1 branch
⑤	036 type : 3 directions + 2 branches
⑥	042, 48, 54 type : 3 directions + 2 branches

Cover method



Use air discharge direction kit (TCB-BC1602UUL) to cover the air discharge port.

Dimension



TOSHIBA CARRIER (THAILAND) CO.,LTD.

144/9 Moo 5, Bangkadi Industrial Park, Tivanon Road, Tambol Bangkadi,
Amphur Muang, Pathumthani 12000, Thailand

Copyright © 2023 TOSHIBA CARRIER (THAILAND), All Rights Reserved

Notice : Toshiba is committed to continuously improving its products to ensure the highest quality and reliability standard, and to meet local regulations and market requirements. All features and specifications are subject to change without prior notice.
