

# SMMS-*u* / SHRM-*u* VRF Indoor Unit MML-UP0071BH-UL - Floor Console - Recessed

**TOSHIBA**  
*Carrier*

## Submittal Data

Job Name \_\_\_\_\_ Location \_\_\_\_\_  
Tag \_\_\_\_\_



### SMMS-*u* / SHRM-*u* VRF Floor Console - Recessed Features

- R-410A Refrigerant
- Six sizes from 7,500 to 24,000 Btu/h
- Wiring connection on the left side
- Piping and drain can be routed from right side, bottom, or back
- Drain tray and drain hose ship with the unit for field installation
- Five-year parts limited warranty

|                                   |                    |  |
|-----------------------------------|--------------------|--|
| Indoor Unit Model                 | MML-UP0071BH-UL    |  |
| PERFORMANCE                       |                    |  |
| Cooling Rated Capacity            | Btu/h              | 7,500  |
| Heating Rated Capacity            | Btu/h              | 8,500  |
| Fan Type (Qty)                    |                    | Centrifugal (1)                                  |
| Airflow ( L / M / H )             | CFM                | 180 / 240 / 270                                  |
| Sound Pressure (L / M / H)        | dBA                | 33 / 36 / 40<br>(208V)<br>36 / 39 / 42<br>(230V) |
| ELECTRICAL                        |                    |  |
| Power Supply                      | V/Ph/Hz            | 208-230/1/60                                     |
| Power Consumption<br>(Input)      | kW                 | 0.047 (208V)<br>0.056 (230V)                     |
| Full Load Amps (FLA)              | A                  | 0.3  |
| Minimum Circuit Amps              | A                  | 0.4  |
| Maximum Overcurrent<br>Protection | A                  | 15   |
| Motor Type                        | AC Inverter Driven |  |
| Motor Watts                       |                    | 19   |

|   |                             |             |
|---|-----------------------------|-------------|
| <b>PHYSICAL DATA</b>                          |                             |             |
| Pipe Connection Size - Liquid (High Pressure) | in.                         | 1/4 (Flare) |
| Pipe Connection Size - Gas (Low Pressure)     | in.                         | 3/8 (Flare) |
| Pipe Connection Size - Drain (OD)             | in.                         | 0.8         |
| Refrigerant                                   | R-410A                      |             |
| External Finish                               | Zinc Hot Dipped Steel Plate |             |
| Unit Width                                    | in.                         | 29.3        |
| Unit Height                                   | in.                         | 23.6        |
| Unit Depth                                    | in.                         | 8.7         |
| Unit Net Weight                               | lb                          | 50.7        |

### ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS51E-ES / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL

# DIMENSIONAL DRAWING

## INDOOR UNIT FLOOR CONSOLE - RECESSED MML-UP0071BH-UL

