

SMMSu VRF u-Series Outdoor Unit MMY-MUP0961H1HT6P-UL—Heat Pump (Elite Heat)

TOSHIBA
Carrier

Submittal Data

Job Name _____ Location _____

Tag _____



A230327

SMMSu VRF Heat Pump (Elite Heat) Features

- Energy-efficient priority design
- Super-efficient heat exchanger
- Refrigerant cooling inverter system
- Intelligent VRF control
- Less refrigerant
- Space efficient design
- Configuration flexibility
- Wider Operating temperature range
- Comprehensive System construction solution
- Comprehensive Service solution

Header Unit Model		MMY-MUP0961H1HT6P-UL
PERFORMANCE		
Nominal Cooling Capacity†	Btu/h	96,000
Nominal Heating Capacity†	Btu/h	108,000
Maximum number of indoor units		17
Total Connected Indoor Unit Capacity		192
COOLING EFFICIENCY†		
EER (Non-Ducted)	Btu/Wh	13.1
Power Consumption (Non-Ducted)	kW	6.98
EER (Ducted)	Btu/Wh	13.3
Power Consumption (Ducted)	kW	6.89
HEATING EFFICIENCY†		
COP (Non-Ducted)	Btu/Wh	4.6
Power Consumption (Non-Ducted)	kW	6.51
COP (Ducted)	Btu/Wh	4.7
Power Consumption (Ducted)	kW	6.49
FAN		
Fan Type		Propeller
Airflow	CFM	7770
Motor Output	kW	0.33 x 2
ELECTRICAL		
Power Supply	V/Ph/Hz	460/3/60
MCA	A	24.9
MOCP	A	25

COMPRESSORS		
Type (Number)	Hermetic Twin Rotary (1)	
Motor Output	kW	6.3
PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	1/2 (Brazing)
Pipe Connection Size - Gas (Low Pressure)	in.	1-1/8 (Brazing)
Refrigerant	R-410A	
Factory Charge††	lb	19.8
External Finish	Munsell 1Y8.5/0.5	
Unit Width	in.	51.4
Unit Height	in.	66.5
Unit Depth	in.	31.1
Unit Net Weight	lb	721

LEGEND

EER	—	Energy Efficiency Ratio
COP	—	Coefficient of Performance
MCA	—	Minimum Circuit Amps
MOCP	—	Maximum Overcurrent Protection


†Rated per AHRI (Air-Conditioning, Heating and Refrigeration Institute) 210/240 Standard.

Cooling: Indoor 80°F (27°C) db/67°F (20°C) wb; Outdoor 95°F (35°C) db

Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db/43°F (6°C) wb

††Additional charge required.

(Unit:in(mm))



Edition Date: 06/23
Printed in U.S.A.

Replaces: New

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.