SMMSu / SHRMu VRF Indoor Unit MMU-UP0071MH-UL—Compact 4-Way-Cassette



Submittal Data

Job Name	Location
Tan	



SMMSu / SHRMu VRF Compact 4-Way Cassette Features

- R-410A refrigerant
- Five sizes from 7,500 to 18,000 Btu/h
- · Standard condensate pump with 25.0 in. lift capacity
- Quiet operation (as low as 31 dBA)
- · Independent louver control (fixed or swing)
- · Optional wired or wireless controls
- · Auto or manually set three fan speeds
- · Easy to remove cleanable filter
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMU-UP0071MH-UL		
PERFORMANCE				
Cooling Rated Capacity	Btu/h	7,500		
Heating Rated Capacity	Btu/h	8,500		
Fan Type (Qty)	Turbo (1)			
Airflow (H / M / L)	CFM	320 / 270 / 220		
Sound Pressure (H / M / L)	dBA	39 / 35 / 31		
ELECTRICAL				
Power Supply	V/Ph/Hz	208-230/1/60		
Power Consumption (Input)	kW	0.023		
Full Load Amps (FLA)	Α	0.4		
Minimum Circuit Amps (MCA)	Α	0.5		
Maximum Overcurrent Protection	Α	15		
MOTOR				
Motor Type	Motor Type			
Motor Watts	W	60		

PHYSICAL DATA				
Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)		
Pipe Connection Size - Gas (Low Pressure)	in.	3/8 (Flare)		
Pipe Connection Size - Drain (OD)	in.	1-1/4		
Pipe Connection Size - Drain (ID)	in.	1		
Refrigerant	•	R-410A		
External Finish	Mansell 5PB9/1			
Unit Width	in.	22-5/8		
Unit Height	in.	10-1/8		
Unit Depth	in.	22-5/8		
Unit Net Weight	lb	33.10		
Panel Width	in.	24-3/8		
Panel Height	in.	1/2		
Panel Depth	in.	24-3/8		
Panel Net Weight	lb	5.50		

ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- □ Simple Wired Remote Control RBC-AS41UL
- □ Wireless Remote Control Kit RBC-AXU31IM-UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Grille Panel RBC-UM21PG-UL
- ☐ Occupy Sensor RCB-SIR41UM-E
- ☐ Auxiliary Fresh Air Flange TCB-FF101URUL

DIMENSIONAL DRAWING INDOOR UNIT COMPACT 4-WAY CASSETTE MMU-UP0071MH-UL



