

# SMMSe / SHRMe VRF Indoor Unit MMD-AP0366HPUL—HIGH STATIC DUCT

**TOSHIBA**  
*Carrier*

## Submittal Data

Job Name \_\_\_\_\_ Location \_\_\_\_\_  
Tag \_\_\_\_\_



### SMMSe / SHRMe VRF High Static Ducted Features

- R-410A refrigerant
- Seven sizes from 24,000 to 96,000 Btu/h
- Quiet operation, as low as 30 dBA
- Rear return
- 208/230 V PSC (Permanent Split Capacitor) motor
- Optional wired or wireless controls
- Five-year parts limited warranty
- Standard condensate pump with 24.3 in. lift capability

|                                       |                 |                       |
|---------------------------------------|-----------------|-----------------------|
| INDOOR UNIT MODEL                     |                 | MMD-AP0366HPUL        |
| PERFORMANCE                           |                 |                       |
| Cooling Rated Capacity                | Btu/h           | 36,000                |
| Heating Rated Capacity                | Btu/h           | 40,000                |
| Fan Type (Qty)                        | Centrifugal (2) |                       |
| Airflow, Standard Range (H / M / L)   | CFM             | 1130 / 918 / 789      |
| Sound Pressure, 208V/230 (H / M / L)  | dBA             | 51 / 46 / 41          |
| External Static Pressure (L / M / H*) | in.wg           | 0.2-1.0 (7 Step)      |
| FILTER (Optional, Accessory Required) |                 |                       |
| Type                                  | Washable        |                       |
| Quantity                              | 1               |                       |
| MERV Corresponding Value              | 5               |                       |
| Dimensions (W x L x D)                | in.             | 10-5/8 x 27-5/8 x 5/8 |
| ELECTRICAL                            |                 |                       |
| Power Supply                          | V/Ph/Hz         | 208-230/1/60          |
| Power Consumption (208/230 V)         | kW              | 0.35                  |
| Full Load Amps (FLA)                  | A               | 2.75                  |
| Minimum Circuit Amps (MCA)            | A               | 3.44                  |
| Maximum Overcurrent Protection (MOCP) | A               | 15.0                  |

|   |                             |             |
|---|-----------------------------|-------------|
| MOTOR   |                             |             |
| Motor Type                                    | DC                          |             |
| Motor Watts                                   | W                           | 350         |
| PHYSICAL DATA                                 |                             |             |
| Pipe Connection Size - Liquid (High Pressure) | in.                         | 3/8 (Flare) |
| Pipe Connection Size - Gas (Low Pressure)     | in.                         | 5/8 (Flare) |
| Pipe Connection Size - Drain (OD)             | in.                         | 1-1/4       |
| Pipe Connection Size - Drain (ID)             | in.                         | 1           |
| Refrigerant                                   | R-410A                      |             |
| External Finish                               | Zinc Hot Dipped Steel Plate |             |
| Unit Width                                    | in.                         | 55-1/8      |
| Unit Height                                   | in.                         | 11-3/4      |
| Unit Depth                                    | in.                         | 29-1/2      |
| Net Weight                                    | lb                          | 98          |

\* Low, Medium, High Taps. Medium Tap set from factory.

### ACCESSORIES

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL
- Filter - TCB-LK1401D-E

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

# DIMENSIONAL DRAWING

## INDOOR UNIT HIGH STATIC DUCT MMD-AP0366HPUL

