SMMSu / SHRMu VRF Indoor Unit MMD-UP0541BHP-UL—Concealed Duct



Submittal Data

Job Name	Location
Tag	



SMMSu / SHRMu CONCEALED DUCT FEATURES

- R-410A Refrigerant
- Twelve sizes from 7,500 to 54,000 Btu/h
- · Standard condensate pump with 24.3 in. lift capability
- · Quiet operation, as low as 30 dBA
- · Rear return configurable for bottom return
- · Auto or manually set three fan speeds
- Five-year parts limited warranty

INDOOR UNIT MODEL				
PERFORMANCE				
Btu/h 54,000				
Btu/h	60,000			
Centrifugal (1)				
in. WG	0.6 (Factory default)			
	0.8 (Max)			
CFM	1177 / 1024 / 883			
dBA	47 / 42 / 38			
FILTER (Standard)				
Washable				
2				
5				
in. 10-5/8 x 27-5/8 x 5/				
ELECTRICAL				
V/Ph/Hz	208-230/1/60			
kW	0.34			
Α	2.85			
Α	3.56			
А	15.0			
	in. WG dBA			

MOTOR			
Motor Type	DC		
Motor Watts	250		
PHYSICAL DATA	•		
Pipe Connection Size - Liquid	in.	3/8 (Flare)	
Pipe Connection Size - Suction	in.	5/8 (Flare)	
Pipe Connection Size - Drain (OD)	in.	1-1/4	
Pipe Connection Size - Drain (ID)	in.	1	
Refrigerant		R-410A	
External Finish	Zinc F	Hot Dipped Steel Plate	
Unit Width	in.	55-1/4	
Unit Height	in.	10-7/8	
Unit Depth	in.	29-5/8	
Net Weight	lb	93	

ACCESSORIES

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Auxiliary OA Flange TCB-FF151US-UL
- ☐ Zoning Duct Flange TCB-SF56C6BP-UL
- ☐ Filter Kit TCB-FW561DP-UL

© 2023 Carrier. All rights reserved.

Edition Date: 01/23

Form No: MMD-UP0541BHP-UL_01
Replaces: MMD-AP0546BHPUL 01

A Carrier Company

Printed in U.S.A.

replaces. WIVID 711 03-10BH CE_01

^{*} The actual values in an external operating environment are generally higher than the indicated values due to ambient noise.

DIMENSIONAL DRAWING CONCEALED DUCT MMD-UP0541BHP-UL



