# SMMSu / SHRMu VRF Indoor Unit MMD-UB0361BHP-UL—Concealed Duct



## **Submittal Data**

Job Name <sub>.</sub>	Location	
Tag		



#### SMMSu / SHRMu CONCEALED DUCT FEATURES

- R-454B Refrigerant
- Twelve sizes from 7,500 to 54,000 Btu/h
- · Standard condensate pump with 24.3 in. lift capability
- · Quiet operation, as low as 30 dBA
- Rear return configurable for bottom return
- · Auto or manually set three fan speeds
- · Five-year parts limited warranty

INDOOR UNIT MODEL	MMD-UB0361BHP-UL			
PERFORMANCE				
Cooling Rated Capacity	Btu/h	36,000		
Heating Rated Capacity	Btu/h	40,000		
Fan Type (Qty)	Centrifugal (1)			
External Static Pressure	in.	0.6 (Factory default)		
(ESP)		0.8 (Max)		
Standard Airflow (H / M / L)	CFM	1130 / 955 / 810		
Sound Pressure (H / M / L)*	dBA	46 / 41 / 37		
ELECTRICAL				
Power Supply	V/Ph/Hz	208-230/1/60		
Power Consumption (Input)	kW	0.33		
Full Load Amps (FLA)	Α	2.71		
Minimum Circuit Amps (MCA)	Α	3.39		
Maximum Overcurrent Protection (MOCP)	Α	15.0		

MOTOR				
Motor Type		DC		
Motor Watts		250		
PHYSICAL DATA				
Pipe Connection Size - Liquid	in.	3/8 (Flare)		
Pipe Connection Size - Suction	in.	5/8 (Flare)		
Pipe Connection Size - Drain	in.	VP25		
Refrigerant		R-454B		
External Finish	Zinc F	Zinc Hot Dipped Steel Plate		
Unit Width	in.	55-1/8		
Unit Height	in.	10-7/8		
Unit Depth	in.	29-1/2		
Net Weight	lb	93		

#### **ACCESSORIES**

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-ASCU11-UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Auxiliary OA Flange TCB-FF151US-UL
- ☐ Zoning Duct Flange TCB-SF56C6BP-UL
- ☐ Filter Kit TCB-FW561DP-UL

<sup>\*</sup> The actual values in an external operating environment are generally higher than the indicated values due to ambient noise.

### **DIMENSIONAL DRAWING CONCEALED DUCT MMD-UB0361BHP-UL**



