SMMSu / SHRMu VRF Indoor Unit MMU-UP0071HP-UL—4-Way-Cassette



Submittal Data

Job Name _	 Location	
Tan _		



SMMSu / SHRMu VRF 4-Way Cassette Features

- · R-410A refrigerant
- Eleven sizes from 7,500 to 54,000 Btu/h
- · Optional fresh air intake
- · Quiet operation (as low as 29 dBA)
- · Standard condensate pump with 26 in. lift capacity
- · Independent louver control (fixed or swing)
- · Optional wired or wireless controls
- · Auto or manually set three fan speeds
- · Easy to remove cleanable filter
- · Five-year parts limited warranty

INDOOR UNIT MODEL	MMU-UP0071HP-UL				
PERFORMANCE					
Cooling Rated Capacity	Btu/h	7,500			
Heating Rated Capacity	Btu/h	8,500			
Fan Type (Qty)	Turbo (1)				
Airflow (H, M, L)	CFM	470 / 430 / 400			
Sound Pressure (H, M, L)	dBA	32.5 / 30.5 / 29			
ELECTRICAL					
Power Supply	V/Ph/Hz	208-230/1/60			
Power Consumption (Input)	kW	0.021			
Full Load Amps (FLA)	Α	0.63			
Minimum Circuit Amps (MCA)	Α	0.79			
Maximum Overcurrent Protection (MOCP)	Α	15.0			
MOTOR					
Motor Type	DC				
Motor Watts	W	60			

PHYSICAL DATA					
Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)			
Pipe Connection Size - Gas (Low					
Pressure)	in.	3/8 (Flare)			
Pipe Connection Size - Drain (OD)	in.	1-1/4			
Pipe Connection Size - Drain (ID)	in.	1			
Refrigerant		R-410A			
External Finish	Zinc Hot Dipped Steel Plate				
Unit Width	in.	33-1/8			
Unit Height	in.	10-1/8			
Unit Depth	in.	33-1/8			
Unit Net Weight	lb	45			
Panel Width	in.	37-3/8			
Panel Height	in.	1-3/16			
Panel Depth	in.	37-3/8			
Panel Net Weight	lb	10			
FILTER (Included)					
Туре		Washable			
Quantity	1				
MERV rating	5				
Dimensions	in.	21-3/8 x 21-7/8 x 3/4			

ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable)
 RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Wireless Receiver Kit RBC-AXU33UP-UL
- ☐ Wireless Controller Kit RBC-AXU31UP-UL
- ☐ Remote Sensor TCB-TC41U-UL

		_			
п	Crilla	Danal		U32PGP	1 11
11	Carme	ranei	KDU-	いいくてはて	-()

- ☐ Spacer for Height Adjustment TCB-SP1602UUL
- ☐ Air Discharge Direction Kit TCB-BC1602UUL
- ☐ Fresh Air Chamber TCB-GFC1602UUL
- ☐ Fresh Air Inlet Box TCB-GB1602UUL
- ☐ Auxiliary Fresh Air Flange TCB-FF101URUL
- ☐ Occupancy Sensor TCB-SIR33UP-UL

© 2023 Carrier. All rights reserved.

Edition Date: 01/23 Printed in U.S.A. Form No: MMU-UP0071HP-UL 01

DIMENSIONAL DRAWING INDOOR UNIT 4-WAY CASSETTE MMU-UP0071HP-UL





