SMMSu / SHRMu VRF Indoor Unit MMU-UP0091MHP-UL—Compact 4-Way-Cassette Carrier



Submittal Data

Job Name_	 Location	
Tag		



SMMSu / SHRMu VRF Compact 4-Way Cassette Features

- R-410A refrigerant
- Five sizes from 7,500 to 18,000 Btu/h
- · Standard condensate pump with 25.0 in. lift capacity
- Quiet operation (as low as 26 dBA)
- · Independent louver control (fixed or swing)
- · Optional wired or wireless controls
- · Auto or manually set five fan speeds
- · Easy to remove cleanable filter
- · Five-year parts limited warranty

INDOOR UNIT MODEL					
PERFORMANCE					
Btu/h	9,500				
Btu/h	10,500				
Turbo (1)					
CFM	340 / 230 / 175				
dBA	38 / 30 / 26				
ELECTRICAL					
V/Ph/Hz	208-230/1/60				
kW	0.024				
Α	0.34				
Α	0.43				
Α	15				
MOTOR					
DC Inverter Driven					
W	60				
	Btu/h CFM dBA V/Ph/Hz kW A A A				

PHYSICAL DATA				
Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)		
Pipe Connection Size - Gas (Low Pressure)	in.	3/8 (Flare)		
Pipe Connection Size - Drain (OD)	in.	1-1/4		
Pipe Connection Size - Drain (ID)	in.	1		
Refrigerant	•	R-410A		
External Finish	Mansell 5PB9/1			
Unit Width	in.	22-5/8		
Unit Height	in.	10-1/8		
Unit Depth	in.	22-5/8		
Unit Net Weight	lb	35.30		
Panel Width	in.	24-3/8		
Panel Height	in.	2-1/4		
Panel Depth	in.	24-3/8		
Panel Net Weight	lb	6.60		

ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AWSU52-UL
- Simple Wired Remote Control RBC-ASCU11-UL
- Wireless Remote Control Kit RBC-AXU31IM-UL, RBC-AXU31UMP-UL, RBC-AXU31UMPB-UL
- Remote Sensor TCB-TC41U-UL
- Grille Panel RBC-UM21PG-UL, RBC-UM21P-UL, RBC-UM21PB-UL
- Occupy Sensor TCB-SIR41UM-E and TCB-SIR41UMP-UL
- Auxiliary Fresh Air Flange TCB-FF101URUL

DIMENSIONAL DRAWING INDOOR UNIT COMPACT 4-WAY CASSETTE MMU-UP0091MHP-UL



