

SMMSe / SHRMe VRF Indoor Unit MMD-AP0246HPUL—HIGH STATIC DUCT



Submittal Data

Job Name _____ Location _____
Tag _____



SMMSe / SHRMe VRF High Static Ducted Features

- R-410A refrigerant
- Seven sizes from 24,000 to 96,000 Btu/h
- Quiet operation, as low as 30 dBA
- Rear return
- 208/230V DC motor
- Optional wired or wireless controls
- Five-year parts limited warranty
- Standard condensate pump with 24.3 in. lift capability

INDOOR UNIT MODEL	MMD-AP0246HPUL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	24,000
Heating Rated Capacity	Btu/h	27,000
Fan Type (Qty)	Centrifugal (2)	
Airflow, Standard Range (H / M / L)	CFM	706 / 571 / 471
Sound Pressure, 208V/230 (H / M / L)	dBA	45 / 35 / 30
External Static Pressure (ESP)	in.WG	0.8 (Factory Default)
		1.0 (Max.)
FILTER (Optional, Accessory Required)		
Type	Washable	
Quantity	1	
MERV Corresponding Value	5	
Dimensions (W x L x D)	in.	10-5/8 x 19-5/8 x 5/8
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (208/230 V)	kW	0.255
Full Load Amps (FLA)	A	2.07
Minimum Circuit Amps (MCA)	A	2.59
Maximum Overcurrent Protection (MOCP)	A	15.0

MOTOR		
Motor Type	DC	
Motor Watts	W	250
PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1-1/4
Pipe Connection Size - Drain (ID)	in.	1
Refrigerant	R-410A	
External Finish	Zinc Hot Dipped Steel Plate	
Unit Width	in.	39-3/8
Unit Height	in.	11-3/4
Unit Depth	in.	29-5/8
Net Weight	lb	80

ACCESSORIES

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL
- Filter - TCB-LK801D-E

DIMENSIONAL DRAWING

INDOOR UNIT HIGH STATIC DUCT MMD-AP0246HPUL

