SMMSe / SHRMe VRF Indoor Unit MMD-AP0306HPUL—HIGH STATIC DUCT



Submittal Data

Job Name	 Location
Tag	



SMMSe / SHRMe VRF High Static Ducted Features

- R-410A refrigerant
- Seven sizes from 24,000 to 96,000 Btu/h
- · Quiet operation, as low as 30 dBA
- Rear return
- 208/230V DC motor
- · Optional wired or wireless controls
- · Five-year parts limited warranty
- · Standard condensate pump with 24.3 in. lift capability

INDOOR UNIT MODEL	MMD-AP0306HPUL			
PERFORMANCE				
Cooling Rated Capacity	Btu/h	30,000		
Heating Rated Capacity	Btu/h	34,000		
Fan Type (Qty)		Centrifugal (2)		
Airflow, Standard Range (H / M / L)	CFM	883 / 795 / 706		
Sound Pressure, 208V/230 (H / M / L)	dBA	50 / 46 / 43		
External Static Pressure (ESP)	in.WG	0.8 (Factory Default)		
External Static Flessure (ESF)		1.0 (Max.)		
FILTER (Optional, Accessory Required)				
Туре		Washable		
Quantity	1			
MERV Corresponding Value	5			
Dimensions (W x L x D)	in.	10-5/8 x 19-5/8 x 5/8		
ELECTRICAL				
Power Supply	V/Ph/ Hz	208-230/1/60		
Power Consumption (208/230 V)	kW	0.295		
Full Load Amps (FLA)	Α	2.39		
Minimum Circuit Amps (MCA)	Α	2.99		
Maximum Overcurrent Protection (MOCP)	Α	15.0		

MOTOR				
MOTOR	T			
Motor Type		DC		
Motor Watts	W	250		
PHYSICAL DATA				
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)		
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)		
Pipe Connection Size - Drain (OD)	in.	1-1/4		
Pipe Connection Size - Drain (ID)	in.	1		
Refrigerant	R-410A			
External Finish	Zinc Hot Dipped Steel Plate			
Unit Width	in.	39-3/8		
Unit Height	in.	11-3/4		
Unit Depth	in.	29-5/8		
Net Weight	lb	80		

ACCESSORIES

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- Remote Sensor TCB-TC41LUL
- ☐ Wired Remote Controller RBC-AMT32UL
- ☐ Filter TCB-LK801D-E

DIMENSIONAL DRAWING INDOOR UNIT HIGH STATIC DUCT MMD-AP0306HPUL



