# SMMSu / SHRMu VRF Indoor Unit MMD-UP0361BHP-UL—Concealed Duct



### **Submittal Data**

Job Name	Location
Tag	



#### SMMSu / SHRMu CONCEALED DUCT FEATURES

- R-410A Refrigerant
- Twelve sizes from 7,500 to 54,000 Btu/h
- · Standard condensate pump with 24.3 in. lift capability
- · Quiet operation, as low as 30 dBA
- · Rear return configurable for bottom return
- · Auto or manually set three fan speeds
- · Five-year parts limited warranty

	INDOOR UNIT MODEL		MMD-UP0361BHP-UL		
-	PERFORMANCE				
_	Cooling Rated Capacity	Btu/h	36,000		
_	Heating Rated Capacity	Btu/h	40,000		
_	Fan Type (Qty)	Centrifugal (1)			
	External Static Pressure (ESP)	in. WG	0.6 (Factory default)		
			0.8 (Max)		
	Standard Airflow (H / M / L)	CFM	1130 / 954 / 812		
	Sound Pressure (H / M / L)*	dBA	46 / 41 / 37		
FILTER (Standard)					
_	Type		Washable		
_	Quantity	5			
	MERV Corresponding Value				
	Dimensions (W x L x D)	in.	10-5/8 x 27-5/8 x 5/8		
	ELECTRICAL				
_	Power Supply	V/Ph/Hz	208-230/1/60		
	Power Consumption (Input)	kW	0.33		
	Full Load Amps (FLA)	Α	2.71		
	Minimum Circuit Amps (MCA)	Α	3.39		
_	Maximum Overcurrent Protection (MOCP)	Α	15.0		

MOTOR				
Motor Type	DC			
Motor Watts	250			
PHYSICAL DATA				
Pipe Connection Size - Liquid	in.	3/8 (Flare)		
Pipe Connection Size - Suction	in.	5/8 (Flare)		
Pipe Connection Size - Drain (OD)	in.	1-1/4		
Pipe Connection Size - Drain (ID)	in.	1		
Refrigerant		R-410A		
External Finish	Zinc F	Hot Dipped Steel Plate		
Unit Width	in.	55-1/4		
Unit Height	in.	10-7/8		
Unit Depth	in.	29-5/8		
Net Weight	lb	93		

#### **ACCESSORIES**

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Auxiliary OA Flange TCB-FF151US-UL
- ☐ Zoning Duct Flange TCB-SF56C6BP-UL
- ☐ Filter Kit TCB-FW561DP-UL

© 2023 Carrier. All rights reserved.

Edition Date: 01/23

Form No: MMD-UP0361BHP-UL\_01

A Carrier Company

Printed in U.S.A.

Replaces: MMD-AP0366BHPUL 01

<sup>\*</sup> The actual values in an external operating environment are generally higher than the indicated values due to ambient noise.

## DIMENSIONAL DRAWING CONCEALED DUCT MMD-UP0361BHP-UL



