SMMSu / SHRMu VRF Indoor Unit MMU-UP0121MH-UL—Compact 4-Way-Cassette



Submittal Data

Job Name ₋	Location	
Tag		



SMMSu / SHRMu VRF Compact 4-Way Cassette Features

- R-410A refrigerant
- Five sizes from 7,500 to 18,000 Btu/h
- · Standard condensate pump with 25.0 in. lift capacity
- Quiet operation (as low as 31 dBA)
- · Independent louver control (fixed or swing)
- · Optional wired or wireless controls
- · Auto or manually set three fan speeds
- · Easy to remove cleanable filter
- · Five-year parts limited warranty

INDOOR UNIT MODEL	MMU-UP0121MH-UL				
PERFORMANCE					
Cooling Rated Capacity	Btu/h	12,000			
Heating Rated Capacity	Btu/h	13,500			
Fan Type (Qty)	Turbo (1)				
Airflow (H / M / L)	CFM	350 / 300 / 240			
Sound Pressure (H / M / L)	dBA	40 / 36 / 32			
ELECTRICAL					
Power Supply	V/Ph/Hz	208-230/1/60			
Power Consumption (Input)	kW	0.027			
Full Load Amps (FLA)	Α	0.4			
Minimum Circuit Amps (MCA)	Α	0.5			
Maximum Overcurrent Protection	Α	15			
MOTOR					
Motor Type	DC Inverter Driven				
Motor Watts	W	60			

PHYSICAL DATA				
Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)		
Pipe Connection Size - Gas (Low Pressure)	in.	3/8 (Flare)		
Pipe Connection Size - Drain (OD)	in.	1-1/4		
Pipe Connection Size - Drain (ID)	in.	1		
Refrigerant		R-410A		
External Finish M		ansell 5PB9/1		
Unit Width	in.	22-5/8		
Unit Height	in.	10-1/8		
Unit Depth	in.	22-5/8		
Unit Net Weight	lb	33.10		
Panel Width	in.	24-3/8		
Panel Height	in.	1/2		
Panel Depth	in.	24-3/8		
Panel Net Weight	lb	5.50		

ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Wireless Remote Control Kit RBC-AXU31IM-UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Grille Panel RBC-UM21PG-UL
- ☐ Occupy Sensor RCB-SIR41UM-E
- ☐ Auxiliary Fresh Air Flange TCB-FF101URUL

DIMENSIONAL DRAWING INDOOR UNIT COMPACT 4-WAY CASSETTE MMU-UP0121MH-UL



