


SMMSe / SHRMe VRF Indoor Unit MMD-AP0486HPUL—HIGH STATIC DUCT

TOSHIBA
Carrier

Submittal Data

Job Name _____ Location _____
Tag _____



SMMSe / SHRMe VRF High Static Ducted Features

- R-410A refrigerant
- Seven sizes from 24,000 to 96,000 Btu/h
- Quiet operation, as low as 30 dBA
- Rear return
- 208/230 V PSC (Permanent Split Capacitor) motor
- Optional wired or wireless controls
- Five-year parts limited warranty
- Standard condensate pump with 24.3 in. lift capability

INDOOR UNIT MODEL		MMD-AP0486HPUL
PERFORMANCE		
Cooling Rated Capacity	Btu/h	48,000
Heating Rated Capacity	Btu/h	54,000
Fan Type (Qty)		Centrifugal (2)
Airflow, Standard Range (H / M / L)	CFM	1236 / 1024 / 836
Sound Pressure (H / M / L)	dBA	52 / 47 / 42
External Static Pressure (L / M / H*)	in.wg	0.2-1.0 (7 Step)
FILTER (Optional, Accessory Required)		
Type		Washable
Quantity		1
MERV Corresponding Value		5
Dimensions (W x L x D)	in.	10-5/8 x 27-5/8 x 5/8
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (208/230 V)	kW	0.385
Full Load Amps (FLA)	A	3.10
Minimum Circuit Amps (MCA)	A	3.88
Maximum Overcurrent Protection (MOCP)	A	15.0

MOTOR		
Motor Type		DC
Motor Watts	W	350
PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1-1/4
Pipe Connection Size - Drain (ID)	in.	1
Refrigerant		R-410A
External Finish		Zinc Hot Dipped Steel Plate
Unit Width	in.	55-1/5
Unit Height	in.	11-3/4
Unit Depth	in.	29-5/8
Net Weight	lb	98

* Low, Medium, High Taps. Medium Tap set from factory.

ACCESSORIES

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL
- Filter - TCB-LK1401D-E

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

