# SMMSu / SHRMu VRF Indoor Unit MMD-UP0211BHP-UL—Concealed Duct



## **Submittal Data**

Job Name _	Location	
Tan		



#### SMMSu / SHRMu CONCEALED DUCT FEATURES

- R-410A Refrigerant
- Twelve sizes from 7,500 to 54,000 Btu/h
- · Standard condensate pump with 24.3 in. lift capability
- · Quiet operation, as low as 30 dBA
- Rear return configurable for bottom return
- · Auto or manually set three fan speeds
- · Five-year parts limited warranty

INDOOR UNIT MODEL	MMD-UP0211BHP-UL						
PERFORMANCE							
Cooling Rated Capacity	Btu/h	21,000					
Heating Rated Capacity	Btu/h	24,000					
Fan Type (Qty)	Centrifugal (1)						
External Static Pressure	in. WG	0.6 (Factory default)					
(ESP)		0.8 (Max)					
Standard Airflow (H / M / L)	CFM	706 / 583 / 512					
Sound Pressure (H / M / L)*	dBA	44 / 34 / 30					
FILTER (Standard)							
Туре	Washable						
Quantity	2						
MERV Corresponding Value	5						
Dimensions (W x L x D)	in.	10-5/8 x 27-5/8 x 5/8					
ELECTRICAL							
Power Supply	V/Ph/Hz	208-230/1/60					
Power Consumption (Input)	kW	0.21					
Full Load Amps (FLA)	Α	1.78					
Minimum Circuit Amps (MCA)	Α	2.23					
Maximum Overcurrent	Α	15.0					

MOTOR					
Motor Type		DC			
Motor Watts		150			
PHYSICAL DATA					
Pipe Connection Size - Liquid		3/8 (Flare)			
Pipe Connection Size - Suction		5/8 (Flare)			
Pipe Connection Size - Drain (OD)	in.	1-1/4			
Pipe Connection Size - Drain (ID)	in.	1			
Refrigerant	R-410A				
External Finish	Zinc Hot Dipped Steel Plate				
Unit Width	in.	55-1/4			
Unit Height	in.	10-7/8			
Unit Depth	in.	29-5/8			
Net Weight	lb	93			

#### **ACCESSORIES**

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL
- ☐ Auxiliary OA Flange TCB-FF151US-UL
- ☐ Zoning Duct Flange TCB-SF56C6BP-UL
- ☐ Filter Kit TCB-FW561DP-UL

© 2023 Carrier. All rights reserved.

Edition Date: 01/23

Form No: MMD-UP0211BHP-UL\_01

A Carrier Company

Printed in U.S.A.

Replaces: MMD-AP0216BHPUL 01

<sup>\*</sup> The actual values in an external operating environment are generally higher than the indicated values due to ambient noise.

### **DIMENSIONAL DRAWING CONCEALED DUCT MMD-UP0211BHP-UL**



