## SMMSu VRF u-Series Outdoor Unit MMY-MUP0961HT6P-UL—Heat Pump



# **Submittal Data**

Job Name _	 Location
Tan _	



A230327

Header Unit Model	MMY-MUP0961HT6P-UL			
PERFORMANCE				
Nominal Cooling Capacity†	Btu/h	96,000		
Nominal Heating Capacity†	Btu/h	108,000		
Maximum number of indoor units		17		
Total Connected Indoor Unit Capac	ity	192		
COOLING EFFICIENCY†				
EER (Non-Ducted)	Btu/Wh	11.80		
Power Consumption (Non-Ducted)	kW	7.60		
EER (Ducted)		12.60		
Power Consumption (Ducted)	kW	6.83		
HEATING EFFICIENCY†				
COP (Non-Ducted)	Btu/Wh	11.80		
Power Consumption (Non-Ducted)	kW	6.96		
COP (Ducted)	Btu/Wh	3.83		
Power Consumption (Ducted)		7.04		
FAN				
Fan Type		Propeller		
Airflow	CFM	6180		
Motor Output	kW	0.59 x 1		
ELECTRICAL				
Power Supply	V/Ph/Hz	460/3/60		
MCA	Α	17.5		
MOCP	Α	20		

#### **SMMSu VRF Heat Pump Features**

- · Energy-efficient priority design
- · Super-efficient heat exchanger
- · Refrigerant cooling inverter system
- Intelligent VRF control
- · Less refrigerant
- · Space efficient design
- · Configuration flexibility
- · Wider Operating temperature range
- Comprehensive System construction solution
- · Comprehensive Service solution

COMPRESSORS				
Type (Number)		Hermetic Twin Rotary (1)		
Motor Output	kW	6.2		
PHYSICAL DATA				
Pipe Connection Size - Liquid (High Pressure)	in.	1/2 (Brazing)		
Pipe Connection Size - Gas (Low Pressure)	in.	7/8 (Brazing)		
Refrigerant		R-410A		
Factory Charge††	lb	13.2		
External Finish	Munsell 1Y8.5/0.5			
Unit Width	in.	39.6		
Unit Height	in.	66.5		
Unit Depth	in.	31.1		
Unit Net Weight	lb	533		

#### **LEGEND**

EEK	_	Energy Eπiciency Ratio
COP	_	Coefficient of Performance
MCA	_	Minimum Circuit Amps
MOCP	_	Maximum Overcurrent Protectio

†Rated per AHRI (Air-Conditioning, Heating and Refrigeration Institute) 1230

Cooling: Indoor 80°F (27°C) db/67°F (20°C) wb; Outdoor 95°F (35°C) db Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db/43°F (6°C) wb ††Additional charge required.

### OUTDOOR UNIT HEAT PUMP MMY-MUP0961HT6P-UL **DIMENSIONAL DRAWING**



