

SMMSu VRF u-Series Outdoor Unit MMY-MUP1201HT9P-UL—Heat Pump

TOSHIBA
Carrier

Submittal Data

Job Name _____ Location _____

Tag _____



A230327

SMMSu VRF Heat Pump Features

- Energy-efficient priority design
- Super-efficient heat exchanger
- Refrigerant cooling inverter system
- Intelligent VRF control
- Less refrigerant
- Space efficient design
- Configuration flexibility
- Wider Operating temperature range
- Comprehensive System construction solution
- Comprehensive Service solution

Header Unit Model		MMY-MUP1201HT9P-UL
PERFORMANCE		
Nominal Cooling Capacity†	Btu/h	120,000
Nominal Heating Capacity†	Btu/h	135,000
Maximum number of indoor units		21
Total Connected Indoor Unit Capacity		240
COOLING EFFICIENCY†		
EER (Non-Ducted)	Btu/Wh	11.10
Power Consumption (Non-Ducted)	kW	10.00
EER (Ducted)	Btu/Wh	11.70
Power Consumption (Ducted)	kW	8.66
HEATING EFFICIENCY†		
COP (Non-Ducted)	Btu/Wh	4.09
Power Consumption (Non-Ducted)	kW	8.99
COP (Ducted)	Btu/Wh	3.83
Power Consumption (Ducted)	kW	8.79
FAN		
Fan Type		Propeller
Airflow	CFM	7770
Motor Output	kW	0.33 x 2
ELECTRICAL		
Power Supply	V/Ph/Hz	230/3/60
MCA	A	50.5
MOCP	A	60

COMPRESSORS		
Type (Number)		Hermetic Triple Rotary (1)
Motor Output	kW	8.0
PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	1/2 (Brazeing)
Pipe Connection Size - Gas (Low Pressure)	in.	1-1/8 (Brazeing)
Refrigerant		R-410A
Factory Charge††	lb	19.8
External Finish		Munsell 1Y8.5/0.5
Unit Width	in.	51.4
Unit Height	in.	66.5
Unit Depth	in.	31.1
Unit Net Weight	lb	725

LEGEND

EER	—	Energy Efficiency Ratio
COP	—	Coefficient of Performance
MCA	—	Minimum Circuit Amps
MOCP	—	Maximum Overcurrent Protection


†Rated per AHRI (Air-Conditioning, Heating and Refrigeration Institute) 1230 Standard.

Cooling: Indoor 80°F (27°C) db/67°F (20°C) wb; Outdoor 95°F (35°C) db

Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db/43°F (6°C) wb

††Additional charge required.

(Unit:in(mm))



Edition Date: 05/24
Printed in U.S.A.

Form No: MMY-MUP1201HT9P-UL_02
Replaces: MMY-MUP1201HT9P-UL 01

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.