


- NOTES:
1. BE SURE TO USE A WET RAG AND REMOVE ALL VALVE CORES BEFORE BRAZING FIELD PIPING.
 2. TEMPERATURE RELIEF DEVICES LOCATED ON LIQUID LINE AND HAVE 3/8" SAE FLARE CONNECTION.
DO NOT CAP OR OTHERWISE OBSTRUCT THE TEMPERATURE/PRESSURE RELIEF.
 3. ø 7/8" [22.2] PILOT HOLE PROVIDED FOR LOCATING FIELD POWER WIRING. ACTUAL HOLE REQUIRED DEPENDS ON FIELD WIRE SIZING.
 4. ø 1/2" [13.3] HOLE USED FOR MOUNTING UNIT.
 5. UNIT MUST HAVE AIRFLOW SERVICE CLEARANCES AS FOLLOWS:
TOP - DO NOT RESTRICT.
COIL SIDE - 42" [1067] FROM SOLID SURFACE.
PANEL SIDE - 48" [1219] PER NEC.
 6. CARRIER DOES NOT RECOMMEND INSTALLATION IN A PIT.
 7. UNIT CAN BE HANDLED USING THE FORK TRUCK LIFT POCKETS.
 8. DIMENSIONS ARE IN "INCH [MM]"
 9. FOR 38RCS PIPING, REFER TO "CIRCUIT A LIQUID CONNECTION" AND "CIRCUIT A SUCTION CONNECTION" DIMENSIONS SHOWN.
 10. DRAWING SHOWN WITH GREENSPEED OPTION.



PLAN VIEW

CENTER OF GRAVITY INCH [MM]			MACHINE OPTIONS			SERVICE VALVE CONNECTIONS	
CGx	CGy	CGz	GREENSPEED	COIL TYPE	DISCONNECT	SUCTION	LIQUID
35.9 [911]	44.3 [1128]	29.6 [751]	✓	CU-AL	✓	1 5/8" [41]	5/8" [16]



P.O. BOX 4906, SYRACUSE, N.Y. 13221

JOB NAME:

BUYER:

SALES ENG.:

MODEL NO.:

JOB NO.:

P.O. NO.:

PREPARED BY:

ELECTRICAL
CHARACTERISTICS:

JOBSITE LOCATION:
Job_Location 1
Job_Location 2

SALES OFFICE:

REFRIGERANT NO.:

NOTES:
Notes_1
Notes_2

38RC 040T STD
MACHINE ASSEMBLY
PLAN VIEW

DATE:

REVISION:

THIS DOCUMENT IS THE PRO-
PERTY OF CARRIER CORP.
AND IS DELIVERED UPON THE
EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DIS-
CLOSED OR USED WITHOUT
CARRIER CORP. WRITTEN
CONSENT.

SUBMISSION OF THESE DWG'S.
OR DOCUMENTS DOES NOT
CONSTITUTE PART PERFOR-
MANCE OR ACCEPTANCE OF
CONTRACT.

CARRIER DWG # 38RC-040-STD-P

REV. - SHT 01 OF 01



DATE: 08/05/2024

SUPERSEDES DWG. DATED:

38RC

SHT 01 OF 03

- NOTES:
1. BE SURE TO USE A WET RAG AND REMOVE ALL VALVE CORES BEFORE BRAZING FIELD PIPING.
 2. TEMPERATURE RELIEF DEVICES LOCATED ON LIQUID LINE AND HAVE 3/8" SAE FLARE CONNECTION.
DO NOT CAP OR OTHERWISE OBSTRUCT THE TEMPERATURE/PRESSURE RELIEF.
 3. ø 7/8" [22.2] PILOT HOLE PROVIDED FOR LOCATING FIELD POWER WIRING. ACTUAL HOLE REQUIRED DEPENDS ON FIELD WIRE SIZING.
 4. ø 1/2" [12.7] HOLE USED FOR MOUNTING UNIT.
 5. UNIT MUST HAVE AIRFLOW SERVICE CLEARANCES AS FOLLOWS:
TOP - DO NOT RESTRICT.
COIL SIDE - 42" [1067] FROM SOLID SURFACE.
PANEL SIDE - 48" [1219] PER NEC.
 6. CARRIER DOES NOT RECOMMEND INSTALLATION IN A PIT.
 7. UNIT CAN BE HANDLED USING THE FORK TRUCK LIFT POCKETS
 8. DIMENSIONS ARE IN "INCH [MM]"
 9. FOR 38RCS PIPING, REFER TO "CIRCUIT A LIQUID CONNECTION" AND "CIRCUIT A SUCTION CONNECTION" DIMENSIONS SHOWN.
 10. DRAWING SHOWN WITH GREENSPEED OPTION.



FRONT VIEW

CENTER OF GRAVITY INCH [MM]			MACHINE OPTIONS			SERVICE VALVE CONNECTIONS	
CGx	CGy	CGz	GREENSPEED	COIL TYPE	DISCONNECT	SUCTION	LIQUID
35.9 [911]	44.3 [1128]	29.6 [751]	✓	CU-AL	✓	1 5/8" [41]	5/8" [16]



JOB NAME:

BUYER:

SALES ENG.:

MODEL NO.:

JOB NO.:

P.O. NO.:

PREPARED BY:

ELECTRICAL
CHARACTERISTICS:

JOBSITE LOCATION:
Job_Location 1
Job_Location 2

SALES OFFICE:

REFRIGERANT NO.:

NOTES:
Notes_1
Notes_2

38RC 040T STD
MACHINE ASSEMBLY
FRONT VIEW

DATE:

REVISION:

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORP. AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORP. WRITTEN CONSENT.

SUBMISSION OF THESE DWG'S. OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT.

CARRIER DWG # 38RC-040-STD-F

REV. - SHT 01 OF 01

DATE: 08/05/2024

SUPERSEDES DWG. DATED:

38RC

SHT 02 OF 03

1. BE SURE TO USE A WET RAG AND REMOVE ALL VALVE CORES BEFORE BRAZING FIELD PIPING.
2. TEMPERATURE RELIEF DEVICES LOCATED ON LIQUID LINE AND HAVE 3/8" SAE FLARE CONNECTION. DO NOT CAP OR OTHERWISE OBSTRUCT THE TEMPERATURE/PRESSURE RELIEF.
3. Ø 7/16" [22.2] PILOT HOLE PROVIDED FOR LOCATING FIELD POWER WIRING. ACTUAL HOLE REQUIRED DEPENDS ON FIELD WIRE SIZING.
4. Ø 1/2" [12.7] HOLE USED FOR MOUNTING UNIT.
5. UNIT MUST HAVE AIRFLOW SERVICE CLEARANCES AS FOLLOWS:
 - TOP - DO NOT RESTRICT.
 - COIL SIDE - 42" [1067] FROM SOLID SURFACE.
 - PANEL SIDE - 48" [1219] PER NEC.
6. CARRIER DOES NOT RECOMMEND INSTALLATION IN A PIT.
7. UNIT CAN BE HANDLED USING THE FORK TRUCK LIFT POCKETS
8. DIMENSIONS ARE IN "INCH [MM]"
9. FOR 3BRCS PIPING, REFER TO "CIRCUIT A LIQUID CONNECTION" AND "CIRCUIT A SUCTION CONNECTION" DIMENSIONS SHOWN.
10. DRAWING SHOWN WITH GREENSPEED OPTION.



CENTER OF GRAVITY INCH [MM]			MACHINE OPTIONS			SERVICE VALVE CONNECTIONS	
CGx	CGy	CGz	GREENSPEED	COIL TYPE	DISCONNECT	SUCTION	LIQUID
36.0 [913]	44.0 [1120]	39.0 [794]	✓	CU-AL	✓	1 5/8" [41]	5/8" [16]

**JOB NAME:**

BUYER:

SALES ENG.:

MODEL NO.:

JOB NO.:

P.O. NO.:

PREPARED BY:

ELECTRICAL CHARACTERISTICS:

JOBSITE LOCATION:

Job_Location 1
Job_Location 2

SALES OFFICE:

REFRIGERANT NO.:

NOTES:

Notes_1
Notes_2

38RC 040T STD
MACHINE ASSEMBLY
SIDE VIEW

DATE: _____

REVISION:

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORP. AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORP. WRITTEN CONSENT.

SUBMISSION OF THESE DWG'S.
OR DOCUMENTS DOES NOT
CONSTITUTE PART PERFORM-
ANCE OR ACCEPTANCE OF
CONTRACT.

CARRIER DWG # 38RC-040-STD-S

REV. - SHT 01 OF 01

DATE: 08/05/2024

SUPERSEDES DWG. DATED:

38RC

SHT 03 OF 03