

SMMS-*u* / SHRM-*u* VRF Indoor Unit MML-UP0241BH-UL - Floor Console - Recessed

TOSHIBA
Carrier

Submittal Data

Job Name _____ Location _____
Tag _____



SMMS-*u* / SHRM-*u* VRF Floor Console - Recessed Features

- R-410A Refrigerant
- Six sizes from 7,500 to 24,000 Btu/h
- Wiring connection on the left side
- Piping and drain can be routed from right side, bottom, or back
- Drain tray and drain hose ship with the unit for field installation
- Five-year parts limited warranty

Indoor Unit Model	MML-UP0241BH-UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	24,000
Heating Rated Capacity	Btu/h	27,000
Fan Type (Qty)		Centrifugal (1)
Airflow (L / M / H)	CFM	380 / 470 / 560
Sound Pressure (L / M / H)	dBA	35 / 42 / 47 (208V) 37 / 44 / 49 (230V)
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.104 (208V) 0.120 (230V)
Full Load Amps (FLA)	A	0.6
Minimum Circuit Amps	A	0.7
Maximum Overcurrent Protection	A	15
Motor Type	AC Inverter Driven	
Motor Watts		70

PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	0.8
Refrigerant	R-410A	
External Finish	Zinc Hot Dipped Steel Plate	
Unit Width	in.	41.1
Unit Height	in.	23.6
Unit Depth	in.	8.7
Unit Net Weight	lb	68.3

ACCESSORIES (Optional)

- ☐ Wired Remote Controller (7-Day Programmable) RBC-AMS51E-ES / RBC-AWSU52-UL
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Remote Sensor TCB-TC41U-UL

DIMENSIONAL DRAWING

INDOOR UNIT FLOOR CONSOLE - RECESSED MML-UP0241BH-UL

