

Outdoor Unit Single Zone Heat Pump Ductless System

Outdoor Model: 38MARBQ18AA3

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Variable Speed (Inverter)
- Factory installed Base Pan Heater
- Factory installed Crankcase Heater
- Low Voltage Controls
- Auto-Restart function
- Condenser High Temp Protection
- Modes: Cool, Heat, Dry, Fan, Auto
- Quiet operation
- Anti-corrosive fin coating

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
 - *For residential applications.
- See warranty for full details.



NOTE: Images for illustration purposes only. Actual models may be slightly different.

System	Size		18
	Outdoor Model		38MARBQ18AA3
Electrical	Voltage, Phase, Cycle		V/Ph/Hz 208/230-1-60
	MCA	A.	16
	MOCP - Fuse Rating		A. 25
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	-22~122 (-30~50)
	Heating Outdoor DB Min - Max	°F(°C)	-22~86 (-30~30)
Piping	Total Piping Length		ft (m) 98 (30)
	Piping Lift ¹		ft (m) 65 (20)
	Pipe Connection Size - Liquid		in (mm) 1/4 (6.35)
	Pipe Connection Size - Suction		in (mm) 1/2 (12.7)
Refrigerant	Refrigerant Type		R410A
	Metering Device		EEV
	Charge	lbs (kg)	4.08 (1.85)

* Condensing unit above or below indoor unit
For Compatibility See Product Data

Outdoor Coil	Face Area	Sq. Ft.	5.9
	No. Rows		2
	Fins per inch		20
	Circuits		6
Compressor	Type		Rotary Inverter
	Model		KTM240D43UKT
	Oil Type		VG74
	Oil Charge	Fl. Oz.	21.0
	Rated Current	RLA	14.3
Outdoor	Unit Width	in (mm)	35.04 (890)
	Unit Height	in (mm)	29.13 (740)
	Unit Depth	in (mm)	13.46 (342)
	Net Weight	lbs (kg)	100.97 (45.8)
	Airflow	CFM	1,765
	Sound Pressure	dB(A)	59.0

Performance

High Wall	Indoor Model		DHMAHBQ18XA3
	Energy Star		YES
	Cooling Rated Capacity	Btu/h	18,000
	Cooling Cap. Range Min - Max	Btu/h	8,870~19,400
	SEER		21.5
	EER		12.5
	Heating Rated Capacity (47°F)	Btu/h	18,000
	Heating Rated Capacity (17°F)	Btu/h	10,800
	Heating Maximum Capacity (17°F)	Btu/h	14,000
	Heating Maximum Capacity (5°F)	Btu/h	18,000
	Heating Cap. Range Min - Max	Btu/h	8,400~19,500
	HSPF		13.0
	COP (47°F)	W/W	3.10
	COP (17°F)	W/W	2.80
COP (5°F)	W/W	1.78	
Cassette	Indoor Model		40MBCQ18---3
	Energy Star		YES
	Cooling Rated Capacity	Btu/h	16,000
	Cooling Cap. Range Min - Max	Btu/h	5,600~17,000
	SEER		20.0
	EER		12.5
	Heating Rated Capacity (47°F)	Btu/h	18,000
	Heating Rated Capacity (17°F)	Btu/h	11,200
	Heating Maximum Capacity (17°F)	Btu/h	21,000
	Heating Maximum Capacity (5°F)	Btu/h	17,000
	Heating Cap. Range Min - Max	Btu/h	8,700~21,000
	HSPF		10.3
	COP (47°F)	W/W	2.88
	COP (17°F)	W/W	1.80
COP (5°F)	W/W	1.68	
Ducted	Indoor Model		40MBDQ18---3
	Energy Star		YES
	Cooling Rated Capacity	Btu/h	16,500
	Cooling Cap. Range Min - Max	Btu/h	6,500~18,800
	SEER		19.6
	EER		12.5
	Heating Rated Capacity (47°F)	Btu/h	19,000
	Heating Rated Capacity (17°F)	Btu/h	12,700
	Heating Maximum Capacity (17°F)	Btu/h	21,500
	Heating Maximum Capacity (5°F)	Btu/h	17,800
	Heating Cap. Range Min - Max	Btu/h	8,900~22,000
	HSPF		11.0
	COP (47°F)	W/W	2.93
	COP (17°F)	W/W	1.90
COP (5°F)	W/W	1.75	
Console	Indoor Model		40MBFQ18---3
	Energy Star		YES
	Cooling Rated Capacity	Btu/h	17,000
	Cooling Cap. Range Min - Max	Btu/h	7,800~19,900
	SEER		20.2
	EER		12.5
	Heating Rated Capacity (47°F)	Btu/h	18,000
	Heating Rated Capacity (17°F)	Btu/h	12,000
	Heating Maximum Capacity (17°F)	Btu/h	20,700
	Heating Maximum Capacity (5°F)	Btu/h	16,900
	Heating Cap. Range Min - Max	Btu/h	8,600~21,500
	HSPF		10.6
	COP (47°F)	W/W	3.19
	COP (17°F)	W/W	1.80
COP (5°F)	W/W	1.75	

Construction View

Outdoor Model: 38MARBQ18AA3

