

Outdoor Unit Single Zone Heat Pump Ductless System

Outdoor Model: 38MHRCQ24AA3

Submittal Data

Job Data:		Location:	
Buyer:		Buyer P.O. #:	
		Carrier #:	
Unit Number:		Model Number:	
Performance Data Certified By:		Date:	

STANDARD FEATURES

- Cost competitive
- Factory installed Base Pan Heater
- Factory installed Crankcase Heater
- Auto-restart function
- Condenser high-temperature protection
- Refrigerant leakage detection
- Quiet outdoor operation
- Anti-corrosive fin coating

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications. See warranty for full details.



Specifications

System	Size		24
	Outdoor Model		38MHRCQ24AA3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	MCA	A.	19
	MOCP - Fuse Rating	A.	30
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	0~122 (-17~50)
Piping	Total Piping Length	ft (m)	164 (50)
	Piping Lift*	ft (m)	82 (25)
	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)
			R410A
Refrigerant	Type		R410A
	Charge	lbs (kg)	3.92 (1.78)
	Metering Device		EEV
Outdoor Coil	Face Area	Sq. Ft.	5.9
	No. Rows		1.6
	Fins per inch		20
	Circuits		5

* Condensing unit above or below indoor unit

Compressor	Compressor Type		Rotary Inverter
	Model		KTM240D43UKT
	Oil Type		VG74
	Oil Charge	Fl. Oz.	21.0
	Rated Current	RLA	14.25
Outdoor	Unit Width	in (mm)	35.04 (890)
	Unit Height	in (mm)	26.50 (673)
	Unit Depth	in (mm)	13.46 (342)
	Net Weight	lbs (kg)	97.88 (44.4)
	Airflow	CFM	1765
	Sound Pressure	dB(A)	59.5

Performance

High Wall	Energy Star		NO
	Cooling System Tons		2
	Cooling Rated Capacity	Btu/h	24000
	Cooling Cap. Range Min - Max	Btu/h	6760~24300
	SEER	Btu/Wh	19
	EER	Btu/Wh	9.4
	Heated Rated Capacity (47°F)	Btu/h	24800
	Heated Rated Capacity (17°F)	Btu/h	15300
	Heated Rated Capacity (5°F)	Btu/h	14000
	Heating Cap. Range Min - Max	Btu/h	6040~26210
	HSPF		10.2
	COP (47°F)	W/W	3.13
	COP (17°F)	W/W	2.61
	COP (5°F)	W/W	1.75

Compatibility Table

OUTDOOR UNIT	38MHRCQ24AA3
INDOOR UNIT	40MHHQ24---3

Construction View

