

High Wall Heat Pump Ductless System



Indoor Model: 40MHHAQ24XA3

Submittal Data

Job Data:

Location:

Buyer: Buyer P.O. #:

Carrier #:

Unit Number:

Model Number:

Performance Data Certified By:

Date:



STANDARD FEATURES:

- Available in 208/230V (9-36K)
- Available in 115V (9K-12K)
- Modes: Cool, Heat, Dry, Fan, Auto
- Turbo Mode
- Fully Modulating fan speeds
- Up-Down / Right-Left Louver control (fixed or swing)
- ECO Mode
- Heating Setback (46° F Heating Mode)
- Anti-corrosive fin coatings

CONTROLS:

- Wireless Remote Controller included with indoor unit

System	Size		24
	Indoor Model		40MHHAQ24XA3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	0.632
Controls	Wireless Remote Controller (°F/°C Convertible)		Standard
	Wired Remote Controller (°F/°C Convertible)		Optional
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	63~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)

Indoor Coil	Face Area		Sq. Ft.	2.67
	No. Rows			2
	Fins per inch			20
	Circuits			4
Indoor	Unit Width	in (mm)		42.60 (1082)
	Unit Height	in (mm)		13.27 (337)
	Unit Depth	in (mm)		9.21 (234)
	Net Weight	lbs (kg)		29.98 (13.6)
	Number of Fan Speeds			4
	Airflow (lowest to highest)	CFM		330/402/546/728
	Sound Pressure (lowest to highest)	dB(A)		32/38/44/51
	Air throw Data	ft (m)		27.2 (8.3)
	Moisture removal	Pint/h (L/h)		5.3 (2.54)
	Field Drain Pipe Size	in (mm)		5/8 (16)


Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.
For Compatibility See Product Data

Accessories

KSACN0901AAA	Wired Remote Control 7 Day Programmable
KSACN0101AAA	Wired Remote Control with Timer Function
KSAIF0601AAA	Wi-Fi™ Kit High Wall Mid-Tier
KSAIC0301230	24V Interface Kit 230V

Construction View

Indoor Model: 40MHHAQ24XA3



Unit Width	in (mm)	42.60 (1082)
Unit Height	in (mm)	13.27 (337)
Unit Depth	in (mm)	9.21 (234)
Net Weight	lbs (kg)	29.98 (13.6)

