

Outdoor Unit Single Zone Heat Pump Ductless System

Outdoor Model: 38MHRCQ18AA3

Submittal Data

Job Data:

Location:

Buyer: Buyer P.O. #:

Carrier #:

Unit Number: Model Number:

Performance Data Certified By:

Date:

STANDARD FEATURES

- Cost competitive
- Factory installed Base Pan Heater
- Factory installed Crankcase Heater
- Auto-restart function
- Condenser high-temperature protection
- Refrigerant leakage detection
- Quiet outdoor operation
- Anti-corrosive fin coating

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years

*For residential applications. See warranty for full details.



Specifications

System	Size		18
	Outdoor Model		38MHRCQ18AA3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	MCA	A.	15
	MOCP - Fuse Rating	A.	20
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	0~122 (-17~50)
Piping	Total Piping Length	ft (m)	98 (30)
	Piping Lift*	ft (m)	65 (20)
	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	1/2 (12.7)
	Pipe Connection Size - Suction	in (mm)	1/2 (12.7)
Refrigerant	Type		R410A
	Charge	lbs (kg)	2.98 (1.35)
	Metering Device		EEV
Outdoor Coil	Face Area	Sq. Ft.	4.67
	No. Rows		2
	Fins per inch		20
	Circuits		4

* Condensing unit above or below indoor unit

Compressor	Compressor Type		Rotary Inverter
	Model		KSN140D21UFZ
	Oil Type		VG74
	Oil Charge	Fl. Oz.	14.9
	Rated Current	RLA	10
Outdoor	Unit Width	in (mm)	31.69 (805)
	Unit Height	in (mm)	21.81 (554)
	Unit Depth	in (mm)	12.99 (330)
	Net Weight	lbs (kg)	73.85 (33.5)
	Airflow	CFM	1235
	Sound Pressure	dB(A)	55

Performance

High Wall	Energy Star		NO
	Cooling System Tons		1.5
	Cooling Rated Capacity	Btu/h	18000
	Cooling Cap. Range Min - Max	Btu/h	3760~19900
	SEER	Btu/Wh	19
	EER	Btu/Wh	11.2
	Heated Rated Capacity (47°F)	Btu/h	18000
	Heated Rated Capacity (17°F)	Btu/h	11800
	Heated Rated Capacity (5°F)	Btu/h	10000
	Heating Cap. Range Min - Max	Btu/h	6400~19000
	HSPF		11
	COP (47°F)	W/W	3.2
	COP (17°F)	W/W	2.72
	COP (5°F)	W/W	2

Compatibility Table

OUTDOOR UNIT	38MHRCQ18AA3
INDOOR UNIT	40MHHQ18---3

Construction View

