

Outdoor Unit Single Zone Heat Pump Ductless System

Outdoor Model: 38MARBQ06AA3

Submittal Data

Job Data:

Location:

Buyer: Buyer P.O. #:

Carrier #:

Unit Number:

Model Number:

Performance Data Certified By:

Date:



STANDARD FEATURES

- Variable Speed (Inverter)
- Factory installed Base Pan Heater
- Factory installed Crankcase Heater
- Low Voltage Controls
- Auto-Restart function
- Condenser High Temp Protection
- Modes: Cool, Heat, Dry, Fan, Auto
- Quiet operation
- Anti-corrosive fin coating

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications.
See warranty for full details.



NOTE: Images for illustration purposes only. Actual models may be slightly different.

System	Size		6
	Outdoor Model		38MARBQ06AA3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	MCA	A.	13
	Recommended Fuse Size	A.	15
	MOCP - Fuse Rating	A.	15
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	-22~122 (-30~50)
	Heating Outdoor DB Min - Max	°F(°C)	-22~86 (-30~30)
Piping	Total Piping Length	ft (m)	82 (25)
	Piping Lift	ft (m)	32 (10)
	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)
Refrigerant	Refrigerant Type		R410A
	Metering Device		EEV
	Charge	lbs (kg)	2.38 (1.08)

* Condensing unit above or below indoor unit
For Compatibility See Product Data

Outdoor Coil	Face Area	Sq. Ft.	4.0
	No. Rows		2
	Fins per inch		21
	Circuits		4
Compressor	Type	Rotary Inverter	
	Model	KSK103D33UEZ3	
	Oil Type	VG74	
	Oil Charge	Fl. Oz.	10.5
Outdoor	Rated Current	RLA	6.4
	Unit Width	in (mm)	30.12 (765)
	Unit Height	in (mm)	21.85 (555)
	Unit Depth	in (mm)	11.93 (303)
	Net Weight	lbs (kg)	63.71 (28.9)
	Airflow	CFM	1,324
	Sound Pressure	dB(A)	54.5

Performance

High Wall	Indoor Model		DHMAHBQ06XA3
	Energy Star		YES
	Cooling Rated Capacity	Btu/h	6,000
	Cooling Cap. Range Min - Max	Btu/h	2,500~11,000
	SEER		26.5
	EER		15.8
	Heating Rated Capacity (47°F)	Btu/h	7,400
	Heating Rated Capacity (17°F)	Btu/h	4,900
	Heating Maximum Capacity (17°F)	Btu/h	9,000
	Heating Maximum Capacity (5°F)	Btu/h	7,500
	Heating Cap. Range Min - Max	Btu/h	3,500~11,600
	HSPF		14.0
	COP (47°F)	W/W	3.90
	COP (17°F)	W/W	3.05
	COP (5°F)	W/W	1.90

Construction View

Outdoor Model: 38MARBQ06AA3

