

Outdoor Unit Single Zone Heat Pump Ductless System



Outdoor Model: 38MARBQ36AA3

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Variable Speed (Inverter)
- Factory installed Base Pan Heater
- Factory installed Crankcase Heater
- Low Voltage Controls
- Auto-Restart function
- Condenser High Temp Protection
- Modes: Cool, Heat, Dry, Fan, Auto
- Quiet operation
- Anti-corrosive fin coating

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications.
- See warranty for full details.

NOTE: Images for illustration purposes only. Actual models may be slightly different.

System	Size	36	
	Outdoor Model	38MARBQ36AA3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	MCA	A.	28
	MOCP - Fuse Rating	A.	35
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	-22~122 (-30~50)
	Heating Outdoor DB Min - Max	°F(°C)	-22~86 (-30~30)
Piping	Total Piping Length	ft (m)	213 (65)
	Piping Lift ¹	ft (m)	98 (30)
	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)
Refrigerant	Refrigerant Type	R410A	
	Metering Device	EEV	
	Charge	lbs (kg)	7.50 (3.40)

* Condensing unit above or below indoor unit
For Compatibility See Product Data

Outdoor Coil	Face Area	Sq. Ft.	24.0
	No. Rows	3	
	Fins per inch	18	
	Circuits	6	
Compressor	Type	Rotary Inverter	
	Model	KTF250D22UMT	
	Oil Type	VG74	
	Oil Charge	Fl. Oz.	22.7
Outdoor	Rated Current	RLA	18.0
	Unit Width	in (mm)	37.24 (946)
Outdoor	Unit Height	in (mm)	34.84 (885)
	Unit Depth	in (mm)	16.14 (410)
	Net Weight	lbs (kg)	150.13 (68.1)
	Airflow	CFM	2,235
	Sound Pressure	dB(A)	61.5

Performance

High Wall	Indoor Model		619AHBQ36XA3
	Energy Star		NO
	Cooling Rated Capacity	Btu/h	36,000
	Cooling Cap. Range Min - Max	Btu/h	9,300~38,800
	SEER		17.5
	EER		8.5
	Heating Rated Capacity (47°F)	Btu/h	36,000
	Heating Rated Capacity (17°F)	Btu/h	22,400
	Heating Maximum Capacity (17°F)	Btu/h	23,600
	Heating Maximum Capacity (5°F)	Btu/h	20,400
	Heating Cap. Range Min - Max	Btu/h	11,570~37,000
	HSPF		9.0
	COP (47°F)	W/W	2.51
	COP (17°F)	W/W	2.18
COP (5°F)	W/W	1.75	

Construction View

Outdoor Model: **38MARBQ36AA3**

