

Outdoor Unit Multi-zone Heat Pump Ductless System

Outdoor Model: 38MGRBQ36DA3

Submittal Data

Job Data:		Location:	
Buyer:		Buyer P.O. #:	
Unit Number:		Carrier #:	
Performance Data Certified By:		Model Number:	
		Date:	

MULTI-ZONE OUTDOOR STANDARD FEATURES:

- Connect 2 to 4, multiple style indoor units
 - High Wall ≤24K
 - Cassette ≤24K
 - Ducted ≤24K
 - Console ≤24K

- Variable Speed (Inverter) Compressor
- Basepan Heater factory installed
- Quiet operation
- Aluminum Hydrophilic pre-coated fins

Cooling operating range -22°~122° F (-30°~50° C)

Heating operating range -22°~75° F (-30°~24° C)

- 71% Heating Capacity Maintenance at 5° F (-15° C)
- 39% Heating Capacity Maintenance at -22° F (-30° C)

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications. See warranty for full details.

Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	-22~122 (-30~50)
	Heating Outdoor DB Min - Max	°F(°C)	-22~75 (-30~24)
Piping	Total Piping Length	ft (m)	262 (80)
	Piping to furthest FCU	ft (m)	115 (35)
	Drop (OD above ID)	ft (m)	49 (15)
	Lift (OD below ID)	ft (m)	49 (15)
	Pipe Connection Size - Liquid	in (mm)	1/4*4(6.35*4)
	Pipe Connection Size - Suction	in (mm)	1/2 *1+ 3/8*3(12.7*1+9.52*3)
Refrigerant	Type		R410A
	Charge	lbs (kg)	8.38 (3.8)
	Metering Device		EXV
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply		Indoor unit powered from outdoor unit
	MCA	A.	25
	Recommended Fuse Size	A.	30
	MOPA - Fuse Rating	A.	40
Compressor	Type		R410A
	Model		KTF310D43UMT
	Oil Type		ESTER OIL VG74
	Oil Charge	Fl. Oz.	33.8
	Rated Current	RLA	18.0
Outdoor	Unit Width	in (mm)	37.24 (946)
	Unit Height	in (mm)	31.89 (810)
	Unit Depth	in (mm)	16.14 (410)
	Net Weight	lbs (kg)	169.09 (76.7)
	Airflow	CFM	2,147
	Sound Pressure	dB(A)	63

Specifications

System	Size		36R
	Outdoor Model		38MGRBQ36DA3
	Max Number of Zones		4
Performance Non-Ducted	Energy Star		NO
	Cooling System Tons		3
	Cooling Rated Capacity	Btu/h	36,000
	Cooling Cap. Range Min - Max	Btu/h	8,209~40,555
	SEER		23
	EER		11.5
	Heating Rated Capacity (47°F)	Btu/h	37,000
	Heating Rated Capacity (17°F)	Btu/h	23,500
	Heating Rated Capacity (5°F)	Btu/h	23,900
	Heating Maximum Capacity (5°F)	Btu/h	23,900
	Heating Cap. Range Min - Max	Btu/h	8,008~44,632
	HSPF		11.3
	COP (47°F)	W/W	3.61
	COP (17°F)	W/W	2.64
	COP (5°F) - Rated	W/W	1.80
Performance Combination Ducted and Non-Ducted	Energy Star		NO
	Cooling System Tons		3
	Cooling Rated Capacity	Btu/h	36,000
	Cooling Cap. Range Min - Max	Btu/h	8,499~40,422
	SEER		21.3
	EER		11.3
	Heating Rated Capacity (47°F)	Btu/h	37,000
	Heating Rated Capacity (17°F)	Btu/h	23,250
	Heating Rated Capacity (5°F)	Btu/h	23,900
	Heating Maximum Capacity (5°F)	Btu/h	23,900
	Heating Cap. Range Min - Max	Btu/h	7,454~45,628
	HSPF		11
	COP (47°F)	W/W	3.61
	COP (17°F)	W/W	2.64
	COP (5°F) - Rated	W/W	1.72
Performance Ducted	Energy Star		NO
	Cooling System Tons		3
	Cooling Rated Capacity	Btu/h	36,000
	Cooling Cap. Range Min - Max	Btu/h	8,789~40,288
	SEER		19.5
	EER		11.0
	Heating Rated Capacity (47°F)	Btu/h	37,000
	Heating Rated Capacity (17°F)	Btu/h	23,000
	Heating Rated Capacity (5°F)	Btu/h	24,000
	Heating Maximum Capacity (5°F)	Btu/h	24,000
	Heating Cap. Range Min - Max	Btu/h	6,900~46,624
	HSPF		10.7
	COP (47°F)	W/W	3.60
	COP (17°F)	W/W	2.64
	COP (5°F) - Rated	W/W	1.68

Rated Combinations

Two Zones	Three Zones		Four Zones	
6+9	6+6+6	9+9+9	6+6+6+6	6+12+12+12
6+12	6+6+9	9+9+12	6+6+6+9	6+12+12+18
6+18	6+6+12	9+9+18	6+6+6+12	9+9+9+9
6+24	6+6+18	9+9+24	6+6+6+18	9+9+9+12
9+9	6+6+24	9+12+12	6+6+6+24	9+9+9+18
9+12	6+9+9	9+12+18	6+6+9+9	9+9+12+12
9+18	6+9+12	9+12+24	6+6+9+12	9+9+12+18
9+24	6+9+18	9+18+18	6+6+9+18	9+12+12+12
12+12	6+9+24	12+12+12	6+6+9+24	12+12+12+12
12+18	6+12+12	12+12+18	6+6+12+12	
12+24	6+12+18	12+18+18	6+6+12+18	
18+18	6+12+24	12+12+24	6+6+12+24	
	6+18+18		6+6+18+18	
	6+18+24		6+9+9+9	
			6+9+9+12	
			6+9+9+18	
			6+9+9+24	

Outdoor Model: 38MGRBQ36DA3

