# CARRIER SINGLE-PHASE VRF PRODUCT LINEUP



# **OUTDOOR UNIT**



Single-Phase Heat Pump

38VMB-1P

Capacity Range (Tons): 3.0 - 5.0


# **INDOOR UNITS**

#### **Ducted**



Low Static Ducted 40VML

Capacity Range (Tons): 0.6 – 2.0



Medium Static Ducted 40VMM

Capacity Range (Tons): 0.6 - 4.0



High Static Ducted 40VMH

Capacity Range (Tons): 2.0 – 8.0



Vertical Air Handling Unit (AHU) 40VMV

Capacity Range (Tons): 1.0 - 4.5

## **Non-Ducted**



4-Way Cassette 40VMF

Capacity Range (Tons): 0.75 – 4.0



### Compact 4-Way Cassette 40VMC

Capacity Range (Tons): 0.4 - 1.25



#### One-Way Cassette 40VMI

Capacity Range (Tons): 0.4 – 2.0



#### High Wall 40VMW

Capacity Range (Tons): 0.4 - 2.5



#### Underceiling/Floor Console (Exposed) 40VMU

Capacity Range (Tons): 1.0 - 4.0



Floor Console (Recessed) 40VMR

Capacity Range (Tons): 0.6 - 2.0

# CARRIER SINGLE-PHASE VRF PRODUCT LINEUP



# **CONTROLS**

## **Individual Zone Controls**







Non-Programmable Wired Remote Controller 40VM900002



24V Interface 40VM900008



Programmable Wired Remote Controller 40VM900003



Low Profile "Button" Sensor 40VM900009

## **Central Controls**




Touch Screen Central Controller 40VM900006A

# **COMMUNICATION WIRING ACCESSORIES**



Connector with Terminal for Field Provided Communication Wiring 40VM900016

Factory Provided with Equipment



Optional Accessories 40VM920015 / 40VM920025 / 40VM900050 / 40VM900100 / 40VM900150 / 40VM900200

Connector with Wiring for Factory Provided Communication Wiring
Available Lengths:

15'/25'/50'/100'/150'/200' Options

# **ADDITIONAL DEVICES**



ERV Interface (DI/DO) 40VM900007



VRF/DLS Interface 40VM900010



### Service Technical Tool (STT)

Service tool software can be downloaded free from hvacpartners.com (Requires RS485 interface - field supplied)