

SENSOR SELECTION GUIDE

For Carrier Commercial Systems



TABLE OF CONTENTS

Temperature Products	Page 1-6
• 33 Part Numbers).....	Page 1
• NSA Part Numbers	Page 2-6
• NSA-HH Part Numbers.....	Page 6
Humidity Products	Page 7-8
• Rooms	Page 7
• Duct.....	Page 7
• Outside Air	Page 8
Pressure Products	Page 9-14
• Differential Pressure Transmitter	Page 9
• Gage Pressure	Page 10
• Wet to Wet Transmitter (WPR2).....	Page 11-12
• Differential Pressure Switches	Page 12
• Differential Pressure Accessories	Page 12
• Pickup Ports.....	Page 13
• Pitot Tubes	Page 13-14
Current Products	Page 14-16
• ECM Current Switch.....	Page 14
• Current Sensor (Mini, Fixed)	Page 14-15
• Current Sensor (Mini, Adjustable)	Page 14-15
• Current Sensor (Fixed)	Page 15-16
• Current Sensor (Adjustable)	Page 15-16

TABLE OF CONTENTS

Power Meters	Page 16-23
• KW350	Page 16
• Power Meter CTs.....	Page 16-21
• Rogowski Coil	Page 21-22
• KW320	Page 22
• KW1850	Page 23
Gas Products	Page 24-26
• CO2 Room Sensors (R2).....	Page 24
• CO2 Duct Sensors.....	Page 24
• CO2 Accessories.....	Page 24
• Q5 Smart Sensor.....	Page 25
• Q5 Smart Sensor Accessories.....	Page 25
• VOC Room.....	Page 25
• PM2.5 Duct	Page 25
• PM2.5 Room	Page 26
BACnet	Page 26
• Q5/B5.....	Page 26
• B6	Page 26
• R2	Page 26
• Duct.....	Page 26
Misc. Devices	Page 27
• Liquid Flow Switch.....	Page 27
• Power Supply (24V)	Page 27
• Spot Leak Detector	Page 27

TEMPERATURE

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Room • Override • Communication Jack 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCT55SPT	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Room • Override • Setpoint 	<ul style="list-style-type: none"> • Communication Jack • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCT56SPT	View Data Sheet »
	<ul style="list-style-type: none"> • Microprocessor Based LCD • 10K Type II Thermistor • Room • Override 	<ul style="list-style-type: none"> • Setpoint • Communication Jack • STD Lead Time 5 Days • Warranty: 5 Years 	33ZCT59SPT	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Probe with Flange 4" • Plenum Cable 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCSENSAT	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Duct 6" Probe Length • Galvanized Enclosure 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCSENPAT	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Outside Air • NEMA 3R Enclosure 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCSENOAT	View Data Sheet »
	<ul style="list-style-type: none"> • Galvanized Enclosure • 0 to 5" Pipe Strap 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCSENCHG	No Data Sheet
	<ul style="list-style-type: none"> • Diff Enthalpy Switch • SPDT Relay 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33CSENTHSW	View Data Sheet »
	<ul style="list-style-type: none"> • 4 to 20mA Loop • Enthalpy • 0 to 50 BTU 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33CSENTSEN	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Enthalpy • Switch • 24BTU • SPDT 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH57ZC005-C	No Data Sheet

TEMPERATURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Plastic Button <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-PBS	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Stainless Steel Button <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-SBS	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Room • White <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-R2-C	View Data Sheet »
	<ul style="list-style-type: none"> • 50K Thermistor • Room • CARRIER LOGO <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/50K-R2L-C	View Data Sheet »
	<ul style="list-style-type: none"> • Microprocessor Based LCD • 10K Type II Thermistor • Setpoint <ul style="list-style-type: none"> • Override • Communication Jack • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CPRSO-RJ6-TUC2-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wall Sensor Clear Lock Cover <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-Locking Cover	View Data Sheet »
	<ul style="list-style-type: none"> • Foam Insulation Pad <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/Room-Foam-Pad	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Stainless Plate <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-SP-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Probe with Flange • 4" Probe Length • 10ft Leads <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-DO-4-10CL2P	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Probe with Flange • 8" Probe Length • 10ft Leads <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-DO-8-10CL2P	View Data Sheet »

TEMPERATURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Duct • 4" Probe Length • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-D-4-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 50K Thermistor • Duct • 4" Probe Length • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/50K-D-4-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Duct • 8" Probe Length • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-D-8-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Duct • 12" Probe Length • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-D-12-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Immersion • 2.5" Well • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-I-25-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Immersion • 4" Well • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-I-4-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Immersion • 6" Well • Plastic Box <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-I-6-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Immersion • 2.5" Well • NEMA 4X Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-I-25-4X	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Immersion • 4" Well • NEMA 4X Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-I-4-4X	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Immersion • 6" Well • NEMA 4X Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-I-6-4X	View Data Sheet »

TEMPERATURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • 50K Thermistor • Strap <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/50K-S-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Strap • 2-10" • Galvanized Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-S10-GD-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Strap • 2-5" • Plastic Box Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-S-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Strap • 2-10" • NEMA 4X Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-S10-4X	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Strap • 2-5" • NEMA 4X Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-S-4X	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Copper Avg • 12ft Coil Length • Plastic Box Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-A-12-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Copper Avg • 24ft Coil Length • Plastic Box Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-A-24-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Copper Avg • 50ft Coil Length • Plastic Box Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-A-50-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Copper Avg • 8ft Coil Length • Plastic Box Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-A-8-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • Copper Averaging Sensor Mounting Clip • Bag of 50 <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CAPILLARY-CLIP	View Data Sheet »

TEMPERATURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Rigid Averaging • 18" Probe Length <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-RA-18-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Rigid Averaging • 24" Probe Length <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-RA-24-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Rigid Averaging • 36" Probe Length <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-RA-36-PB-C	View Data Sheet »
	<ul style="list-style-type: none"> • Plastic Averaging Sensor Mounting Clip • Bag of 50 <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-UNIVERSAL-CLIP	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Outside Air • Euro Enclosure <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CP-O-EH-C	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • 1" Probe • 14" Leads <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-BP	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • 1" Probe • 10ft Plenum Cable <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CP-BP-10CL2P	View Data Sheet »
	<ul style="list-style-type: none"> • 10K Type II Thermistor • 1" Probe • 20ft Plenum Cable <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Year 	NSA-A/CP-BP-20CL2P	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Auto Reset <ul style="list-style-type: none"> • 6' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-06-A	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Manual Reset <ul style="list-style-type: none"> • 6' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-06-M	View Data Sheet »

TEMPERATURE

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Auto Reset 	<ul style="list-style-type: none"> • 10' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-10-A	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Manual Reset 	<ul style="list-style-type: none"> • 10' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-10-M	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Auto Reset 	<ul style="list-style-type: none"> • 20' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-20-A	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Manual Reset 	<ul style="list-style-type: none"> • 20' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-20-M	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Auto Reset 	<ul style="list-style-type: none"> • 50' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-50-A	View Data Sheet »
	<ul style="list-style-type: none"> • Freeze Stat • 4 Wire • Two Circuits • Manual Reset 	<ul style="list-style-type: none"> • 50' Capillary Bulb • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-FLS-50-M	View Data Sheet »

	<ul style="list-style-type: none"> • 10K Type II Thermistor • Probe with Flange • 6" Probe Length • 10ft Plenum Cable 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH79NZ074	No Data Sheet
	<ul style="list-style-type: none"> • 10K Type II Thermistor • Copper Averaging • 24ft Coil Length • Galvanized Enclosure 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH79NZ041	No Data Sheet

RELATIVE HUMIDITY

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Relative Humidity • 3% • 10K Type II Thermistor • Room 	<ul style="list-style-type: none"> • White • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/RH3-CP-R2-C	No Data Sheet
	<ul style="list-style-type: none"> • Relative Humidity • 2% • 10K Type II Thermistor • Room 	<ul style="list-style-type: none"> • White • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/RH2-CP-R2-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 3% • Space Transmitter 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	33ZCSENSRH-02	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity 3% • 10K Type II Thermistor • Setpoint, Override, Communication Jack 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/RH3-CP-RSO-RJ6-TUCH2-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 2% • 10K Type II Thermistor • Stainless Plate 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/RH2-CP-SP-10-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 3% • 10K Type II Thermistor • Stainless Plate 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/RH3-CP-SP-010-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 2% • 10K Type II Thermistor • Duct 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/RH2-CP-D-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 3% • Duct Transmitter 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Year 	33ZCSENDRH-02	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 3% • 10K Type II Thermistor • Duct 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Year 	NSA-HH/RH3-CP-D-C	View Data Sheet »

RELATIVE HUMIDITY

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Relative Humidity • 2% • 10K Type II Thermistor • Outside Air 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years NSA-HH/RH2-CP-O-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 3% • 10K Type II Thermistor • Outside Air 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years NSA-HH/RH3-CP-O-C	View Data Sheet »
	<ul style="list-style-type: none"> • Relative Humidity • 3% • Outside Air Transmitter 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 33ZCSENORH-02	View Data Sheet »

PRESSURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 0.1" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-D10-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 0.25" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-D25-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 2.5" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-2D5-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 0.5" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-D50-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 1" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-001-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 2" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-002-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 3" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-003-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 4" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Year 	NSA-HH/MLP2-004-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 5" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-005-W-U-A-A-OP-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • Panel Mount • 0 to 10" • 4-20mA <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/MLP2-010-W-U-A-A-OP-C	View Data Sheet »

PRESSURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Differential Pressure • 0-0.1", 0-0.2", 0-0.5", 0-1" • LCD • Pitot Tube <ul style="list-style-type: none"> • DIN Rail • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/DLP-001-W-U-D-A-3-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • 0-0.1", 0-0.2", 0-0.5", 0-1" <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/DLP-001-W-U-N-A-0-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • 0-1", 0-2.5", 0-5", 0-10" • LCD • Pitot Tube <ul style="list-style-type: none"> • DIN Rail • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/DLP-010-W-U-D-A-3-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • 0-1", 0-2.5", 0-5", 0-10" <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/DLP-010-W-U-N-A-0-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • 0-10", 0-20", 0-30", 0-40" • LCD • Pitot Tube <ul style="list-style-type: none"> • DIN Rail • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/DLP-040-W-U-D-A-3-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure • 0-10", 0-20", 0-30", 0-40" <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/DLP-040-W-U-N-A-0-C	View Data Sheet »
	<ul style="list-style-type: none"> • Gage Pressure • 0 to 15 PSIG • 4-20mA • Packard <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-GP(0-15G)-20-P	View Data Sheet »
	<ul style="list-style-type: none"> • Gage Pressure • 0 to 50 PSIG • 4-20mA • Packard <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Year 	NSA-GP(0-50G)-20-P	View Data Sheet »
	<ul style="list-style-type: none"> • Gage Pressure • 0 to 100 PSIG • 4-20mA • Packard <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-GP(0-100G)-20-P	View Data Sheet »
	<ul style="list-style-type: none"> • Gage Pressure • 0 to 200 PSIG • 4-20mA • Packard <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-GP(0-200G)-20-P	View Data Sheet »

PRESSURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Gage Pressure • 0 to 300 PSIG • 4-20mA • Packard <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-GP(0-300G)-20-P	View Data Sheet »
	<ul style="list-style-type: none"> • Gage Pressure • 0 to 500 PSIG • 4-20mA • Packard <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-GP(0-500S)-20-P	View Data Sheet »
	<ul style="list-style-type: none"> • 2ft Gage Pressure • Packard Harness • 2ft Lead Length <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/GP-2HARNESS	View Data Sheet »
	<ul style="list-style-type: none"> • 10ft Gage Pressure • Packard Harness • 2ft Lead Length <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/GP-10HARNESS	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 30PSI • 10ft Leads <ul style="list-style-type: none"> • LCD • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/WPR2-30-10-LCD-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 30PSI • 10ft Leads <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/WPR2-30-10-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 100PSI • 10ft Leads <ul style="list-style-type: none"> • LCD • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/WPR2-100-10-LCD-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 100PSI • 10ft Leads <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Year 	NSA-HH/WPR2-100-10-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 300PSI • 10ft Leads <ul style="list-style-type: none"> • LCD • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/WPR2-300-10-LCD-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 300PSI • 10ft Leads <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/WPR2-300-10-C	View Data Sheet »

PRESSURE

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0-30PSID • 20ft Metal Clad Cable <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-A/WPR2-30-M20-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 100PSI • 20ft Metal Clad Cable <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-A/WPR2-100-M20-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 300PSI • 20ft Metal Clad Cable <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-A/WPR2-300-M20-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 100PSI • 20ft Metal Clad Cable <ul style="list-style-type: none"> • LCD • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-A/WPR2-100-M20-LCD-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 300PSI • 20ft Metal Clad Cable <ul style="list-style-type: none"> • LCD • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-A/WPR2-300-M20-LCD-C	View Data Sheet »
	<ul style="list-style-type: none"> • Wet to Wet Differential Pressure • 0 to 30PSI • 20ft Metal Clad Cable <ul style="list-style-type: none"> • LCD • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-A/WPR2-30-M20-LCD-C	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure Switch • 0.2 to 2" Range • SPDT <ul style="list-style-type: none"> • NEMA 3 Enclosure • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-DBL-205B	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure Switch • 0.8 to 4" Range • SPDT <ul style="list-style-type: none"> • NEMA 3 Enclosure • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-DBL-205D	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure Switch • 0.2 to 10" Range • SPDT <ul style="list-style-type: none"> • NEMA 3 Enclosure • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-DBL-205E	View Data Sheet »
	<ul style="list-style-type: none"> • Differential Pressure Switch • 0.08 to 8" Range • SPDT <ul style="list-style-type: none"> • NEMA 3 Enclosure • STD Lead Time: 10 Days • Warranty: 2 Years 	NSA-DBL-205L	View Data Sheet »

PRESSURE

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> Differential Pressure Switch 0.05 to 12" Range SPDT 	<ul style="list-style-type: none"> Auto Reset STD Lead Time: 5 Days Warranty: 2 Years 	NSA-AFS-222	View Data Sheet »
	<ul style="list-style-type: none"> Differential Pressure Switch 0.05 to 2" Range SPDT 	<ul style="list-style-type: none"> Auto Reset STD Lead Time: 5 Days Warranty: 2 Years 	NSA-AFS-262	View Data Sheet »
	<ul style="list-style-type: none"> Differential Pressure Switch 0.4 to 2" Range SPDT 	<ul style="list-style-type: none"> Auto Reset STD Lead Time: 5 Days Warranty: 2 Years 	NSA-AFS-460	View Data Sheet »
	<ul style="list-style-type: none"> DBL Series Duct Mount Kit 	<ul style="list-style-type: none"> STD Lead Time: 10 Days Warranty: 2 Years 	NSA-DBZ-06	View Data Sheet »
	<ul style="list-style-type: none"> Bldg Static Outdoor Pickup Port 	<ul style="list-style-type: none"> STD Lead Time: 5 Days Warranty: 2 Years 	NSA-HH/O-PUP-V-C	View Data Sheet »
	<ul style="list-style-type: none"> Bldg Static SS Plate Pickup Port 	<ul style="list-style-type: none"> STD Lead Time: 5 Days Warranty: 2 Years 	NSA-HH/SP-PUP-C	View Data Sheet »
	<ul style="list-style-type: none"> Pitot Tube 3" 	<ul style="list-style-type: none"> STD Lead Time: 5Days Warranty: 5 Years 	NSA-PT-3	View Data Sheet »
	<ul style="list-style-type: none"> Pitot Tube 5.2" 	<ul style="list-style-type: none"> STD Lead Time: 5 Days Warranty: 5 Years 	NSA-PT-52	View Data Sheet »
	<ul style="list-style-type: none"> Pitot Tube 7.5" 	<ul style="list-style-type: none"> STD Lead Time: 5 Days Warranty: 5 Years 	NSA-PT-75	View Data Sheet »
	<ul style="list-style-type: none"> Pitot Tube 9.7" 	<ul style="list-style-type: none"> STD Lead Time: 5 Days Warranty: 5 Years 	NSA-PT-97	View Data Sheet »

PRESSURE

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Static Pressure Probe • 3.5" 	<ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 5 Years 	NSA-SPT-35	View Data Sheet »
	<ul style="list-style-type: none"> • Static Pressure Probe • 8" 	<ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 5 Years 	NSA-SPT-80	View Data Sheet »
	<ul style="list-style-type: none"> • Velocity Pitot Tube • Aluminum • 3.5" 	<ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 5 Years 	NSA-VPT	View Data Sheet »

CURRENT

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • N/O ECM Current Switch • 0-25A • Split Core 	<ul style="list-style-type: none"> • Trip Adjustment Range: 0.075–0.5 A • Warranty: 5 Years 	N2-ECMCS25	View Data Sheet »
	<ul style="list-style-type: none"> • ECM Calibration Tool 	<ul style="list-style-type: none"> • Warranty: 5 Years 	N2-TRIP-ADJUST-TOOL	View Data Sheet »
	<ul style="list-style-type: none"> • Fixed Current Switch • Mini • Solid Core • Normally Open 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years • 0-150 Amp • < 0.2A or Less 	NSA-A/MCS	View Data Sheet »
	<ul style="list-style-type: none"> • Adjustable Current Switch • Mini • Solid Core 	<ul style="list-style-type: none"> • Normally Open • STD Lead Time: 5 Days • Warranty: 5 Years • 0.32 to 150 Amps 	NSA-A/MCS-A	View Data Sheet »
	<ul style="list-style-type: none"> • Fixed Current Switch • Mini • Solid Core • Normally Open 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years • 0.55 to 150 Amp 	NSA-A/MSCS	View Data Sheet »
	<ul style="list-style-type: none"> • Adjustable Current Switch • Mini • Split Core 	<ul style="list-style-type: none"> • Normally Open • STD Lead Time: 5 Days • Warranty: 5 Years • 0.70 to 150 Amps 	NSA-A/MSCS-A	View Data Sheet »

CURRENT

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Fixed Current Switch • DIN Rail, Solid Core • Normally Open • <0.25A Trip Point <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CS2	View Data Sheet »
	<ul style="list-style-type: none"> • Adjustable Current Switch • DIN Rail • Solid Core <ul style="list-style-type: none"> • Normally Open, 0.5 to 220A Trip Point • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/ACS2	View Data Sheet »
	<ul style="list-style-type: none"> • Fixed Current Switch • DIN Rail • Split Core • Normally Open <ul style="list-style-type: none"> • <1.5A Trip Point • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCS2	View Data Sheet »
	<ul style="list-style-type: none"> • Fixed Current Switch • DIN Rail • Split Core • Normally Open <ul style="list-style-type: none"> • Low Trip • <0.5A Trip Point • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCS2-L	View Data Sheet »
	<ul style="list-style-type: none"> • Adjustable Current Switch • DIN Rail • Split Core <ul style="list-style-type: none"> • Normally Open • 1.5 to 220A Trip Point • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/ASCS2	View Data Sheet »
	<ul style="list-style-type: none"> • Adjustable Current Switch • DIN Rail • Split Core <ul style="list-style-type: none"> • Normally Open • 0.6 to 180A Trip Point • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/ASCS2-L	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 4-20mA • DIN Rail • Solid Core <ul style="list-style-type: none"> • 0-5 Amp • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CTA2-5	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 4-20mA • DIN Rail • Solid Core <ul style="list-style-type: none"> • 0-10, 0-20, 0-50 Amp (Default) • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CTA2-50	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 4-20mA • DIN Rail • Solid Core <ul style="list-style-type: none"> • 0-100, 0-200, 0-250 Amp (Default) • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CTA2-250	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 4-20mA • DIN Rail • Split Core <ul style="list-style-type: none"> • RMS • 0-10, 0-20, 0-50 Amp • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTA2-50-RMS	View Data Sheet »

CURRENT

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Analog Current Sensor • 0-5 VDC • DIN Rail • Split Core <ul style="list-style-type: none"> • 0-10, 0-20, 0-50 Amp (Default) • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTE2-50	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 0-5 VDC • DIN Rail • Split Core <ul style="list-style-type: none"> • 0-50, 0-100, 0-150 Amp (Default) • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTE2-150	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 0-5 VDC • DIN Rail • Split Core <ul style="list-style-type: none"> • 250 Amp Max • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTE2-250	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 0-10 VDC • DIN Rail • Split Core <ul style="list-style-type: none"> • 0-10, 0-20, 0-50 Amp (Default) • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTV2-50	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 0-10 VDC • DIN Rail • Split Core <ul style="list-style-type: none"> • 150 Amp Max • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTV2-150	View Data Sheet »
	<ul style="list-style-type: none"> • Analog Current Sensor • 0-10 VDC • DIN Rail • Split Core <ul style="list-style-type: none"> • 0-100, 0-200, 0-250 Amp (Default) • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/SCTV2-250	View Data Sheet »
	<ul style="list-style-type: none"> • Command Relay • 12VDC Coil • SPDT • 12A <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CR-12DC-12A	View Data Sheet »
	<ul style="list-style-type: none"> • Command Relay • 24VDC Coil • SPDT • 10A <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CR-24AC-10A	View Data Sheet »
	<ul style="list-style-type: none"> • Command Relay • 24VDC Coil • SPDT • 12A <ul style="list-style-type: none"> • Time: 5 Days • Warranty: 5 Years 	NSA-A/CR-DC-12A	View Data Sheet »
	<ul style="list-style-type: none"> • Command Relay • 24VDC Coil • SPDT • 5A <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CR-DC-5A	View Data Sheet »

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Power Meter • Bi-Directional • 3 Circuit • ANSI 0.5 Class Accuracy <ul style="list-style-type: none"> • BACnet/Modbus RTU • Rogowski Coil Input • LCD • Warranty: 5 Years 	N2-KW350-P1-D-S-RC-C	View Data Sheet »
	<ul style="list-style-type: none"> • Power Meter • Bi-Directional • 3 Circuit • ANSI 0.5 Class Accuracy <ul style="list-style-type: none"> • BACnet/Modbus RTU • 333 mV CT Inputs • LCD • Warranty: 5 Years 	N2-KW350-P1-D-S-SC-C	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 20A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-H040-20:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 20A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 10m Leads • Warranty: 5 Years 	N2-AcuCT-H040-20:333-10M	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 30A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-H040-30:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 40A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-H040-40:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 50A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 10m Leads • Warranty: 5 Years 	N2-AcuCT-H040-50:333-10M	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 50A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-H040-50:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 60A • Hinged Split Core • 0.4" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-H040-60:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Hinged Split Core • 1.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-H100-100:333	View Data Sheet »

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Current Transformer • 100A • Hinged Split Core • 1.0" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 10m Leads • Warranty: 5 Years N2-AcuCT-H100-100:333-10M	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 200A • Hinged Split Core • 1.0" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-H100-200:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 200A • Hinged Split Core • 1.0" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 10m Leads • Warranty: 5 Years N2-AcuCT-H100-200:333-10M	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 50A • Split Core • 0.75" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-075-50:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Split Core • 0.75" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-075-100:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Split Core • 1.25" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-125-100:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 300A • Split Core • 1.25" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-125-300:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 400A • Split Core • 1.25" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 10m Leads • Warranty: 5 Years N2-AcuCT-125-400:333-10M	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 400A • Split Core • 1.25" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-125-400:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 600A • Split Core • 1.25" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-125-600:333	View Data Sheet »

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Current Transformer • 600A • Split Core • 2" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200-600:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 800A • Split Core • 2" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200-800:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 1000A • Split Core • 2" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200-1000:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Split Core • 1.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-S77-100:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 200A • Split Core • 1.25" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-S77-200:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 50A • Split Core • 0.75" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-075R-50:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Split Core • 0.75" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-075R-100:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 150A • Split Core • 0.75" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-075R-150:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Split Core • 1.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-100R-100:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 200A • Split Core • 1.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-100R-200:333	View Data Sheet »

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Current Transformer • 250A • Split Core • 1.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-100R-250:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 300A • Split Core • 1.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-125R-300:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 100A • Split Core • 1.25" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-125R-100:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 200A • Split Core • 1.25" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-125R-200:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 400A • Split Core • 1.25" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-125R-400:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 400A • Split Core • 2.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200R-400:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 600A • Split Core • 2.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200R-600:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 800A • Split Core • 2.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200R-800:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 1000A • Split Core • 2.0" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-200R-1000:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 1000A • Split Core • 3.1"x3.5" Aperture <ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years 	N2-AcuCT-3135R-1000:333	View Data Sheet »

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Current Transformer • 2000A • Split Core • 4.1"x6.1" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-4161R-2000:333	View Data Sheet »
	<ul style="list-style-type: none"> • Current Transformer • 4000A • Split Core • 5.1"x7.0" Aperture 	<ul style="list-style-type: none"> • 333mV Output • 2.5m Leads • Warranty: 5 Years N2-AcuCT-5170R-4000:333	View Data Sheet »
	<ul style="list-style-type: none"> • 16" Rogowski Coil • 5 to 1200A • 4.17" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT16-1000	View Data Sheet »
	<ul style="list-style-type: none"> • 16" Rogowski Coil • 12.5 to 3000A • 4.17" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT16-2500	View Data Sheet »
	<ul style="list-style-type: none"> • 24" Rogowski Coil • 5 to 1200A • 4.17" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT24-1000	View Data Sheet »
	<ul style="list-style-type: none"> • 24" Rogowski Coil • 12.5 to 3000A • 7.01" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT24-2500	View Data Sheet »
	<ul style="list-style-type: none"> • 24" Rogowski Coil • 25 to 6000A • 7.01" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT24-5000	View Data Sheet »
	<ul style="list-style-type: none"> • 36" Rogowski Coil • 5 to 1200A • 10.67" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT36-1000	View Data Sheet »
	<ul style="list-style-type: none"> • 36" Rogowski Coil • 12.5 to 3000A • 4.17" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT36-2500	View Data Sheet »
	<ul style="list-style-type: none"> • 47" Rogowski Coil • 12.5 to 3000A • 14.5" Window 	<ul style="list-style-type: none"> • mV Output • 6.5'Leads • Warranty: 5 Years N2-RCT47-2500	View Data Sheet »

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • 36" Rogowski Coil • 25 to 6000A • 10.67" Window <ul style="list-style-type: none"> • mV Output • 6.5' Leads • Warranty: 5 Years 	N2-RCT36-5000	View Data Sheet »
	<ul style="list-style-type: none"> • 47" Rogowski Coil • 25 to 6000A • 14.5" Window <ul style="list-style-type: none"> • mV Output • 6.5' Leads • Warranty: 5 Years 	N2-RCT47-5000	View Data Sheet »
	<ul style="list-style-type: none"> • Wall Mount Enclosure • NEMA 4X/IP66 <ul style="list-style-type: none"> • Steel Mounting Plate • Warranty: 2 Years 	N2-KW1850-ENC	View Data Sheet »
	<ul style="list-style-type: none"> • Wall Mount Enclosure • NEMA 4X/IP66 • DIN Rail <ul style="list-style-type: none"> • Swing Panel Kit • Tamper Proof Locking • Warranty: 2 Years 	N2-KW350-ENC-C	View Data Sheet »
	<ul style="list-style-type: none"> • Panel Upgrade • NEMA 4X Enclosure • Bi-Directional • Prewired supply voltage <ul style="list-style-type: none"> • 3 Circuit • Rogowski Coil Input • ANSI 0.5 Class Accuracy • Warranty: 5 Years 	N2-KW350-P1-D-S-RC-PC-C	View Data Sheet »
	<ul style="list-style-type: none"> • Panel Upgrade • NEMA 4X Enclosure • Bi-Directional • Prewired supply voltage <ul style="list-style-type: none"> • 3 Circuit • 333 mV CT Inputs • ANSI 0.5 Class Accuracy • Warranty: 5 Years 	N2-KW350-P1-D-S-SC-PC-C	View Data Sheet »
	<ul style="list-style-type: none"> • Power Quality Meter • 3 Circuit • ANSI 0.1 Class Accuracy • Serial/Ethernet <ul style="list-style-type: none"> • Data Logging • LCD • Warranty: 5 Years 	N2-KW320-P1-D-W-XX-C	View Data Sheet »
	<ul style="list-style-type: none"> • Power Quality Meter • 3 Circuit • ANSI 0.1 Class Accuracy • Serial/Ethernet <ul style="list-style-type: none"> • NEMA 4X Enclosure • Pre-wired/Factory Installed • Warranty: 5 Years 	N2-KW320-P1-D-W-PC-C	View Data Sheet »
	<ul style="list-style-type: none"> • Power Meter Accessory • DIN Rail Adaptor <ul style="list-style-type: none"> • Warranty: 5 Years 	N2-AXM-DIN	View Data Sheet »
	<ul style="list-style-type: none"> • Power Meter Accessory • RS485 to USB Converter <ul style="list-style-type: none"> • Warranty: 5 Years 	N2-USB-RS485	No Data Sheet

POWER METERS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Power Meter Accessory • Three Pack Inline Fuse Kit <ul style="list-style-type: none"> • 600V • 2A (Slow Blow) • Warranty: 5 Years 	N2-AK-03	View Data Sheet »
	<ul style="list-style-type: none"> • Power Meter • 18 Circuit • ANSI 0.5Class Accuracy • Serial/Ethernet <ul style="list-style-type: none"> • Rogowski • Split/Solid Core • 333 mV • Warranty: 5 Years 	N2-KW1850-P1-D-S-PC	View Data Sheet »
	<ul style="list-style-type: none"> • Panel Upgrade • NEMA 4x • ANSI 0.5Class Accuracy • Serial/Ethernet <ul style="list-style-type: none"> • Labeled and prewired supply voltage • 333 mV • Warranty: 5 Years 	N2-KW1850-P1-D-W-PC	View Data Sheet »
	<ul style="list-style-type: none"> • SnapOn CT Replacement Connector Kit <ul style="list-style-type: none"> • Qty:20 • Warranty: 5 Years 	N2-SO-SP1	View Data Sheet »

GAS

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • CO2 Room Sensor • 0 to 2,000 ppm • 10K Type II Thermistor 	<ul style="list-style-type: none"> • 0-5, 0-10VDC, 4-20mA • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CO2-R2-CP-C	View Data Sheet »
	<ul style="list-style-type: none"> • CO2 Room Sensor • 0 to 2,000 ppm • 10K Type II Thermistor • Override 	<ul style="list-style-type: none"> • 0-5, 0-10VDC, 4-20mA • STD Lead Time: 5 Days • Warranty: 5 Year 	NSA-HH/CO2-R2O-CP-C	View Data Sheet »
	<ul style="list-style-type: none"> • CO2 Room Sensor • 0 to 2,000 ppm • 10K Type II Thermistor • Setpoint 	<ul style="list-style-type: none"> • Overide • 0-5, 0-10VDC, 4-20mA • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-HH/CO2-R2SO-CP-C	View Data Sheet »
	<ul style="list-style-type: none"> • CO2, Temperature • Relay • Space • LCD 	<ul style="list-style-type: none"> • 0-10, 2-10VDC, 4-20, 0-20mA • STD Lead Time: 10 Days • Warranty: 2 Year 	NSA-ASENSE-R-LCD-REL	View Data Sheet »
	<ul style="list-style-type: none"> • CO2, Temperature • Space • LCD 	<ul style="list-style-type: none"> • 0-10, 2-10VDC, 4-20, 0-20mA • STD Lead Time: 10 Days • Warranty: 2 Year 	NSA-ASENSE-R-LCD	View Data Sheet »
	<ul style="list-style-type: none"> • CO2 Duct • 0 to 2,000 ppm • 0-5, 0-10VDC, 4-20mA 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	NSA-A/CO2-DUCT	View Data Sheet »
	<ul style="list-style-type: none"> • CO2 • Relay, Duct • 0 to 2K ppm (Std) • 10K ppm (max) 	<ul style="list-style-type: none"> • 0-10, 2-10VDC, 4-20, 0-20mA • STD Lead Time: 20 Days • Warranty: 2 Year 	NSA-ASENSE-D-REL	View Data Sheet »
	<ul style="list-style-type: none"> • CO2 • Relay • Duct • LCD 	<ul style="list-style-type: none"> • 0 to 2K ppm (Std) • 10K ppm (max) • STD Lead Time: 20 Days • Warranty: 2 Year 	NSA-ASENSE-D-LCD-REL	View Data Sheet »
	<ul style="list-style-type: none"> • Aspiration Box (use with 33ZCSPTCO2-01 or 33ZCSPTCO2LCD-01 for duct mounting) • STD Lead Time: 10 Days • Warranty: 2 Years 		NSA-ASPIRATION BOX	No Data Sheet
	<ul style="list-style-type: none"> • ASENSE CO2 USB CAL CABLE 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-TTL-232R-3V3	No Data Sheet

GAS

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Smart Sensor w/ 3 SPDT Relays • NEMA 4X • 4-20mA Modbus RTU • Carbon Monoxide <ul style="list-style-type: none"> • 0-250 ppm • ETL • NEMA 4X • STD Lead Time: 20 Days • Warranty: 2 Years 	NSA-Q5C-CO-250P-O-X	View Data Sheet »
	<ul style="list-style-type: none"> • Smart Sensor w/ 3 SPDT Relays • NEMA 4X • 4-20mA Modbus RTU • Nitrogen Dioxide <ul style="list-style-type: none"> • 0-10 ppm • NEMA 4X • STD Lead Time: 20 Days • Warranty: 2 Years 	NSA-Q5-NO2-10P-O-X	View Data Sheet »
	<ul style="list-style-type: none"> • Q5/B5 PUMP KIT/CAL ADAPTER <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-85930-006-000	View Data Sheet »
	<ul style="list-style-type: none"> • Q5/B5 DUCT MOUNT KIT <ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 2 Years 	NSA-85930-040-000	View Data Sheet »
	<ul style="list-style-type: none"> • B5 to Q5 CO Repl Sensor Module 0-250ppm <ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 2 Year 	NSA-85930-018-001	View Data Sheet »
	<ul style="list-style-type: none"> • B5 to Q5 NO2 Repl Sensor Module 0-10ppm <ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 2 Year 	NSA-85930-018-005	View Data Sheet »
	<ul style="list-style-type: none"> • VOC • Duct Mount • 4-20 mA and 0-10 VDC • Modbus RS-485 <ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 2 Year 	N2-VOC-D	View Data Sheet »
	<ul style="list-style-type: none"> • VOC • Room Mount • 4-20 mA and 0-10 VDC • Modbus RS-485 <ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 2 Year 	N2-VOC-R	View Data Sheet »
	<ul style="list-style-type: none"> • VOC • Room Mount • 4-20 mA and 0-10 VDC • Modbus RS-485 <ul style="list-style-type: none"> • Relay • LCD • STD Lead Time: 10 Days • Warranty: 2 Year 	N2-VOC-R-LCD	View Data Sheet »
	<ul style="list-style-type: none"> • PM2.5 • Duct Mount • 4-20 mA and 0-10 VDC • Modbus RS-485 <ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 2 Year 	N2-PM-D	View Data Sheet »

GAS

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • PM2.5 • Room Mount • 4-20 mA and 0-10 VDC • Modbus RS-485 	<ul style="list-style-type: none"> • STD Lead Time: 10 Days • Warranty: 2 Year 	N2-PM-R	View Data Sheet »
	<ul style="list-style-type: none"> • PM2.5 • Room Mount • 4-20 mA and 0-10 VDC • Modbus RS-485 	<ul style="list-style-type: none"> • Relay • LCD • STD Lead Time: 10 Days • Warranty: 2 Year 	N2-PM-R-LCD	View Data Sheet »

BACNET

	Product Description		Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • BACnet MSTP • Smart Sensor w/3 SPDT Relays - NEMA X • Carbon Monoxide 	<ul style="list-style-type: none"> • 0-250 ppm • ETL • STD Lead Time: 20 Days • Warranty: 2 Years 	N2-B5C-CO-250P-O-X	View Data Sheet »
	<ul style="list-style-type: none"> • BACnet MSTP • Smart Sensor w/3 SPDT Relays - NEMA X • CO: 0-250 ppm 	<ul style="list-style-type: none"> • Remote NO2: 0-10 ppm • STD Lead Time: 20 Days • Warranty: 2 Years 	N2-B6-CO/NO2-10P	View Data Sheet »
	<ul style="list-style-type: none"> • BACnet MSTP • Smart Sensor w/3 SPDT Relays - NEMA X • Nitrogen Dioxide 	<ul style="list-style-type: none"> • 0-10 ppm • STD Lead Time: 20 Days • Warranty: 2 Years 	N2-B5-NO2-10P-O-X	View Data Sheet »
	<ul style="list-style-type: none"> • BACnet MSTP • Modbus RTU • Temperature 	<ul style="list-style-type: none"> • Room (R2) • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-BN2110-R2-C	View Data Sheet »
	<ul style="list-style-type: none"> • BACnet/Modbus • Temperature • Duct 	<ul style="list-style-type: none"> • STD Lead Time: 5 Days • Warranty: 5 Years 	N2-BN2110-D-4-PB-C	View Data Sheet »

MISC. DEVICES

	Product Description	Carrier Part #	Carrier Data Sheet
	<ul style="list-style-type: none"> • Liquid Flow Switch, • IP65 • Paddle Kit <ul style="list-style-type: none"> • 1-8" Pipe Size • Warranty 5: Years 	N2-SF1K-US	View Data Sheet »
	<ul style="list-style-type: none"> • 24V Power Supply • STD Lead Time: 5 Days <ul style="list-style-type: none"> • Warranty 5: Years 	NSA-A/PS24-24V-S	View Data Sheet »
	<ul style="list-style-type: none"> • Spot Leak Detector • Relay Output <ul style="list-style-type: none"> • 14'/4.26m lead • Warranty 5: Years 	N2-A/SLD	View Data Sheet »