


GSLC for AppController

Installation and Start-up Guide





Verify that you have the most current version of this document from www.hvacpartners.com, the Carrier Partner Community website, or your local Carrier office.

Important changes are listed in **Document revision history** at the end of this document.

CARRIER CORPORATION ©2021. All rights reserved throughout the world. i-Vu is a registered trademark of Carrier Corporation. All other trademarks are the property of their respective owners.



Contents

GSLC overview and specifications	1
What is the GSLC application?	1
Specifications	2
Safety considerations.....	3
Installing the GSLC	4
Mounting the controller	4
Wiring the controller for power.....	5
To wire for power.....	5
Addressing the controller	6
Wiring for communications.....	6
Wiring specifications for BACnet MS/TP and ARC156.....	6
To wire the controller to the BACnet network.....	7
Wiring inputs and outputs	8
Inputs and outputs table.....	8
Input wiring specifications	9
Inputs.....	9
Binary outputs.....	9
Analog outputs	10
To wire inputs and outputs.....	10
Wiring devices to the controller's Rnet port	12
To wire an Equipment Touch to the controller	12
To wire the TruVu™ ET Display.....	13
Wiring equipment to outputs	15
Wiring specifications.....	15
Wiring diagram legend	16
Single pump constant speed with status switch feedback (option).....	16
Single pump constant speed with 0-5 Vdc amp status feedback (option).....	17
Single pump with VFD loop differential pressure control and 0-5 Vdc amp status feedback (option)	17
Single pump with bypass loop differential pressure control and 0-5 Vdc amp status feedback (option).....	18
2 pumps with 2 VFDs, loop differential pressure control and no status feedback	18
Start-up	19
Select the GSLC control program and graphic	19
Configure the controller's properties	19
Sequence of Operation	20
Scheduling without Condenser Water Linkage.....	20
Scheduling with Condenser Water Linkage.....	21
Constant flow pump control.....	22
Loop pump(s) constant flow.....	22
Loop Pump(s) with bypass valve differential pressure control.....	23
Loop Pump(s) with VFD loop differential pressure control.....	23
Two loop pumps with VFDs, lead/lag operation for loop differential pressure control.....	24
Pump rotation	24
Alarm lamp output	25
WSHP compressor enable command output.....	25
Condenser Water Linkage	25
Troubleshooting	26
LED's	26
Serial number.....	27
To replace the controller's battery	27
Compliance	28


FCC Compliance.....	28
CE Compliance	28
BACnet Compliance.....	28
Appendix A: GSLC wire list	29
Appendix B: Device Address Binding.....	30
Appendix C: GSLC Points/Properties	31
Status.....	31
Unit Configuration.....	32
Setpoints	33
Alarm Configuration	34
Service Configuration	35
Maintenance.....	39
Alarms	40
Linkage.....	41
I/O Points	41
Appendix D: GSLC Points/Properties on the Equipment Touch.....	43
Navigation screens	43
Startup Wizard	45
Document revision history.....	47

GSLC overview and specifications

What is the GSLC application?


The Ground Source Loop Control (GSLC) is a field-installed application that is designed to be loaded into an AppController that provides control of the pump operation in a ground source heat pump system. The ground source loop control supplies or removes energy from the source water for the heat pumps. The GSLC can control 1 pump or 2 pumps in a constant-flow application, or up to 2 pumps in a variable-flow source water application, maintaining the loop pressure differential setpoint.

The internal application programming provides loop pump operation based on heat pump demand and/or scheduling. This controller can be used in stand-alone mode, communicate to an i-Vu® Control System, or a BACnet Third Party Building Automation System (BAS).



Specifications

Power	24 Vac $\pm 10\%$, 50–60 Hz 20 VA power consumption 26 Vdc (25 V min, 30 V max) Single Class 2 source only, 100 VA or less
BACnet Port	For communication with the controller network using BACnet ARC156 (156 kbps) or BACnet MS/TP (9600 bps – 76.8 kbps)
Rnet port	Supports one Equipment Touch or one TruVu™ ET Display.
NOTES	
<ul style="list-style-type: none"> Equipment Touch or TruVu™ ET Display must be powered by an external power source. The GSLC application does not support the ZS or Wireless sensor. 	
Local Access port	For system start-up and troubleshooting using Field Assistant
Inputs	6 inputs configurable for thermistor or dry contact. 1 and 2 are also configurable for 0–5 Vdc sensors.
NOTE 7 and 8 are unused.	
Input resolution	10 bit A/D
Analog outputs	3 analog outputs, 0–10 Vdc (5 mA max)
Binary outputs	5 binary outputs, dry relay contacts rated at 1 A max. @ 24 Vac/Vdc. Configured normally open
Output resolution	8 bit A/D, using filtered PWM
Real time clock	Battery-backed real time clock keeps track of time in the event of a power failure
Battery	10-year Lithium CR2032 battery retains the following data for a maximum of 10,000 hours during power outages: control programs, editable properties, schedules, and trends.
Protection	<p>Built-in surge and transient protection for power and communications in compliance with EN61000-6-1.</p> <p>Incoming power and network connections are protected by non-replaceable internal solid-state polyswitches that reset themselves when the condition that causes a fault returns to normal.</p> <p>The power, network, input, and output connections are also protected against transient excess voltage/surge events lasting no more than 10 msec.</p>
 CAUTION To protect against large electrical surges on serial EIA-485 networks, place a PROT485 at each place wire enters or exits the building.	
Status indicators	LEDs indicate status of communications, running, errors, and power.
Environmental operating range	0 to 130°F (-18 to 54°C), 0 to 90% relative humidity, non-condensing
Storage temperature range	-24 to 140°F (-30 to 60°C), 0 to 90% relative humidity, non-condensing
Physical	Rugged GE C2950HF Cyclooy plastic



Overall dimensions	A: B:	5-5/8 in. (14.3 cm) 5-1/8 in. (13 cm)
Mounting dimensions	C: D: E:	5-1/4 in. (13.3 cm) 2-9/16 in. (6.5 cm) 3/16 in. (.5 cm)
Panel depth	2 in. (5.1 cm)	
Weight	0.44 lbs. (0.20 kg)	
BACnet support	Conforms to the BACnet Advanced Application Controller (B-AAC) Standard Device Profile as defined in ANSI/ASHRAE Standard 135-2012 (BACnet) Annex L, Protocol Revision 9	
Listed by	UL-916 (PAZX), cUL-916 (PAZX7), FCC Part 15-Subpart B-Class A, CE	

Safety considerations



WARNING Disconnect electrical power to the controller before wiring it. Failure to follow this warning could cause electrical shock, personal injury, or damage to the controller.

Installing the GSLC

- 1** Mount the controller (page 4).
- 2** Wire the controller for power (page 5).
- 3** Set the controller's address (page 6).
- 4** Wire the controller to the BACnet MS/TP or BACnet ARC156 network (page 6).
- 5** Wire inputs and outputs (page 8).
- 6** Wire equipment to outputs (page 15).


Mounting the controller

WARNING

When you handle the controller:

- Do not contaminate the printed circuit board with fingerprints, moisture, or any foreign material.
- Do not touch components or leads.
- Handle the board by its edges.
- Isolate from high voltage or electrostatic discharge.
- Ensure that you are properly grounded.

Screw the controller into an enclosed panel using the mounting slots on the coverplate. Leave about 2 in. (5 cm) on each side of the controller for wiring. Mounting hole dimensions 5 9/16" (14.1 cm) between mounting slot center lines.



Wiring the controller for power



WARNING Do not apply line voltage (mains voltage) to the controller's ports and terminals.



CAUTIONS

- The controller is powered by a Class 2 power source. Take appropriate isolation measures when mounting it in a control panel where non-Class 2 circuits are present.
- Carrier controllers can share a power supply as long as you:
 - Maintain the same polarity.
 - Use the power supply only for Carrier controllers.

To wire for power


- 1 Remove power from the power supply.
- 2 Pull the screw terminal connector from the controller's power terminals labeled **Gnd** and **Hot**.
- 3 Connect the transformer wires to the screw terminal connector.
NOTE If using a grounded transformer, connect the ungrounded lead to the **Hot** terminal to avoid damaging the transformer.
- 4 Apply power to the power supply.
- 5 Measure the voltage at the controller's power input terminals to verify that the voltage is within the operating range of 21.6–26.4 Vac.
- 6 Insert the screw terminal connector into the controller's power terminals.
- 7 Verify that the **Power** LED is on and the **Run** LED is blinking.

Addressing the controller

You must give the controller an address that is unique on the network. You can address the controller before or after you wire it for power.

- 1 If the controller has been wired for power, pull the screw terminal connector from the controller power terminals labeled **Gnd** and **Hot**. The controller reads the address each time you apply power to it.
- 2 Using the rotary switches, set the controller address. Set the **Tens (10's)** switch to the tens digit of the address, and set the **Ones (1's)** switch to the ones digit.

EXAMPLE If the controller's address is 25, point the arrow on the **Tens (10's)** switch to 2 and the arrow on the **Ones (1's)** switch to 5.



CAUTION The factory default setting is **00** and must be changed to successfully install your controller.

Wiring for communications

The controller communicates using BACnet on the following types of network segments:

- MS/TP communicating at 9600 bps, 19.2 kbps, 38.4 kbps, or 76.8 kbps
- ARC156 communicating at 156 kbps

NOTE For more networking details, see the *Open Controller Network Wiring Installation Guide*.

Wiring specifications for BACnet MS/TP and ARC156

Cable: 22 AWG or 24 AWG, low-capacitance, twisted, stranded, shielded copper wire

Maximum length: 2000 feet (610 meters)



WARNING Do not apply line voltage (mains voltage) to the controller's ports and terminals.

To wire the controller to the BACnet network

- 1 Pull the screw terminal connector from the controller's power terminals labeled **24 Vac** and **Gnd (Return)**.
- 2 Check the communications wiring for shorts and grounds.
- 3 Connect the communications wiring to the controller's screw terminals labeled **Net +**, **Net -**, and **Shield**.

NOTE Use the same polarity throughout the network segment.

- 4 Set the communication type and baud rate.

For...	Set Communications Selection Jumper to...	Set DIP switches 1 and 2 to...	Set DIP switches 3 and 4 to...
MS/TP	BACnet MS/TP	The appropriate baud rate. See the MS/TP Baud diagram on the controller.	Off/Off
ARC156	BACnet ARC156	N/A. Baud rate will be 156 kbps regardless of the DIP switch settings.	Off/Off

NOTE Use the same baud rate for all controllers on the network segment.

- 5 Wire the controllers on a BACnet MS/TP or BACnet ARC156 network segment in a daisy-chain configuration.
- 6 If the controller is at either end of a network segment, connect a BT485 to the controller.
- 7 Insert the power screw terminal connector into the controller's power terminals.
- 8 Verify communication with the network by viewing a Module Status report in the i-Vu® interface.

Wiring inputs and outputs



WARNING Do not apply line voltage (mains voltage) to the controller's ports and terminals.

See Appendix A (page 29) to print a blank wire list.

Inputs and outputs table

Depending on the configuration of the GSLC application, the available I/O points change. For variable flow applications such as the bypass valve control or VFD pump control, the **Source Water Diff. Pressure** (I/O Points (page 41)) AI input on Channel #2 is valid and available only if the **Pump Status Type** (Service Configuration (page 35)) is set to **None** or **Network**. Otherwise, you must use a network input to obtain the source water differential pressure value.

I/O	Type	I/O Terminal	Gnd Terminal	Point Name/Function	Hardware/Signal	Jumper Position of Pins					
Pump 1 Amp Sensor	AI	IN-1*	2 - Gnd	Pump 1 Motor Amps	0-5 Vdc	IN-1 Bottom					
Pump 1 Status	BI	IN-1*	2 - Gnd	Pump 1 Status Switch	Dry Contact	IN-1 Top					
Pump 2 Amp Sensor	AI	IN-2*	4 - Gnd	Pump 2 Motor Amps	0-5 Vdc	IN-2 Bottom					
Pump 2 Status	BI	IN-2*	4 - Gnd	Pump 2 Status Switch	Dry Contact	IN-2 Top					
Source Water Diff. Pressure	AI	IN-2*	4 - Gnd	Source Water Differential Pressure	0-5 Vdc	IN-2 Bottom					
Source Water Flow	BI	IN-3	6 - Gnd	Source Water Flow Switch	Dry Contact	N/A					
Remote Contact Input	BI	IN-4	8 - Gnd	Remote Occupancy Contact	Dry Contact	N/A					
Source Return Water Temp	AI	IN-5	1 - Gnd	Source Return Water Temperature	10K Thermistor	N/A					
Source Supply Water Temp	AI	IN-6	1 - Gnd	Source Supply Water Temperature	10K Thermistor	N/A					
<hr/>											
Pump 1 VFD Output	AO	AO-1*	2 - Gnd	Pump 1 VFD	0-10 Vdc 2-10 Vdc	N/A					
Byp Vlv Output	AO	AO-2*	4 - Gnd	Bypass Valve	0-10 Vdc 2-10 Vdc	N/A					
Pump 2 VFD Output	AO	AO-3*	6 - Gnd	Pump 2 VFD	0-10 Vdc 2-10 Vdc	N/A					
<hr/>											
Pump 1 S/S	BO	BO-1	1 - Pwr	Pump 1 Start/Stop	Relay	N/A					
Pump 2 S/S	BO	BO-2*	1 - Pwr	Pump 2 Start/Stop	Relay	N/A					
WSHP Comp Command	BO	BO-3	1 - Pwr	Enable WSHP Compressor Operation	Relay	N/A					
Alarm	BO	BO-4	1 - Pwr	Alarm Indication	Relay	N/A					
Legend											
AI - Analog Input		AO - Analog Output									
BI - Binary Input		BO - Binary Output									
<hr/>											
*Channel use is determined by specific application configuration.											

Input wiring specifications

Input	Maximum length	Minimum gauge	Shielding
0-5 Vdc	500 feet (152 meters)	22 AWG	100 feet (30.4 meters) unshielded 100 - 500 feet shielded
Thermistor Dry contact	500 feet (152 meters)	22 AWG	100 feet (30.4 meters) unshielded
Pulse counter TLO			100 - 500 feet shielded
Equipment Touch device	See <i>Wiring devices to the controller's Rnet port (page 12)</i> .		
TruVu™ ET Display			

Inputs

The controller has 6 inputs that accept the following signal types.

These inputs...	Support this signal type...	Description
All	Thermistor	Precon type 2 (10 kOhm at 77°F/25°C) Input voltage for IN-5: 1 to 2.52 Vdc Input voltage for all other inputs: 0.33 to 2.52 Vdc
All	Dry contact	A 3.3 Vdc wetting voltage detects contact position, resulting in a 0.3 mA maximum sense current when the contacts are closed.
IN-1, IN-2	0-5 Vdc	The input impedance of the controller is approximately 30 kOhm.
All	Pulse counter	Pulse counting up to 10 pulses per second. Minimum pulse width (on or off time) required for each pulse is 50 msec.

Binary outputs

The controller has 5 binary outputs. You can connect each output to a maximum of 24 Vac/26 Vdc. Each output is a dry contact rated at 1 A, 24 V maximum and is normally open.

To size output wiring, consider the following:

- Total loop distance from the power supply to the controller, and then to the controlled device

NOTE Include the total distance of actual wire. For 2-conductor wires, this is twice the cable length.
- Acceptable voltage drop in the wire from the controller to the controlled device
- Resistance (Ohms) of the chosen wire gauge
- Maximum current (Amps) the controlled device requires to operate

Analog outputs

The controller has 3 analog outputs that support voltage. The controlled device must share the same ground as the controller and have the following input impedance:

0-10 Vdc Minimum impedance 2000 Ohms, max 5 mA


NOTE Ohm's law: $-10V/.005a = 2000$ Ohms

To wire inputs and outputs

- 1 Pull the screw terminal connector from the controller's power terminals labeled **Gnd** and **Hot**.
- 2 Connect the input wiring to the screw terminals on the controller.


NOTES

- o Connect the shield wire to the **GND** terminal with the ground wire.
- o **IN-5** and **IN-6** share the **GND** terminal above **IN-5**.




3 Set the appropriate jumpers on the controller.


To use...	For...	
IN-1	Thermistor	Set jumpers IN-1 to the Therm position.
IN-1	0-5 Vdc	Set jumpers IN-1 to the 0-5 Vdc position.
IN-2	Thermistor/ Dry contact	Set jumpers IN-2 to the Thermistor/Dry contact position.
All	Thermistor Dry contact	Verify the IN-5 jumper is on.
Rnet Port	Equipment Touch	Set the Rnet jumper to Rnet .
	TruVu™ ET Display	



4 Connect the analog output wiring to the screw terminals on the controller and to the controlled device.



5 Connect the binary output wiring to the screw terminals on the controller and to the controlled device.



6 Insert the power screw terminal connector into the controller's power terminals.

Wiring devices to the controller's Rnet port

The Rnet communicates at a rate of 115 kbps and should be wired in a daisy-chain configuration to one Equipment Touch or one TruVu™ ET Display, which must be powered by an external power source.

To wire an Equipment Touch to the controller

Power wiring

2-conductor wire 18 AWG for distances up to 100 feet. All transformer secondaries must be grounded. Wiring connections must be in accordance with NEC and local codes.

The Equipment Touch cannot be powered by the Rnet. It requires a 24 Vac ($\pm 15\%$), 5 VA, 50–60 Hz, Class 2 external power supply.

Rnet wiring

NOTE If you wire the Equipment Touch directly to the controller's Rnet port, you can use a 2-conductor cable instead of the standard 4-conductor Rnet cable.


Description	4-conductor, shielded or unshielded, CMP, plenum rated cable
Conductor	22 AWG (7x0096) bare copper
Maximum length	500 feet (152 meters)
Insulation	Low-smoke PVC (or equivalent)
Color Code	Black, white, green, red
Shielding	If shielded, Aluminum/Mylar shield (100% coverage) with TC drain wire
UL temperature rating	32–167°F (0–75°C)
Voltage	300 Vac, power limited
Listing	UL: NEC CL2P, or better



CAUTION The controller can share a power supply with the Carrier controller as long as:

- The power supply is AC power.
- You maintain the same polarity.
- You use the power source only for Carrier controllers.

- 1 Turn **off** the controller's power.
- 2 Partially cut, then bend and pull off the outer jacket of the cable. Do not nick the inner insulation.



- 3 Strip about 0.25 inch (0.6 cm) of the inner insulation from each wire.
- 4 Wire the controller's **Rnet+** and **Rnet-** terminals to the terminals of the same name on the Equipment Touch's connector.

NOTE If using shielded wire, connect the shield wire and the ground wire to the **Gnd** terminal.

- 5 Turn **on** the controller's power.
- 6 Turn on the Equipment Touch.

For complete Equipment Touch installation instructions including wiring diagrams, see the *Equipment Touch Installation and Setup Guide*.

To wire the TruVu™ ET Display


 **WARNING** Do not apply line voltage (main) - 24 Vdc power only.

Wiring power

Wire the TruVu™ ET Display **24V DC** connector to the 24 Vdc power supply using 2-conductor 18 AWG wire. Maximum distance 100 feet (30 meters).


 **CAUTION** The TruVu™ ET Display can share a power supply with the Carrier controller as long as:

- The power supply is DC power.
- You maintain the same polarity.
- You use the power source only for Carrier controllers.



Wiring communication

- 1 Turn off the controller's power.
- 2 Wire the TruVu™ ET Display's **RS485** connector to the controller's **Rnet** port, **G** to **Gnd**, **+** to **Rnet +**, **-** to **Rnet -** using 2-conductor 22 AWG wire with a maximum distance of 500 feet (152 meters).



- 3 Turn on the controller's power.

For complete TruVu™ ET Display installation instructions, see the *TruVu™ ET Display Installation and Start-up Guide*.

Wiring equipment to outputs

Use the following wiring specifications and diagrams to wire equipment to the controller's outputs:

- *Single pump constant speed with status switch feedback (option) (page 16)*
- *Single pump constant speed with 0-5 Vdc amp status feedback (option) (page 17)*
- *Single pump constant with VFD loop differential control and 0-5 Vdc amp status feedback (option) (page 17)*
- *Single pump with bypass loop differential pressure control and 0-5 Vdc amperage status feedback (option) (page 18)*
- *2 pumps with 2 VFDs, loop differential pressure control and no status feedback (page 18)*

Wiring specifications


To size output wiring, consider the following:

- Total loop distance from the power supply to the controller, and then to the controlled device
NOTE Include the total distance of actual wire. For 2-conductor wires, this is twice the cable length.
- Acceptable voltage drop in the wire from the controller to the controlled device
- Resistance (Ohms) of the chosen wire gauge
- Maximum current (Amps) the controlled device requires to operate


Wiring diagram legend

Abbreviations	
AO	Analog Output
BO	Binary Output (Discrete)
Gnd	Ground
Hot	24 Vac ungrounded power
IN	Input
n/c	No connection
N.C.	Normally closed
N.O.	Normally open
S/S	Start/Stop output
Temp	Temperature
Vac	Volts (Alternating Current)
Vdc	Volts (Direct Current)
VFD	Variable Frequency Drive


Single pump constant speed with status switch feedback (option)




Single pump constant speed with 0-5 Vdc amp status feedback (option)




Single pump with VFD loop differential pressure control and 0-5 Vdc amp status feedback (option)



Single pump with bypass loop differential pressure control and 0-5 Vdc amp status feedback (option)



2 pumps with 2 VFDs, loop differential pressure control and no status feedback



Start-up

Use one of the following interfaces to start up, access information, read sensor values, and test the controller.

This Interface...	Provides a...
Field Assistant application - Runs on a laptop that connects to controller's Local Access port ¹	Temporary interface
Equipment Touch device - Connects to controller's Rnet port ²	Temporary or permanent interface
I-Vu® application Available for BACnet systems only	Permanent interface
System Touch device Available only for BACnet MS/TP systems. Wire to a BACnet MS/TP network connector and a 24 Vac power supply ³	Temporary or permanent interface

¹ Requires a USB Link (Part #USB-L).

² See the *Equipment Touch Installation and Setup Guide* for detailed instructions.

³ See the *System Touch Installation and Setup Guide* for detailed instructions.



CAUTION If multiple controllers share power but polarity was not maintained when they were wired, the difference between the controller's ground and the computer's AC power ground could damage the USB Link and the controller. If you are not sure of the wiring polarity, use a USB isolator between the computer and the USB Link. Purchase a USB isolator online from a third-party manufacturer.

Select the GSLC control program and graphic

The field-installed AppController does not come from the factory with a control program or graphic. You must load a control program and graphic as part of the installation and commissioning. You can select the GSLC control program and graphic from EquipmentBuilder. All the configurations that are currently available for the GSLC are included in a single download file for both the equipment and graphic.

After selecting the control program and graphic files, save and download them to the AppController. If desired, you can create a custom graphic using ViewBuilder. See ViewBuilder Help for details.

Configure the controller's properties

You must configure certain points and properties. Appendix C (page 31) is a complete list of all the points and properties, with descriptions, defaults, and ranges. These properties affect the unit operation and/or control. Review and understand the meaning and purpose of each property before changing it.

To start up the controller, configure your necessary points/properties in the following:

- Unit Configuration
- Setpoints
- Service Configuration

Examples of some settings that you need to configure for start-up are the **Number of Pumps**, **Pump Control**, and **Pump Staging**, found in the **Service Configuration** (page 35) section of Appendix C (page 31).

Sequence of Operation

The Ground Source Loop Control (GSLC) is an application that is designed to control the pump operation in a ground source heat pump system. The pumps provide water loop circulation while the ground source loop supplies or removes energy from the source water for the heat pumps. The GSLC can control one pump or two pumps in a constant-flow application, or up to two pumps in a variable-flow source water application, maintaining the loop pressure differential setpoint.

The GSLC supports Carrier Condenser Water Linkage between Carrier Open WSHP units and the GSLC. When Linkage is active, the loop controller responds to the demands for heating or cooling from the Open WSHPs and will operate the pump(s) when required. The system provides closed loop feedback to the individual WSHPs by confirming source water availability prior to operating any compressors in the Carrier Open WSHPs. Also the GSLC receives the acceptable range of the source water temperature from the Carrier Open WSHPs and verifies that the water provided is within the required operating temperature range.

The GSLC may also be used as a standalone loop control without Carrier Linkage and utilize a third party BACnet system for control or operate in a standalone mode providing a hardwire binary input to command the loop pump operation and a hardwire binary output (WSHP Comp Command) to confirm successful loop operation.

The following sections describe the GSLC's functionality. All points in this sequence of operation refer to the Equipment Touch, i-Vu®, or Field Assistant interface.

Scheduling without Condenser Water Linkage

Scheduling

The GSLC MUST be occupied for loop pump operation. The occupied time periods define when the pump(s) operate. The GSLC operates the pumps continuously during the occupied period.

You must provide a source for occupancy by:

- configuring a **Time Schedule**
- mapping **System Occupancy** to a BACnet point
- utilizing the **Remote Contact Input**
- using a third party control system that **Enables/Disables** the **BAS On/Off** point
- setting the local time and date for the schedule to function and operate properly

You can change the occupancy source to one of the following:

- **Occupancy Schedules**

The controller is occupied 24/7 until you configure a time schedule using the Equipment Touch, Field Assistant, the i-Vu® application, or until a third party control system **Enables/Disables** the **BAS On/Off** point. You can disable the local occupancy default operation by going to **Configuration > Unit Configuration > Occupancy Schedules** and changing the point from **Enable** to **Disable** and clicking **OK**.

NOTE You must **Enable** this point in order for the Equipment Touch, Field Assistant, or the i-Vu® application to assign a time schedule to the controller.

- **Schedule**

The unit operates according to the schedule configured and stored in the unit. The schedule is accessible in the Equipment Touch, Field Assistant, or the i-Vu® application. The daily schedule consists of a start and stop time (standard or 24-hour mode) and 7 days of the week, starting with Monday and ending on Sunday. Enable the **Occupancy Schedules** to use the occupancy scheduling.

- **Occupancy Input Contact** (optional)

If configured for remote occupancy control (default), the controller can use an external dry contact closure to determine the occupancy status of the GSLC. Disable the **Occupancy Schedules** to use the occupancy contact input.

NOTE Scheduling can only be controlled from one source.

- **BAS (Building Automation System) On/Off**

For use with a Building Automation System that supports network scheduling, you must disable the **Occupancy Schedules** so the BAS can control the unit through a network communication and the BAS scheduling function.

NOTE Scheduling can either be controlled from the unit or the BAS, but not both.

- **System Occupancy**

Uses the network to obtain an occupancy status value from another controller, which is read over the network and used by this controller. **Occupancy Schedules** MUST be set to **Disable** to use this function. See *Device Address Binding* (page 6) to configure the **System Occupancy** point.

NOTE Scheduling can only be controlled from one source.

Scheduling with Condenser Water Linkage

When the GSLC is part of a Carrier Open WSHP system and **Condenser Water Linkage** is active, you can configure how the loop pumps operate. The system can be configured to start the pumps only on a heating or cooling demand from any of the Carrier WSHPs linked to the GSLC by setting the **Pump Start to Demand**.

You can configure it to operate the loop pumps on any demand and/or continuously during the occupied period, as defined by the Open WSHPs' schedules that are connected through Linkage. No local occupancy scheduling is available when Linkage is active.

Constant flow pump control

You can configure the GSLC to operate 1 or 2 constant speed loop pumps.

When power is reapplied after a power outage, there is a user-configurable delay of 5 - 600 seconds (default 5) before starting any pump. You must configure **Power Fail Restart Delay** to define the delay time (0 - 600 seconds, default 5) before the pump begins to operate after power has been restored to the controller.

If the **Shutdown** input is active, the pump is shut down after the **Pump Stop Delay** expires, regardless of occupancy state. Otherwise, the pump will operate whenever the occupancy state is determined to be occupied.

Pump Status (Option) - An optional hardware input is available for each pump. You can configure it as either an analog input to detect pump status by measuring the pump current or as a binary input to measure pump state as a discrete input (on/off). Configure each pump separately. Also, there is a Network Status input to read the pump status, if available (See Device Address Binding).

Pump status options include:

- **Switch**
- **Amperage**
- **Network**
- **None**

If the pump status is not configured as None, the controller compares the status of the pump to the desired commanded state. When the pump is commanded to run (ON), the pump status is checked and verified to match the commanded state. If the pump status is not on, then a **Pump 'n' Fall** Alarm ('n' indicates the pump number) is generated after 30 seconds. When the pump is commanded OFF, if the pump status is still on, then a **Pump 'n' In Hand Alarm** is generated after 30 seconds.

Loop pump(s) constant flow

The GSLC operates one or two pumps in constant flow mode to provide source water for the water source heat pumps. For a single pump application, the pump operates as a lead pump whenever the GSLC is in an occupied mode. For two-pump systems, the GSLC is automatically configured to operate the pumps as lead/standby, where the second pump is available as a spare if the lead pump fails.

The following conditions must be true in order for the cooling algorithm to run:

- GSLC is occupied (standalone) or a pump requirement is received from Linkage
- The Shutdown input is not active

If the above conditions are met, the pump is energized, otherwise it is disabled. After the pump output is enabled, if a pump status type is configured, then the pump status will be checked to verify that the actual pump operation matches the commanded state. For two-pump systems, if a pump failure is detected, the GSLC energizes the standby pump and verifies its operation if a pump status type has been selected. An alarm is generated for any pump that has failed.

Loop Pump(s) with bypass valve differential pressure control

The GSLC operates 1 or 2 constant speed pumps in variable flow mode using a bypass valve to control the loop differential pressure and provide source water for the water source heat pumps. For a single pump application, the pump operates as a lead pump whenever the GSLC is in an occupied mode. For 2-pump systems, the GSLC is automatically configured to operate the pumps as lead/standby, where the second pump is available as a spare if the lead pump fails. When the pumps are required to operate, the GSLC monitors the differential loop pressure input and adjusts the bypass valve position to maintain the required loop pressure to meet the desired setpoint.

The following conditions must be true in order for the cooling algorithm to run:

- GSLC is occupied (standalone) or a pump requirement is received from Linkage.
- The **Shutdown** input is not active
- The loop differential pressure input is valid

If the above conditions are met, the pump is energized, otherwise it is disabled. After the pump output is enabled, if a pump status type is configured, then the pump status will be checked to verify that the actual pump operation matches the commanded state. For 2-pump systems, if a pump failure is detected, the GSLC will energize the standby pump and verify its operation if a pump status type has been selected. An alarm is generated for any pump that has failed.

After enabling the pump, the bypass is commanded to the full bypass position. The loop differential pressure is then compared to the desired loop pressure setpoint and a PID calculates the bypass valve position required to meet the loop pressure setpoint.

Loop Pump(s) with VFD loop differential pressure control

The GSLC operates 1 or 2 pumps in variable flow mode using a VFD to control pump speed and provide source water for the water source heat pumps. For a single pump application, the pump operates as a lead pump whenever the GSLC is in an occupied mode. For 2-pump systems, when the GSLC is configured to operate the pumps as lead/standby, the second pump is available as a spare if the lead pump fails. When the pumps are required to operate, the GSLC monitors the differential loop pressure input and adjusts the speed of the lead pump to provide the required loop pressure to meet the desired setpoint.

The following conditions must be true in order for the cooling algorithm to run:

- GSLC is occupied (standalone) or a pump requirement is received from Linkage
- The **Shutdown** input is not active
- The loop differential pressure input is valid

If the above conditions are met, the pump is energized. Otherwise, it is disabled. After the pump output is enabled, if a pump status type is configured, then the pump status is checked to verify that the actual pump operation matches the commanded state. For 2-pump systems, if a pump failure is detected, the GSLC energizes the standby pump and verifies its operation, if a pump status type has been selected. An alarm is generated for any pump that has failed.

After enabling the pump, the VFD is commanded to the user-configured **Min VFD Output** speed. The loop differential pressure is then compared to the desired loop pressure setpoint and a PID calculates the required pump speed to meet the setpoint.

Two loop pumps with VFDs, lead/lag operation for loop differential pressure control

The GSLC operates 2-staged pumps in variable flow mode using a VFD to control pump speed and provide source water for the water source heat pumps. For staged operation, the GSLC Pump Staging must be set to lead/lag, which uses the second pump as a lag pump for additional flow capacity. When the pumps are required to operate, the GSLC monitors the differential loop pressure input and adjusts the number of operating pumps and the speed of the pumps to provide the required loop pressure to meet the desired setpoint.

The following conditions must be true in order for the cooling algorithm to run:

- GSLC is occupied (standalone) or a pump requirement is received from Linkage
- The **Shutdown** input is not active
- The loop differential pressure input is valid

If the above conditions are met, the lead pump is energized, otherwise all pumps are disabled. After the lead pump output is enabled, if a pump status type is configured, then the pump status will be checked to verify the actual pump operation matches the commanded state. If a pump failure is detected, the GSLC will energize the lag pump and verify its operation if a pump status type has been selected. An alarm is generated for any pump that has failed.

After enabling the lead pump, the VFD is commanded to the user-configured **Min VFD Output** speed. The loop differential pressure is then compared to the desired loop pressure setpoint and a PID calculates the required pump speed to meet the setpoint. If the lead pump speed increases above the user-configured setpoint to enable the lag pump (90% default), then the lag pump starts and slowly begins to ramp up to the current VFD commanded output speed. The PID monitors the loop pressure and, as the lag pump increases speed and the loop pressure increases, the PID output is reduced, as necessary, until both pumps achieve the same operating speed.

Lag Pump:

Enable lag pump if control output > **90** %, hyst **25** %.

If the loop flow requirement is reduced, and if both pumps are operating and the VFD speed drops below 65% (the user-configured setpoint minus the configured hysteresis), then the lag pump is disabled.

Pump rotation

The ability to rotate pumps is available for any application with 2 pumps. Pump rotation is user-configured. The following options are available:

- Daily
- Weekly
- Monthly
- Manual Rotation
- Runtime
- Never Rotate

If you select daily, weekly, or monthly, the lead and standby or lag pump rotates as scheduled and on the configured day and time. If you select manual rotation, you must rotate the pumps manually by selecting **Rotate** from the drop-down menu. If you select **Runtime**, the pumps automatically rotate after the lead pump operating hours reach the configured number of hours.

Alarm lamp output

The controller has a binary output that can be connected to a local alarm lamp to indicate a problem with loop flow, the loop pumps, or the source water supply temperature.

If Linkage is inactive, the alarm output is activated whenever the source water supply temperature exceeds the configured **Maximum Source Water Temp** or drops below the configured **Minimum Source Water Temp**. It will also be activated whenever the pumps are commanded to operate and loop flow is not detected or if any pump fails.

If Linkage is active, the alarm output is activated using the same criteria as above, except the source water supply temperature is compared to the minimum and maximum allowable source water temperature limits received from the Open WSHPs through Linkage, rather than the configured values.

WSHP compressor enable command output

The GSLC has a binary output that can be used to interlock the operation of the connected WSHP equipment in standalone application without Linkage. The output determines when the individual WSHP units can safely operate.

The output is activated whenever the pumps are commanded to run and flow has been detected via the Source Water Flow binary input or the Network Flow input.

Condenser Water Linkage

The GSLC receives and sends information through Condenser Water Linkage to operate the source water loop pumps in order to supply water for all the connected water source heat pumps. The GSLC receives the WSHP equipment operating water temperature limits, occupancy, and the total demand for both heating and cooling from all the system equipment.

Troubleshooting

If you have problems mounting, wiring, or addressing the controller, contact Carrier Control Systems Support.

NOTE To help you troubleshoot, obtain a Module Status (Modstat) from the controller and review the System Error and Warning details.

LED's

The LED's indicate if the controller is speaking to the devices on the network. The LED's should reflect communication traffic based on the baud rate set. The higher the baud rate the more solid the LED's become.

Verify the LED patterns by cycling power to the controller and noting the lights and flashes.

LEDs	Status
Power	Lights when power is being supplied to the controller. NOTE The controller is protected by internal solid state Polyswitches on the incoming power and network connections. These Polyswitches are not replaceable, but they will reset themselves if the condition that caused the fault returns to normal.
Rx	Lights when the controller receives data from the network segment; there is an Rx LED for Ports 1 and 2.
Tx	Lights when the controller transmits data from the network segment; there is an Rx LED for Ports 1 and 2.
Run	Lights based on controller health.
Error	Lights based on controller health.

The **Run** and **Error** LED's indicate controller and network status.

If Run LED shows...	And Error LED shows...	Status is...
1 flash per second	1 flash per second, alternating with the Run LED	The controller files are archiving. Archive is complete when Error LED stops flashing.
2 flashes per second	Off	Normal
2 flashes per second	2 flashes, alternating with Run LED	Five minute auto-restart delay after system error
2 flashes per second	3 flashes, then off	The controller has just been formatted
2 flashes per second	4 flashes, then pause	Two or more devices on this network have the same network address
2 flashes per second	1 flash per second	The controller is alone on the network

If Run LED shows...	And Error LED shows...	Status is...
2 flashes per second	On	Exec halted after frequent system errors, due to: <ul style="list-style-type: none"> Controller halted Program memory corrupted One or more programs stopped
5 flashes per second	On	Exec start-up aborted, Boot is running
5 flashes per second	Off	Firmware transfer in progress, Boot is running
7 flashes per second	7 flashes per second, alternating with Run LED	Ten second recovery period after brownout
14 flashes per second	14 flashes per second, alternating with Run LED	Brownout
On	On	Failure. Try the following solutions: <ul style="list-style-type: none"> Turn the controller off, then on. Download memory to the controller. Replace the controller.

NOTE If you resolve the issue but the **Error** LED does not turn off, cycle power to the controller.

Serial number

If you need the controller's serial number when troubleshooting, the number is on a sticker on the back of the main controller board.

To replace the controller's battery

To determine when to replace the battery, remove power and measure the voltage. If the voltage is below 2.9 volts, you need to replace the battery.



CAUTION Power must be **ON** to the controller when replacing the battery, or your date, time, and trend data will be lost.

- 1 Remove the battery from the controller, making note of the battery's polarity.
- 2 Insert the new battery, matching the battery's polarity with the polarity indicated on the controller.

Compliance

FCC Compliance

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.



CAUTION Changes or modifications not expressly approved by the responsible party for compliance could void the user's authority to operate the equipment.

CE Compliance



WARNING This is a Class A product. In a domestic environment, this product may cause radio interference in which case the user may be required to take adequate measures.

BACnet Compliance

Compliance of listed products to requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL® is a registered trademark of BACnet International.

Appendix A: GSLC wire list

Open System Network - GSLC									
Project Name: Location:				Controller: Network Number: MAC Address:					
 Thermistor/dry contact  0-5Vdc									
Point/ Cable#	Inputs (+)	(G)	Input Type	Jumper Position of Pins	I/O	Sensor code	Equipment Name	Point Name	
IN-1	Gnd	Therm/Dry Contact	Upper	IN-1	IN-1				
	Gnd	0-5Vdc	Lower						
IN-2	Gnd	Therm/Dry Contact	Upper	IN-2	IN-2				
	Gnd	0-5Vdc	Lower						
IN-3	Gnd	Therm/Dry Contact	N/A	IN-3					
IN-4	Gnd	Therm/Dry Contact	N/A	IN-4					
IN-5	Gnd	Therm/Dry Contact	N/A	IN-5					
IN-6	Gnd	Therm/Dry Contact	N/A	IN-6					
IN-7		Unused							
IN-8		Unused							
Point/ Cable#	Outputs (+)	COM	B-Output Type	Jumper Position of Pins	I/O	Sensor code	Equipment Name	Point Name	
	AO-1	Gnd	N/A	N/A	AO-1				
	AO-2	Gnd	N/A	N/A	AO-2				
	AO-3	Gnd	N/A	N/A	AO-3				
	BO-1	Pwr	N.O.	N/A	BO-1				
	BO-2	Pwr	N.O.	N/A	BO-2				
	BO-3	Pwr	N.O.	N/A	BO-3				
	BO-4	Pwr	N.O.	N/A	BO-4				
	BO-5	Pwr	N.O.	N/A	BO-5				


Appendix B: Device Address Binding

Device Address Binding (DAB) allows the controller to receive data from other Open controllers when they are connected by a network. The controller receives data from other Open or BACnet controllers when they are installed as part of an i-Vu® Control System. The data transfer takes the form of DAB, which you must configure.


Currently, the controller implements DAB for the following variables:

- **System Outdoor Air Temperature**
- **System Occupancy**
- **System Water Differential Pressure**
- **Network Flow Input**
- **Pump 1 Network Status**
- **Pump 2 Network Status**

You can implement DAB on network points with an undefined BACnet address, displayed in Field Assistant and the i-Vu® interface on the **Properties** page > **Network Points** tab. See example below.



Name	Type	Value	Locked	Default Value	Com Enabled	COV Enable	Refresh Time (mm:ss)	Address	Search / Replace	Error
System Outdoor Air Temperature	(ANI2)	-999.00	<input type="checkbox"/>	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	10:00	bacnet://	0 No Error	
(Primary)								bacnet://	0 No Error	
(Secondary)										



Name	Type	Value	Locked	Default Value	Com Enabled	COV Enable	Refresh Time (mm:ss)	Address	Search / Replace	Error
System Outdoor Air Temperature	(ANI2)	88.80	<input type="checkbox"/>	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	10:00	bacnet://1610151/AV:80001	0 No Error, bound to DEV:1610151, AV:80001	
(Primary)								bacnet://1610151/AV:80001	0 No Error, bound to DEV:1610151, AV:80001	
(Secondary)										

Appendix C: GSLC Points/Properties

The following tables describe all of the possible settings for your controller on the i-Vu® or Field Assistant **Properties** tab.

NOTE Some of the properties are available only when other settings have been enabled. For example, **Service Configuration > Pump 2 Network Status** is visible only when **Service Configuration > Number of Pumps** is set to **Two** and **Service Configuration > Pump Status Type** is set to **Network (3)**.

See *Appendix D* (page 43) for the points and properties available on the Equipment Touch interface.

NOTE Engineering units shown in this document in the defaults and ranges are strictly for reference. You must enter an integer only.

Status

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Status**

Point Name/Description	Range
Run Status – The controller's status.	R: Off/On
Source Water Supply Temp – The water temperature entering the WSHP.	R: -56 to 245 °F
Source Water Return Temp – The water temperature returning from the WSHP.	R: -56 to 245 °F
Pump 1 Operation Status – Pump 1's status.	R: Off - OK to Run On as Lead Waiting in Standby On as Replacement Running as Lag Failed
Pump 1 VFD Speed – The current commanded speed of the VFD.	R: 0 to 100%
Pump 2 Operation Status – Pump 2's status.	R: Off - OK to Run On as Lead Waiting in Standby On as Replacement Running as Lag Failed
Pump 2 VFD Speed – The current commanded speed of the VFD.	R: 0 to 100%
Delta Pressure – The differential pressure between the supply and return pipes.	R: 0 to 100%
Bypass Valve Percent – The percent the bypass valve is open or closed.	R: 0 to 100%
Outdoor Air Temperature – The outdoor air temperature used for control.	R: -56 to 245 °F
Shutdown – When Active , provides a means to stop the operation of the control in an orderly manner. All alarms are reset and current active alarms are displayed.	R: Inactive/Active

Unit Configuration

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Configuration > Unit Configuration**

Point Name/Description	Range
On – Off – Auto – HOA switch Auto – The pumps cycle on and off based on demand or occupancy Off – Unit is locked off. On – Unit is locked on.	D: Auto R: Auto Off On
Pump Start – Enables or disables the pumps based on demand only or on occupancy-or-demand. This parameter is only applicable to systems using Carrier Condenser Water Linkage and when Linkage is active.	D: Demand Only R: Demand Only Occ or Demand
Minimum Heat Pump Demand – Number of requests required to start the pumps. This parameter is only applicable to systems using Carrier Condenser Water Linkage and when Linkage is active.	D: 0 R: 0 - 100
Power Fail Restart Delay – How long the controller delays normal operation after the power is restored. Typically used to prevent excessive demand when recovering from a power failure.	D: 5 seconds R: 0 to 600 seconds
Pump Stop Delay – The number of minutes the pump continues to run after the system goes unoccupied (w/ Condenser Water Linkage - and/or all heating or cooling demands have been satisfied).	D: 15 minutes R: 0 to 9999 minutes
Occupancy Schedules – If enabled, the unit runs as occupied 24/7 until either the occupancy schedule or another occupancy control is configured. Enables or disables the occupancy schedule function.	D: Enable R: Disable/Enable
Rotation Method	
Rotation Method Daily – Rotates the pumps daily at a specified time. Weekly – Rotates the pumps weekly on a specified day and time. Monthly – Rotates the pumps monthly on a specified day and time. Manual Rotation – Manually rotates the pumps when the operator commands it. Runtime – Rotates the pumps after the lead pump reaches a specified number of runtime hours. Never Rotate – Does not allow the pumps to rotate.	D: Daily R: Daily Weekly Monthly Manual Rotation Runtime Never Rotate

Point Name/Description				Range
Rotation Method Parameters - Specify further details of the selected method.				
Method	Enter...			
Daily	time of the day to rotate the lead pump NOTE Enter the time of day in Defined Time for Rotation . The time of day you specify is used during a weekly or monthly rotation.	D: R:	13:00 00:00 to 23:59	
Weekly	day of the week to rotate the lead pump performed at the time of day specified in Defined Time for Rotation	D: R:	3 (Wednesday) 1 to 7 (Monday to Sunday)	
Monthly	day of the month to rotate the lead pump performed at the time of day specified in Defined Time for Rotation	D: R:	1 1 to 31	
Manual Rotation	manually rotate the lead pump	D: R:	Do not Rotate Rotate Do Not Rotate	
Runtime	number of runtime hours before rotating the lead pump	D: R:	360 hrs 24 - 9999 hrs	
	Runtime since last rotation: - Pump 1 - Pump 2	R: R:	0 - 360 hrs 0 - 360 hrs	

Setpoints

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Configuration > Setpoints**

Point Name/Description		Range
Source Loop Diff Press. Setpoint - The differential pressure setpoint maintained by the bypass valve or the pump's VFD (Variable Frequency speed Drive).		D: 15 psi R: 0 to 9999 psi
Lag Pump	Enables lag pump if VFD is greater than this setpoint. Disables lag pump when VFD output falls below.	D: 90% R: 0 to 100% D: 25% R: 10 to 65%

Alarm Configuration

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Configuration > Alarm Configuration**

Point Name/Description	Range
Maximum Source Water Temp – The value that the source water temperature must exceed to generate a High Source Water Temp Alarm .	D: 90°F R: 0 to 999°F
Minimum Source Water Temp – The value that the source water temperature must drop below to generate a Low Source Water Temp Alarm .	D: 60°F R: 0 to 999°F
Differential Pressure Alarm Hysteresis – The value that the differential pressure must change from the alarm setpoint to release a High or Low Differential Pressure Alarm .	D: 5 psi R: 0 to 999 psi
Pump 1 Status Alarm(s) – Generates a Pump Fail Alarm if the feedback status of pump 1 has not turned on after it has been enabled. If the status is on, and the pump has not been enabled, it will enable the Pump In Hand Alarm .	D: 30 seconds R: 0 to 9999 seconds
Pump 1 Runtime Alarm – The value that the runtime must exceed to generate a Runtime Alarm.	D: 10000 hr R: 0 to 99999 hr
Pump 2 Status Alarm(s) – Generates a Pump Fail Alarm if the feedback status of pump 2 has not turned on after it has been enabled. If the status is on and the pump has not been enabled, it will enable the Pump In Hand Alarm .	D: 30 seconds R: 0 to 9999 seconds
Pump 2 Runtime Alarm – The value that the runtime must exceed to generate a Runtime Alarm.	D: 10000 hr R: 0 to 99999 hr
Main Loop Flow Status Alarm(s) – If the pumps have been enabled to run, and the flow does not turn on after the specified time, it will generate a No Water Flow & Shutdown Alarm .	D: 180 seconds R: 0 to 9999 seconds
Disabled Pumps should the loop lose main CW flow – Will disable all pumps if there is no flow. You must manually reset the system.	D: Yes R: No/Yes

Service Configuration

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Configuration > Service Configuration**

Point Name/Description	Range
Number Of Pumps – The number of pumps in the system.	D: One R: One Two
Pump Status Type – The type of status that the pumps deliver to the loop controller to indicate they are on.	D: Switch R: Switch Amperage Network None
Pump Control – This is the type of pump being controlled. Constant Volume – Turns the pump on and leaves it on until scheduled to turn off or the demand has been satisfied. Constant Vol w/Bypass – Turns the pump on and then maintains a differential pressure with the bypass valve. Vfd – Turns the pump on and maintains a differential pressure by modulating the speed of the Vfd.	D: Constant Volume R: Constant Volume Constant Volume w/Bypass Vfd
Pump Staging – If there are 2 pumps, this type of staging enables or disables the pumps, based on Demand Only or Occ or Demand (set in Unit Configuration). Lead/Standby - One pump runs as the lead pump and the other pump waits in standby. Lead/Lag – One pump runs as the lead pump and, if the pressure is not maintained, brings the second pump on as the lag pump. (Only available if Pump Control is set to Two VFDs)	D: Lead/Standby R: Lead/Standby Lead/Lag
Remote Contact Unocc Logic State – Sets the remote contact's normal logic state.	D: Open R: Open/Closed
Flow Type – Sets the flow input's normal logic state.	D: Normal R: Normal Inverted
Pressure Sensor Min Input Volts – The lowest voltage that should be read from the pressure sensor.	D: 0.00 V R: 0 to 5.00 V
Pressure Sensor Max Input Volts – The highest voltage that should be read from the pressure sensor.	D: 5.00 V R: 0 to 5.00 V
Pressure Sensor Value @ Min Volts – The psi value that correlates to the pressure sensor's low voltage.	D: 0.00 psi R: 0 to 9999.00 psi
Pressure Sensor Value @ Max Volts – The psi value that correlates to the pressure sensor's high voltage.	D: 30.00 psi R: 0 to 9999.00 psi
Pump 1 Trip Point – Determines when Pump 1 is on. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 3.00 A R: 0 to 9999.00 A

Point Name/Description	Range
Pump 1 Sensor Min Input Volts – The lowest voltage that should be read from the pump feedback. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 0.00 V R: 0 to 5.00 V
Pump 1 Sensor Max Input Volts – The highest voltage that should be read from the pump feedback. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 5.00 V R: 0 to 5.00 V
Pump 1 Sensor Value @ Min Volts – The amps value that correlates to the pump feedback's low voltage. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 0.00 A R: 0 to 9999.00 A
Pump 1 Sensor Value @ Max Volts – The amps value that correlates to the pump feedback's high voltage. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 60.00 A R: 0 to 9999.00 A
Pump 2 Trip Point – Determines when Pump 2 is on. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 3.00 A R: 0 to 9999.00 A
Pump 2 Sensor Min Input Volts – The lowest voltage that should be read from the pump feedback. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 0.00 V R: 0 to 5.00 V
Pump 2 Sensor Max Input Volts – The highest voltage that should be read from the pump feedback. Configuration > Service Configuration > Pump Status Type must be set to Amps .	D: 5.00 V R: 0 to 5.00 V
Pump 2 Sensor Value @ Min Volts – The amps value that correlates to the pump feedback's low voltage.	D: 0.00 A R: 0 to 9999.00 A
Pump 2 Sensor Value @ Max Volts – The amps value that correlates to the pump feedback's high voltage.	D: 60.00 A R: 0 to 9999.00 A
Pump 1 VFD Output – Used to determine VFD output signal range.	D: 0-10 Vdc R: 0-10 Vdc 2-10 Vdc
Pump 2 VFD Output – Used to determine VFD output signal range.	D: 0-10 Vdc R: 0-10 Vdc 2-10 Vdc
Bypass Output – Used to determine Bypass output signal range.	D: 0-10 Vdc R: 0-10 Vdc 2-10 Vdc
System Outdoor Air Temperature – Allows the controller to use an outdoor air temperature value from the network. The remote controller must have a network-accessible outdoor air temperature sensor value.	D: -999.00 °F R: N/A
Source Water Diff. Pressure – Allows using another controller's differential pressure sensor from the network. The remote controller must have a network-accessible differential pressure sensor value.	D: -999.00 psi R: N/A

Point Name/Description	Range
System Occupancy – Allows reading and using another controller's occupancy status value over the network. The remote controller must have a network-accessible Occupancy Status point.	D: Unoccupied R: Unoccupied/Occupied
Network Flow Input – Allows using another controller's flow sensor value over the network. The remote controller must have a network-accessible flow sensor value.	D: No Flow R: No Flow/Flow
Pump 1 Network Status – Allows using another controller's Pump 1 status value over the network. The remote controller must have the point network-accessible.	D: Off R: Off/On
Pump 2 Network Status – Allows using another controller's Pump 2 status value over the network. The remote controller must have the point network-accessible.	D: Off R: Off/On
Pump 1 Network S/S – Provides the ability to transfer the desired state of Pump 1 to an external controller or the pump directly. The remote point to receive this state must have network-accessibility.	D: Off R: Off/On
Pump 2 Network S/S – Provides the ability to transfer the desired state of Pump 2 to an external controller or the pump directly. The remote point to receive this state must have network-accessibility.	D: Off R: Off/On
Pump 1 VFD Network Output – Provides the ability to transfer the desired speed of the Pump 1 VFD to an external controller or the VFD directly. The remote point to receive this state must have network-accessibility.	D: 0% R: 0 to 100%
Pump 2 VFD Network Output – Provides the ability to transfer the desired speed of the Pump 2 VFD to an external controller or the VFD directly. The remote point to receive this state must have network-accessibility.	D: 0% R: 0 to 100%
Byp Vlv Network Output – Provides the ability to transfer the desired position of the bypass valve to an external controller or the valve directly. The remote point to receive this state must have network-accessibility.	D: 0% R: 0 to 100%

Point Name/Description	Range
Lockout	
Lockout – If disabled, allows pumps to continue to cycle until either pump status is attained. If enabled it will lockout out the pumps after they have failed 3 (default value) consecutive times	D: Disabled R: Enabled/Disabled
Manually release lockout? – If the pump lockout is enabled and the pumps are locked out, you can manually release the lockout.	D: Off R: Off/On
Loop Bypass PID – This Bacnet Object determines what the bypass valve target setpoint should be. Configuration > Service Configuration > Pump Control must be set to Constant Volume w/Bypass . NOTE The default values should be changed only by a technician trained in PID Loop algorithms	R: direct 1.00 10 2 0 0 30
Action Update Interval Proportional Integral Derivative Deadband Bias	
Bypass Valve Type – Defines the normal position of the Bypass valve with no signal. Configuration > Service Configuration > Pump Control must be set to Constant Volume w/Bypass .	D: Normally Closed R: Normally Closed Normally Open
VFD PID – This Bacnet Object determines what the variable frequency drive target setpoint should be. Configuration > Service Configuration > Pump Control must be set to Constant Volume w/Bypass . NOTE The default values should be changed only by a technician trained in PID Loop algorithms	R: direct 1.00 10 5 0 0 30
Action Update Interval Proportional Integral Derivative Deadband Bias	
Minimum VFD Output – The minimum output signal the control supplies to the VFD as a percentage of its range. The balancer can set this to adjust the unit's minimum flow.	D: 20% R: 0 to 50%

Maintenance

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Maintenance**

Point Name/Description	Default/Range
Unit	
Pump 1 Status – Pump 1's status.	R: On/Off
Pump 2 Status – Pump 2's status.	R: On/Off
Pump 1 Amps – The amps from pump 1 entering the loop controller.	R: 0 to 60.0 A
Pump 2 Amps – The amps from pump 2 entering the loop controller.	R: 0 to 60.0 A
Loop Status / Cmpr Operation – Displays if the loop conditions are conducive for the WSHP units to run their compressors.	R: Not OK to run WSHP compressors / OK to run WSHP compressors
Outdoor Air Temperature	
Outdoor Air Temperature Source – The source of the OAT value. States: N/A – No sensor value associated with this device Local – A physical sensor is wired and connected to the appropriate input channel of this controller Network – A network sensor value provided to this controller Linkage – The sensor value from an active Linkage connection, such as Airside Linkage. Locked Value – The controller's sensor input is manually locked to a specific value	R: N/A Local Network Linkage Locked Value
System Outdoor Air Temperature – Allows another controller or third party BAS to write the value of the OAT to this controller. Requires that the controller is equipped with an outdoor air temperature sensor. This point is written to by the BACnet network every 10 to 15 minutes.	D: -999.00 °F R: N/A
Outdoor Air Temperature – The outdoor air temperature used for control.	R: -56 to 245 °F
Occupancy	
Remote Contact Input – The current status of Input Channel #4 .	R: Open/Closed
BAS On/Off – Determines the controller's occupancy state and can be set over the network by another device or third party BAS. Options: Inactive – Occupancy is determined by a configured schedule Occupied – The controller is always in the occupied mode Unoccupied – The controller is always in the unoccupied mode	D: Inactive R: Inactive Occupied Unoccupied
System Occupancy – The status of the System Occupancy network BNI2 point.	D: Unoccupied R: Inactive Unoccupied Occupied
Occupancy Contact – The current status of Input Channel #4 when configured as a Remote Contact Input .	R: Inactive Active Occupied
Schedules – The current state of the controller's local occupancy schedule.	R: Unoccupied/Occupied

Alarms

Navigation:

i-Vu® / Field Assistant:

Properties > Control Program > Alarms

Point Name/Description	Default/Range
Pump 1 In Hand – Pump 1's status on, but the commanded state is off.	R: Normal/Hand
Pump 1 Fall – Pump 1's commanded state is on, but the status is off and has exceeded the feedback delay timer.	R: Normal/Hand
Pump 1 Runtime – Pump 1's runtime has been exceeded.	R: Accumulating Exceeds Limit
Pump 2 In Hand – Pump 2's status is on, but the commanded state is off.	R: Normal/Hand
Pump 2 Fall – Pump 2's commanded state is on, but the status is off and has exceeded the feedback delay timer.	R: Normal/Alarm
Pump 2 Runtime – Pump 2's runtime has been exceeded.	R: Accumulating Exceeds Limit
Pump 1 and 2 Failed – Pump 1 and 2 have been locked out by exceeding the attempts to start the pumps. You must manually reset them.	R: Normal/Alarm
High Source Water Temperature – Source water temperature has exceeded the high limit.	R: Normal/Alarm
Low Source Water Temperature – Source water temperature has dropped below the low limit.	R: Normal/Alarm
No Water Flow – Indicates there is no water flow detected in the system.	R: Normal/Alarm
High Differential Pressure – Differential pressure has exceeded the high limit.	R: Normal/Alarm
Low Differential Pressure – Differential pressure has dropped below the low limit.	R: Normal/Alarm
Outdoor Air Temperature – Indicates the controller is no longer receiving a valid network outdoor air temperature value.	R: Normal/Alarm
Condenser Water Linkage – Indicates if Condenser Waterside Linkage has failed.	R: Normal/Alarm

Linkage

Navigation: i-Vu® / Field Assistant: **Properties > Control Program > Linkage**

Point Name/Description	Range
Linkage	
Linkage Equip – (Collector) Shows the linkage information that is being sent from the WSHP to the Loop Controller.	N/A
Condenser Water Linkage – If Active , the controller is part of a linked system. If Not Active , the controller is a stand-alone device.	R: Active/Not Active
Min Allowable Loop Temperature – The minimum loop temperature that the WSHP is sending to the Loop Controller.	R: 0 to 999 °F
Max Allowable Loop Temperature – The maximum loop temperature that the WSHP is sending to the Loop Controller.	R: 0 to 999 °F
Water Loop Temp – The source water supply temperature of the loop.	R: °F
Loop Pump Status – The actual state of the source water loop pump(s).	R: Off/On
Heat Pumps In Cool Mode – The number of WSHP's that are currently calling for cooling operation.	R: 0 to 999
Heat Pumps In Heat Mode – The number of WSHP's that are currently calling for heating operation.	R: 0 to 999

I/O Points

The values shown on the **I/O Points Properties** page are the raw values at the I/O objects and may not match values shown on status displays that are affected by control program logic.

i-Vu® users logged in as **Power User** and above are able to edit various parameters associated with the input channels and the display names for all channels.

We strongly recommend that you leave these parameters at their defaults. I/O can only be used for the purpose designed in the equipment control program. Modifying these parameters may result in unpredictable equipment control.

NOTES

- Depending on the configuration of the GSLC application, the available I/O points change. For variable flow applications such as the bypass valve control or VFD pump control, the **Source Water Diff. Pressure** AI input on Channel #2 is valid and available only if the **Pump Status Type** (in *Service Configuration* (page 35)) is set to **None** or **Network**. Otherwise, you must use a network input to obtain the source water differential pressure value.
- See *Inputs and outputs table* (page 8) for more information. This table lists each of the I/O channels, their functions, associated hardware, and terminal numbers.

⚠️ WARNINGS

- Do not change the **Value**, **Offset/Polarity**, **Exp:Num**, **I/O Type**, **Sensor/Actuator Type**, **Min/Max**, or **Resolution** I/O configuration parameter for the points listed below. Changing these parameters could cause improper control and/or equipment damage.
- Use extreme caution if locking a point as this may also cause improper control and/or equipment damage.



Point Name/Description	
Pump 1 Amp Sensor – The current voltage of the controller's pump 1 amp input.	R: 0 to 5 Volt
Pump 2 Amp Sensor – The current voltage of the controller's pump 1 amp input.	R: 0 to 5 Volt
Source Water Diff. Pressure – The current reading of the controller's differential pressure input.	R: 0 to 5 Volt
Source Return Water Temp – The temperature of the return water loop.	R: -56 to 245°F
Source Supply Water Temp – The temperature of the supply water loop used for control.	R: -56 to 245°F
Pump 1 Status – The current state of pump 1's status input.	R: Off/On
Pump 2 Status – The current state of pump 2's status input.	R: Off/On
Source Water Flow – The current state of the flow input.	R: No Flow/Flow
Remote Contact Input – The current state of the input connected to the remote contact input.	R: Off/On
Pump 1 VFD Ouput – The current commanded output to the pump 1 VFD.	R: 0 to 100%
Byp Vlv Output – The current commanded output to the Bypass Valve.	R: 0 to 100%
Pump 2 VFD Ouput – The current commanded output to the pump 2 VFD.	R: 0 to 100%
Pump1 S/S – The current commanded output to start or stop pump 1.	R: Off/On
Pump2 S/S – The current commanded output to start or stop pump 2.	R: Off/On
WSHP Comp Command – The WSHP Compressor Command is set to On (enabled output) if the loop controller is running, has flow, and the loop temperature is suitable for compressor operation.	R: Off/On
Alarm – If an alarm is present in the loop controller, the alarm output is turned on.	R: Off/On

Appendix D: GSLC Points/Properties on the Equipment Touch

NOTE Engineering units shown in this document in the defaults and ranges are strictly for reference. You must enter an integer only.


Navigation screens

Screen Names	Display	Details
Standby	 <p>Not an interactive screen. Touch anywhere to advance to Home screen.</p>	<p>Screen displays after the Inactivity Timer expires (default is 5 minutes).</p> <p>Displays:</p> <ul style="list-style-type: none"> • Source water supply temperature • Status - On/Off • Occupancy
Home	 <p>Click  on the right to navigate to Snapshot screen.</p>	<p>Displays:</p> <ul style="list-style-type: none"> • Source water supply temperature • Status - On/Off • Occupancy <p>Allows:</p> <ul style="list-style-type: none"> • Pushbutton Override

Screen Names	Display	Details
Snapshot		<p>Navigates to:</p> <ul style="list-style-type: none"> • Alarm status  • Schedules  • Trends  • Back to the Home screen - click ... on the left
Ground Source Loop Properties Menu		<p>Navigates to Property pages</p> <p>Login with one of the following passwords:</p> <ul style="list-style-type: none"> ○ User level - type user ○ Admin level - type admin ○ Factory level - type Touch <p>NOTE Only the buttons that are authorized for a specific password level are visible.</p>

Startup Wizard

You can easily configure the GSLC using the **Start-up Wizard**, which gives you access to the Properties without having to change views between several different screens.



Pump 1 Sensor Amps @ Min (V)	00.0 A	
Pump 1 Sensor Amps @ Max (V)	00.0 A	
<hr/>		
Pump 2 Trip Point	00.0 A	
Pump 2 Sensor Min Input (V)	00.0 V	
<hr/>		
Pump 2 Sensor Max Input (V)	00.0 V	
Pump 2 Sensor Amps @ Min (V)	00.0 A	
Pump 2 Sensor Amps @ Max (V)	00.0 A	
<hr/>		
Pump 1 VFD	0-10 vdc	
Pump 1 VFD Output	0-10 vdc	
Pump 2 VFD Output	0-10 vdc	
<hr/>		
Lockout	Disabled ▾	
Lockout After X Tries	00	
<hr/>		
Manually Release Lockout?	Off ▾	
<hr/>		
Bypass Output	0-10 vdc	
Bypass Valve Operation	Normally Closed	
Minimum VFD Output	00.0 %	

Document revision history

Important changes to this document are listed below. Minor changes such as typographical or formatting errors are not listed.

Date	Topic	Change description	Code*
9/21/21	Wiring devices to the controller's Rnet port	Removed hybrid wiring configuration for Rnet port	X-TS-AK-E
8/18/20	Cover, What is the GSLC application	Updated company logo	C-D
1/24/19	Wiring devices to the controller's Rnet port	Removed star configuration from the first paragraph.	X-TS-TS-O
	Specifications	Added surge CAUTION to Protection specification.	X-TS-AK-E-CC
10/26/18	Wiring inputs and outputs > Input wiring specifications	Added TruVu™ ET Display and referred user to Wiring the Rnet port section.	C-D
	Wiring devices to the controller's Rnet port	Added TruVu™ ET Display.	C-D
	Specifications	Added TruVu™ ET Display. Reworked Protection specification and added first paragraph.	X-H-JS-O
12/14/17	Analog Outputs	Corrected impedance from 500 Ohms to 2000 Ohms	C-AE-ZL-E-WB

* For internal use only



CARRIER CORPORATION ©2021 · Catalog No. 11-808-576-01 · 9/21/2021