

ProxyConfig v8.5 add-on User Guide

for v8.5, v9.0, and v10.0





Verify that you have the most current version of this document from www.hvacpartners.com, the **Carrier Partner Community** website, or your local Carrier office.

Important changes are listed in **Document revision history** at the end of this document.

Carrier© 2025. All rights reserved.

The content of this guide is furnished for informational use only and is subject to change without notice. Carrier assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.



Contents

What Is the ProxyConfig add-on?	1
Installing and setting up the ProxyConfig add-on	2
Installing the ProxyConfig add-on	2
Using the ProxyConfig add-on	2
Document revision history	3

What is the ProxyConfig add-on?

The i-Vu® v6.5 or 7.0 application or some of its add-ons require information from the Internet and your company has a proxy set up, you must configure the proxy settings for i-Vu® that allow access to the Internet. The ProxyConfig add-on lets you define these settings.

Proxy Settings

Automatically determine proxy settings

Use a proxy

Proxy requires authentication

Test URL: Testing ...

Save Configuration and Test

Installing and setting up the ProxyConfig add-on

If your company's internet access has a proxy set up, you must configure the proxy settings to allow some add-ons to access someone else's data. You define these settings in the ProxyConfig add-on.

Installing the ProxyConfig add-on

See the *Installing an add-on* user guide on the Automated Logic® Partner Community website for instructions on installing the add-on

Using the ProxyConfig add-on

- 1 If you did not connect to the add-on through the **Main Page** link in the Weather add-on interface on the **Add-on** tab, you can use the following method to access the setup page:
Go to `http://<system IP address>/proxyconfig`.
NOTE /proxyconfig is case sensitive.
- 2 When you installed ProxyConfig, it automatically tried to determine the proxy settings.
- 3 If it found the settings, the **Host** and **Port** information is filled in for you. If it could not find the proxy settings or, if you are using the i-Vu® Plus application, you need to enter them as follows:
 - a) Uncheck **Automatically determine proxy settings**.
 - b) Check **Use a proxy**.
 - c) Enter the **Host** and **Port** information. You can obtain these from your network administrator.
- 4 Check **Proxy requires authentication** if the proxy requires it, and then enter the **Username** and **Password**. You can obtain these from the network administrator.
- 5 Click **Save Configuration and Test**.

NOTE The **Test URL:**`http://` field has an external website address. If the proxy settings are correct, you will see the green text shown below.

Test URL: `http:// www.google.com` Test through proxy WORKED

Save Configuration and Test

- 6 Close the **Setup** page.

Document revision history

Important changes to this document are listed below. Minor changes such as typographical or formatting errors are not listed.

Date	Topic	Change description	Code*
11/13/25	Requirements	Updated supported versions	A-D
	Installing the ProxyConfig add-on	Updated location of information	
12/14/20	Requirements	Updated supported versions	A-D
3/16/20	Cover	New Carrier® Logo	A-D

* For internal use only



Carrier ©2025 · Catalog No. 11-808-589-01 · 11/13/2025