

VRF Outdoor Unit 38VMA072RDS6-1 - Heat Recovery



Submittal Data

Job Data _____ Location _____
 Buyer _____ Buyer PO # _____ Carrier # _____
 Unit Number _____ Model Number _____
 Performance Data Certified By _____ Date _____



Heat Recovery Features

- Modules available from 6 to 28 tons
- Modules have inverter-driven scroll compressors
- Direct-drive, inverter-driven outdoor motor
- Up to 3280 ft (1000 m) actual total system piping (liquid line)
- 656 ft (200 m) actual piping length from outdoor unit to furthest fan coil
- Up to 3937 ft (1200 m) control wiring between the outdoor units and indoor units
- Operating temperature range
Cooling (db): 5° to 125°F
Heating (wb): -13° to 64°F
(-25° to 18°C)

Header Unit Model		38VMA072RDS6-1
PERFORMANCE		
Nominal Cooling Capacity	Btu/h	72,000
Nominal Heating Capacity	Btu/h	80,000
Maximum Total Connected Indoor Unit Capacity		50% to 150%
SIMULTANEOUS COOLING AND HEATING EFFICIENCY†		
SCHE, Ducted FCUs		27.40
SCHE, Ductless FCUs		30.00
COOLING EFFICIENCY†		
EER/IEER, Ducted FCUs	Btu/Wh	13.20/24.20
Power Consumption, Ducted FCUs	kW	5.00
EER/IEER, Ductless FCUs	Btu/Wh	14.10/24.60
Power Consumption, Ductless FCUs	kW	4.20
HEATING EFFICIENCY†		
COP at 47°F, Ducted FCUs		3.85
Power Consumption, Ducted FCUs	kW	5.70
COP at 47°F, Ductless FCUs		4.37
Power Consumption, Ductless FCUs	kW	4.40
Fan Type (Qty)		Propeller (2)
Airflow, Standard Range	CFM	6900
Sound Pressure	dBA	58.4
External Static Pressure*	in. wg	0.24

LEGEND

db	— Dry Bulb
COP	— Coefficient of Performance
EER	— Energy Efficiency Ratio
FCU	— Fan Coil Unit
IEER	— Integrated Energy Efficiency Ratio
wb	— Wet Bulb
SCHE	— Simultaneous Cooling and Heating Efficiency

ELECTRICAL		
Power Supply	V/Ph/Hz	460/3/60
Minimum Circuit Amps (MCA)	A	20
COMPRESSORS		
Type (Number)		Inverter Hermetic Scroll (1)
FAN MOTOR		
Motor Type (Steps)	Inverter Direct Driven (13)	
Motor Output	kW	2 x 0.18
PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	5/8 (Brazed)
Pipe Connection Size - Gas (Low Pressure)	in.	3/4 (Brazed)
Refrigerant	R-410A	
Factory Charge††	lb	26.5
Unit Width	in.	52-3/4
Unit Height	in.	64-3/8
Unit Depth	in.	31-1/8
Net Weight	lb	672

†Rated per AHRI (Air-Conditioning, Heating and Refrigeration Institute) 1230 Standard.


Cooling: Indoor 80°F (27°C) db/67°F (20°C) wb; Outdoor 95°F (35°C) db
Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db/43°F (6°C) wb

*Requires setting by menu functions.

††Additional charge required.

NOTE: Unit cabinet and coil slab shall be capable of withstanding 500-hour salt spray test.

**DIMENSIONAL DRAWING
OUTDOOR UNIT 38VMA072RDS6-1**



© Carrier Corporation 2018

