

VRF Indoor Unit 40VML015---3—Low Static Duct



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Rear Return Air Opening is Standard and Bottom Return is Optional
- Three Fan Speeds - High, Medium, and Low
- Knockout for Outside Air
- Built-in Drain Pump from Factory
- Built in EXV (Electronic Expansion Valve) for Installation Ease


INDOOR UNIT MODEL		40VML015---3
PERFORMANCE		
Cooling Rated Capacity	Btu/h	15,210
Sensible Cooling Capacity	Btu/h	9,800
Heating Rated Capacity	Btu/h	17,000
Airflow (H / M / L)	CFM	459 / 367 / 306
Sound Pressure (H / M / L)	dBA	36.7 / 35.2 / 33.2
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	W	43
Minimum Circuit Amps (MCA)	A	0.8
Maximum Overcurrent Protection	A	15.0
Motor Type		DC

PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	1/4 (OD)
Pipe Connection Size - Suction	in.	1/2 (OD)
Pipe Connection Size - Drain	in.	1 (OD)
Minimum External Static Pressure (ESP) (Factory Default)	in. wg	0.0
Maximum External Static Pressure (ESP)	in. wg	0.2
Refrigerant		R-410A
Unit Width	in.	39-3/4
Unit Height	in.	8-1/4
Unit Depth	in.	19-3/4
Net Unit Weight	lb	48.5


ACCESSORIES

- Wireless Remote Controller 40VM900001
- Wired Remote Controller - Non-Prog. 40VM900002
- Wired Remote Controller - Prog. 40VM900003
- Touch Screen Wired Controller 40VM900005
- Touch Screen Central Controller 40VM900006


DIMENSIONAL DRAWING INDOOR UNIT LOW STATIC DUCT 40VML015---3




REAR VIEW




FRONT VIEW



SIDE VIEW



BOTTOM VIEW



TOP VIEW

Note: All dimensions are shown in inches

40VML UNIT SIZE	DIMENSION (in.)													
	A	B	C	D	E	F	G	H	J	K	L	N	P	
015	36 1/4	8 1/4	19 3/4	17 3/4	39 1/4	1 3/4	28 7/8	5/8	5 3/4	32 1/4	7 7/8	37 3/4	13 3/4	

