

## Submittal Data

Job Name \_\_\_\_\_ Location \_\_\_\_\_  
Tag \_\_\_\_\_



### STANDARD FEATURES

- Dual Drainage Spouts
- Three Fan Speeds - High, Medium and Low
- Unit Can Be Installed Standing Vertical or Laid Horizontally
- Electronically Commutated Fan Motor (ECM)
- Built In Pulse Modulating Valve For Installation Ease
- Removable Front Panel Provides Easy Access
- Filter MERV 3

INDOOR UNIT MODEL	MMD-AP0180VHG2UL	
<b>PERFORMANCE</b>		
Cooling Rated Capacity	Btu/h	18,000
Heating Rated Capacity	Btu/h	20,000
Airflow (H / M / L)	CFM	670 / 640 / 600
Sound Data (H / M / L) †	dBA	41.4 / 38.4 / 37.5
External Static Pressure (ESP)	in. WG	0.3 (Factory Default)
		0.5 (Max.)
<b>ELECTRICAL</b>		
Power Supply	V/Ph/Hz	208-230/1/60
MCA*	A	2.8
MOCP*	A	15
Full Load Amps (FLA)	A	2.2

PHYSICAL DATA		
Pipe Connection Size - Liquid	inches	3/8 (brazed)
Pipe Connection Size - Suction	inches	1/2 (brazed)
Pipe Connection Size - Drain	inches	3/4 (FTP)
Refrigerant		R410A
DIMENSIONS (inches)	H (in)	46-7/8
	W (in)	17-3/4
	D (in)	22-1/4
NET WEIGHT	lbs	164

### ACCESSORIES (Optional)

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Stand Alone Receiver with Wireless Remote TCB-AX32UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL
- Filter Box / 2" MERV8 (TCB-FB2F241VDGUL)
- Plenum TCB-PL2S241VDGUL
- Electrical Heater (240V/208V):

1.0kW/0.8kW	TCB-HT101VDGUL
3.0kW/2.3kW	TCB-HT301VDGUL
5.0kW/3.8kW	TCB-HT501VDGUL
6.0kW/4.5kW	TCB-HT601VDGUL

### NOTES:

\* Does not include electric heater.

† Average / weighted sound values.

**Dimensional Drawing**  
**Indoor Unit Vertical Air Handler MMD-AP0180VHG2UL**

