

SMMSe / SHRMe VRF Indoor Unit MMK-AP0183H2UL—HIGH WALL

TOSHIBA
Carrier

Submittal Data

Job Data _____ Location _____
Buyer _____ Buyer PO # _____ Carrier # _____
Unit Number _____ Model Number _____
Performance Data Certified By _____ Date _____



SMMSe / SHRMe VRF High Wall Features

- R-410A refrigerant
- Six sizes from 7,000 to 24,000 Btu/h
- Quiet operation, as low as 30 dBA
- Vertical airflow can be set to swing or fixed position
- Air throw up to 23 feet
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMK-AP0183H2UL
PERFORMANCE		
Cooling Rated Capacity	Btu/h	18,000
Heating Rated Capacity	Btu/h	20,000
Fan Type (Qty)	Cross-Flow (1)	
Airflow (L / M / H)	CFM	320 / 390 / 490
Sound Pressure (L / M / H)	dBA	34.5 / 38 / 43
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.043
Full Load Amps (FLA)	A	0.4
Minimum Circuit Amps (MCA)	A	0.5
Maximum Overcurrent Protection	A	15
MOTOR		
Motor Type	DC Inverter Driven	
Motor Watts	W	30

PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	1/2 (Flare)
Pipe Connection Size - Drain (OD)	in.	7/8
Pipe Connection Size - Drain (ID)	in.	5/8
Refrigerant		R-410A
External Finish		Munsell 2.5GY9.0/0.5
Unit Width	in.	41-5/16
Unit Height	in.	12-9/16
Unit Depth	in.	9
Net Weight	lb	33
CONTROLS		
Wireless Remote Controller (Standard)		

ACCESSORIES

- ☐ Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- ☐ Simple Wired Remote Control - RBC-AS41UL
- ☐ Remote Sensor TCB-TC41LUL
- ☐ Wired Remote Controller - RBC-AMT32UL
- ☐ Condensate Drain Pump Kit 53DS-900---118

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

DIMENSIONAL DRAWING INDOOR UNIT HIGH WALL MMK-AP0183H2UL

