

VRF Outdoor Unit 38VMA096HDS5-1 - Heat Pump



Submittal Data

Job Data _____ Location _____
 Buyer _____ Buyer PO # _____ Carrier # _____
 Unit Number _____ Model Number _____
 Performance Data Certified By _____ Date _____



Heat Pump Features

- 6, 8, 10, and 12 ton modules available
- Modules have inverter-driven scroll compressors
- Direct-drive, inverter-driven outdoor motor
- Modules can be combined to form larger systems, up to 36 tons
- 3280 ft (1000 m) actual total system piping (liquid line)
- 656 ft (200 m) actual piping length from outdoor unit to furthest fan coil
- Up to 3937 ft (1200 m) control wiring between the outdoor units and indoor units
- Operating temperature range
 Cooling (db): 5° to 125°F
 (-15° to 52°C)
 Heating (wb): -5° to 64°F
 (-21° to 18°C)
- Protection: high pressure sensor and switch, low pressure sensor and switch, process controller board fuse, inverter overload protection
- 7-year compressor limited warranty
- 5-year parts limited warranty

Header Unit Model		38VMA096HDS5-1
PERFORMANCE		
Nominal Cooling Capacity	Btu/h	96,000
Nominal Heating Capacity	Btu/h	108,000
Maximum Total Connected Indoor Unit Capacity		50% to 135%
COOLING EFFICIENCY†		
EER/IEER, Ducted FCUs	Btu/Wh	11.80/23.00
Power Consumption, Ducted FCUs	kW	7.50
EER/IEER, Ductless FCUs	Btu/Wh	13.20/23.50
Power Consumption, Ductless FCUs	kW	6.20
HEATING EFFICIENCY†		
COP at 47°F, Ducted FCUs		3.63
Power Consumption, Ducted FCUs	kW	8.00
COP at 47°F, Ductless FCUs		3.82
Power Consumption, Ductless FCUs	kW	7.20
Fan Type (Qty)		Propeller (2)
Airflow, Standard Range	CFM	7650
Sound Pressure	dBA	63
External Static Pressure*	in. wg	0.08
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/3/60
Minimum Circuit Amps (MCA)	A	46
Recommended Fuse Size	A	50

COMPRESSORS

Type (Number)		Inverter Hermetic Scroll (1)
---------------	--	------------------------------

FAN MOTOR

Motor Type (Steps)	Inverter Direct Driven (13)
Motor Output	kW

PHYSICAL DATA

Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Brazed)
Pipe Connection Size - Gas (Low Pressure)	in.	7/8 (Brazed)
Balance	in.	1/4 (Brazed)
Refrigerant		R-410A
Factory Charge††	lb	37.5
Unit Width	in.	52-3/4
Unit Height	in.	64-3/8
Unit Depth	in.	31-1/8
Net Weight	lb	659

†Rated per AHRI (Air-Conditioning, Heating and Refrigeration Institute) 1230 Standard.

Cooling: Indoor 80°F (27°C) db/67°F (20°C) wb; Outdoor 95°F (35°C) db

Heating: Indoor 70°F (21°C) db; Outdoor 47°F (8°C) db/43°F (6°C) wb

*Requires setting by menu functions.

††Additional charge required.


NOTE: Unit cabinet and coil slab shall be capable of withstanding 500-hour salt spray test.

LEGEND

db	— Dry Bulb
COP	— Coefficient of Performance
EER	— Energy Efficiency Ratio
FCU	— Fan Coil Unit
IEER	— Integrated Energy Efficiency Ratio
wb	— Wet Bulb

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

**DIMENSIONAL DRAWING
OUTDOOR UNIT 38VMA096HDS5-1**



NOTE: All dimensions shown in inches.



© Carrier Corporation 2017

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.
Printed in U.S.A. Form 38VMH0965-C-1SD Pg 2 01-17 Replaces: New