



# LIGHT COMMERCIAL ROOFTOP UNITS

Contact Your Local Office for Stocking Details



Series	<b>Preferred™ Series</b> 581K / 551K / 549K	<b>Legacy™ Line</b> 582K / 559K / 547K
Sizes	3 to 25 Tons	3 to 27.5 Tons 3 to 25 Tons (Heat Pump)
Max Efficiency	SEER: 17.4 / SEER2: 16.5 EER: 12.8 / EER2: 12.0 / IEER: 17.5, COP: 3.8 / HSPF: 8.9	SEER: 14.0 / SEER2: 13.8 EER: 11.8 / EER2: 11.6 / IEER: 15.2 COP: 3.8 / HSPF: 8.2
Application	Staged Air Volume (SAV)	Constant Volume (CV) Staged Air Volume (SAV)
Cooling Stages	Two-Stage Cooling	One- and Two-Stage Cooling
Heat Type	Gas / Low NOx Electric / Cooling Only Heat Pump	Gas / Low NOx Electric / Cooling Only Heat Pump
Supply Fan and Motor Options	Direct Drive ECM / Vane Axial Fan With Axion™ Fan Technology	Direct Drive ECM / Vane Axial Fan With Axion™ Fan Technology
Coils, Coatings and Protection	Round Tube Plate Fin Coils (Al / Cu or Cu / Cu) Precoated Coils* E-Coated Coils* Louvered Hail Guard*	Round Tube Plate Fin Coils (Al / Cu or Cu / Cu) Precoated Coils* E-Coated Coils* Louvered Hail Guard*
Controls	Electromechanical	Electromechanical
Premium Options	Perfect Humidity™ Dehumidification System Stainless Steel Heat Exchanger	
Options	Convenience Outlet Smoke Detectors CO <sub>2</sub> Sensors Winter Start Kit	Low Ambient Operation Economizer with Fault Detection and Diagnostics (FDD) Non-Fused Disconnect
		Hinged Panels Power Exhaust Economizer Ultra Low Leak Economizer