

# VRF Indoor Unit 40VMA036---3—Outside Air Unit



## Submittal Data

Job Name \_\_\_\_\_ Location \_\_\_\_\_  
Tag \_\_\_\_\_



### STANDARD FEATURES

- Ducted Supply and Return Opening
- Three Fan Speeds - High, Medium, and Low
- Built in Drain Pump from Factory (27-1/2 inch lift)
- Built in EXV (Electronic Expansion Valve) for Install Ease

INDOOR UNIT MODEL		40VMA036---3
<b>PERFORMANCE</b>		
Cooling Rated Capacity	Btu/h	36,510
Sensible Cooling Capacity	Btu/h	22,430
Heating Rated Capacity	Btu/h	24,000
Airflow (H / M / L)	CFM	588 / 529 / 441
Sound Pressure (H / M / L)	dBA	49.5 / 47.8 / 43.8
<b>ELECTRICAL</b>		
Power Supply	V/Ph/Hz	208-230/1/60
Indoor Fan Motor Power Consumption (Input)	W	64
Minimum Circuit Amps (MCA)	A	5.7
Maximum Overcurrent Protection	A	15.0
Motor Type		DC


### PHYSICAL DATA

Pipe Connection Size - Liquid	in.	3/8 (OD)
Pipe Connection Size - Discharge Gas	in.	5/8 (OD)
Pipe Connection Size - Drain	in.	1 (OD)
Minimum External Static Pressure (ESP) (Factory Default)	in. wg	0.2
Maximum External Static Pressure (ESP)	in. wg	0.8
Refrigerant		R-410A
Unit Width	in.	51-3/16
Unit Height	in.	16-1/2
Unit Depth	in.	27-3/16
Net Unit Weight	lb	161.4


### ACCESSORIES

- Wireless Remote Controller 40VM900001
- Wired Remote Controller - Non-Prog. 40VM900002
- Wired Remote Controller - Prog. 40VM900003
- Touch Screen Wired Controller 40VM900005
- 24V Controller 40VM900008
- Button Sensor 40VM900009

**DIMENSIONAL DRAWING**  
**OUTSIDE AIR INDOOR UNIT 40VMA036---3**



## Recommended Service / Maintenance Clearances



## Recommended Mounting Instructions

