

VRF Indoor Unit 45VMC015A---3—Compact 4-Way Cassette



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Delivers air in all four directions
- Seven fan speeds
- Built-in condensate lift mechanism
- Condensate lift up to 47-1/4 inches
- Built in EEV (Electronic Expansion Valve) for installation ease
- Outside air connection
- Branch duct for supply (blank off required)
- Panel/grill (45VMC001----) - ordered separately


INDOOR UNIT MODEL		45VMC015A---3
PERFORMANCE		
Total Cooling Capacity	Btu/h	15,000
Total Heating Capacity	Btu/h	17,000
Airflow Rates (Highest to Lowest)	CFM	395/368/343/317/ 292/266/241
Sound Pressure Levels (Highest to Lowest)	dBA	36.5/35/33/31/29/28/ 26.5
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Indoor Fan Motor Rated Motor (Output)	W	45
Minimum Circuit Amps (MCA)	A	0.61
Maximum Overcurrent Protection	A	15.0
Motor Type		DC

PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	1/4
Pipe Connection Size - Suction	in.	1/2
Pipe Connection Size - Drain	in.	1
Refrigerant		R-454B
Unit Width	in.	25-1/8
Unit Height	in.	9-1/4
Unit Depth	in.	22-5/8
Unit Net Weight	lbs.	30.9
Panel Width	in.	24-7/16
Panel Height	in.	2-9/16
Panel Depth	in.	24-7/16
Panel Net Weight	lbs.	5

ACCESSORIES

- ☐ Wireless Remote Controller 45VM900001
- ☐ Wired Remote Controller - Non-Prog. 45VM900002
- ☐ Panel 45VMC001----

DIMENSIONAL DRAWING INDOOR UNIT COMPACT 4-WAY CASSETTE 45VMC015A---3



Capacity (kBtu/h)

A: Connect to refrigerant piping (liquid side)

B: Connect to refrigerant piping (gas side)

All sizes

$\Phi 1/4$ (6.35)

$\Phi 1/2$ (12.7)

