

## Submittal Data

Job Name \_\_\_\_\_ Location \_\_\_\_\_  
Tag \_\_\_\_\_



### STANDARD FEATURES

- R-410A Refrigerant
- Three sizes from 48,000 to 96,000 Btu/h
- Rear return
- 208/230 V PSC (Permanent Split Capacitor) motor
- Five-year parts limited warranty

INDOOR UNIT MODEL	MMD-AP0481HF2UL	
<b>PERFORMANCE</b>		
Cooling Rated Capacity	Btu/h	48,000
Heating Rated Capacity	Btu/h	30,000
Fan Type (Qty)		Centrifugal (1)
Standard Airflow	CFM	636
Sound Pressure (H / M / L)	208V (dBA)	44 / 43 / 36
	230V (dBA)	46 / 45 / 42
External Static Pressure (ESP) (208V)	in. WG	0.55 (Factory Default)
	in. WG	0.75 (Max.)
External Static Pressure (ESP) (230V)	in. WG	0.86 (Factory Default)
	in. WG	1.06 (Max.)
<b>ELECTRICAL</b>		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (208V / 230V)	kW	0.31 / 0.34
Full Load Amps (FLA)	A	1.84
Minimum Circuit Amps (MCA)	A	2.30
Maximum Overcurrent Protection	A	15.0

MOTOR		
Motor Type	PSC	
Motor Watts	W	160
<b>PHYSICAL DATA</b>		
Pipe Connection Size - Liquid	in.	3/8 (OD)
Pipe Connection Size - Suction	in.	5/8 (OD)
Pipe Connection Size - Drain	in.	1-1/4 (OD)
Refrigerant	R-410A	
Unit Width	in.	35-3/8
Unit Height	in.	19-1/2
Unit Depth	in.	49-3/4
Net Weight	lb	212

### ACCESSORIES

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Stand Alone Receiver with Wireless Remote TCB-AX32UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL

# DIMENSIONAL DRAWING

## OUTSIDE AIR INDOOR UNIT – MMD-AP0481HF2-UL

