

**SMMS-e / SHRM-e VRF Indoor Unit
MMD-AP0721HF2-UL—Outside Air Unit**

TOSHIBA
Carrier

Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- R-410A Refrigerant
- Three sizes from 48,000 to 96,000 Btu/h
- Rear return
- 208/230 V PSC (Permanent Split Capacitor) motor
- Five-year parts limited warranty

INDOOR UNIT MODEL	MMD-AP0721HF2UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	72,000
Heating Rated Capacity	Btu/h	47,000
Fan Type (Qty)	Centrifugal (2)	
Standard Airflow	CFM	989
Sound Pressure (H / M / L)	208V (dBA)	47 / 46 / 40
	230V (dBA)	48 / 47 / 46
External Static Pressure (ESP) (208V)	in. WG	0.74 (Factory Default)
	in. WG	0.84 (Max.)
External Static Pressure (ESP) (230V)	in. WG	1.00 (Factory Default)
	in. WG	1.08 (Max.)
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (208V / 230V)	kW	0.56 / 0.58
Full Load Amps (FLA)	A	3.43
Minimum Circuit Amps (MCA)	A	4.29
Maximum Overcurrent Protection	A	15.0

MOTOR		
Motor Type	PSC	
Motor Watts	W	160x2
PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	1/2 (OD)
Pipe Connection Size - Suction	in.	7/8 (OD)
Pipe Connection Size - Drain	in.	1-1/4 (OD)
Refrigerant	R-410A	
Unit Width	in.	55
Unit Height	in.	19-1/2
Unit Depth	in.	49-3/4
Net Weight	lb	349

ACCESSORIES

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Stand Alone Receiver with Wireless Remote TCB-AX32UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL

DIMENSIONAL DRAWING

OUTSIDE AIR UNIT – MMD-AP0721HF2-UL

