

# VRF Indoor Unit 40VMM030A--3—Medium Static Duct



## Submittal Data

Job Data \_\_\_\_\_ Location \_\_\_\_\_  
 Buyer \_\_\_\_\_ Buyer PO # \_\_\_\_\_ Carrier # \_\_\_\_\_  
 Unit Number \_\_\_\_\_ Model Number \_\_\_\_\_  
 Performance Data Certified By \_\_\_\_\_ Date \_\_\_\_\_



### STANDARD FEATURES

- Rear Return Air Opening is Standard and Bottom Return is Optional
- Three Fan Speeds - High, Medium, and Low
- Knockout for Outside Air
- Built-in Condensate Lift Mechanism
- Built in EXV (Electronic Expansion Valve) for Installation



INDOOR UNIT MODEL		40VMM030A--3	
<b>PERFORMANCE</b>			
Cooling Rated Capacity	Btu/h	30,000	
Heating Rated Capacity	Btu/h	34,000	
Airflow (H / M / L)	CFM	1070 / 900 / 780	
Sound Pressure (H / M / L)	dBA	46.7 / 42.3 / 39.4	
<b>ELECTRICAL</b>			
Power Supply	V/Ph/Hz	208-230/1/60	
Indoor Fan Motor Power Consumption (Input)	W	290	
Minimum Circuit Amps (MCA)	A	3.13	
Maximum Overcurrent Protection	A	15	
Motor Type		DC	

PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	3/8 (OD)
Pipe Connection Size - Suction	in.	5/8 (OD)
Pipe Connection Size - Drain	in.	3/4 NPT
Maximum External Static Pressure (ESP)	in. wg	0.6
Refrigerant		R-410A
Unit Width	in.	50-3/4
Unit Height	in.	11-7/8
Unit Depth	in.	34-1/8
Net Unit Weight	lb	124


### ACCESSORIES

- Wireless Remote Controller 40VM900001
- Wired Remote Controller - Non-Prog. 40VM900002
- Wired Remote Controller - Prog. 40VM900003
- Touch Screen Wired Controller 40VM900005
- Touch Screen Central Controller 40VM900006


**DIMENSIONAL DRAWING**  
**INDOOR UNIT MEDIUM STATIC DUCT 40VMM030A--3**



Front View




Rear View




Left Side View

Nameplate and other labels



Top View

Mounting Brackets (4)



Bottom View

Warning labels

Note: All dimensions are shown in inches

40VMM Unit Size	Dimensions (inches)												
	A	B	C	D	E	F	G	H	I	J	K	L	M
030	47 1/8	11 7/8	34 1/8	31 1/2	50 3/4	3 1/8	37 7/16	1 1/2	8	11 3/8	43	48 7/8	19 5/8

