

VRF Multiport Distribution Controller (MDC) 40VMD010M--3 — Main MDC (6 to 20 Ton, Small and Medium Cabinet)



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Allows the connection of multiple indoor units to the Heat Recovery VRF system
- MDC allows up to 10 zones
- Main MDCs have refrigerant ports that feed sub MDCs (if used)
- Heat Recovery VRF System can support one Main MDC and two sub MDCs, maximum
- Separate 208-230/1/60 power required
- MDC ports may be twinned to serve high-capacity units (sizes greater than 54 kBtu/h)
- MDC has individual “home run” communication port plugs for each indoor unit
- Liquid and gas pipe adapters are provided with MDCs to accommodate various indoor unit capacities
- High-pressure, low-pressure, and gas pipe adapters are provided with Sub MDCs to accommodate various MDC total capacities

MDC UNIT MODEL		40VMD010M--3
NUMBER OF PORTS		10
MAX CAPACITY PER INDOOR UNIT PORT	kBtu/h	54
AVAILABLE SUB MDC MODELS*		40VMD006S--3, 40VMD008S--3, 40VMD010S--3
ELECTRICAL		
Power Supply	V-Ph-Hz	208/230-1-60
Minimum Circuit Amps	A	1.05
Maximum Overcurrent Protection	A	15
Power Wiring		Sized per NEC and local codes based on nameplate electrical data
Signal Wiring		2-core shielded twisted pair cable 18 AWG
DESIGN PRESSURE, HIGH/LOW	psig	580/320
DRAINAGE WATER PIPE DIAMETER, OD	in.	1
PIPE SIZE - ODU TO MAIN MDC		
High Pressure (Mixed Phase)	in.	5/8 - 1-1/8
Low Pressure (Gas)	in.	3/4 - 1-3/8



PIPE SIZE - MAIN MDC TO SUB MDC		
High Pressure (Gas)	in.	5/8 - 7/8
Low Pressure (Gas)	in.	3/4 - 1-1/8
Liquid	in.	3/8 - 5/8
PIPE SIZE - MAIN MDC TO IDU		
Liquid	in.	1/4 - 3/8
Gas	in.	1/2 - 7/8
PHYSICAL DATA		
Refrigerant		R-410A
Unit Dimensions (W x H x D)	in.	37 x 12-7/8 x 22-5/8
Packing Dimensions (W x H x D)	in.	44-1/2 x 18 x 33-1/8
Net Weight	lb	143

LEGEND
AWG — American Wire Gauge
IDU — Indoor Unit
MDC — Multiport Distribution Controller
NEC — National Electrical Code
ODU — Outdoor Unit


* Number of sub MDC ports cannot exceed the number of main MDC ports.

DIMENSIONAL DRAWING

MAIN MDC 40VMD010M--3 (6 TO 20 TON, SMALL AND MEDIUM CABINET)






Detail of Z section



Detail of Y section

Detail of X section




NOTES:

1. An indoor unit must be connected to port #1 to avoid communication error.
2. Optional condensate connection is available on either side of the unit.
3. Refer to installation manual for piping sizes.
4. All dimensions shown in inches.

MODEL	MDC010
A	37 in.
B	33-7/8 in.

RECOMMENDED SERVICE CLEARANCES



RECOMMENDATION FOR GRAVITY DRAIN INSTALLATION

