

VRF Indoor Unit 45VMW015---3 — High Wall



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Dual Guided Air Design Provides Smoother and More Comfortable Air Flow
- Seven Fan Speeds
- Multi-Refrigerant Outlet Piping Methods - Left, Right or Rear
- Built in EXV (Electronic Expansion Valve) for Installation Ease
- Internally Installed A2L Refrigerant Leak Sensor

Indoor Unit Model		45VMW015---3
PERFORMANCE		
Total Cooling Capacity	Btu/h	15,000
Total Heating Capacity	Btu/h	17,000
Airflow (H / M / L)	CFM	426/396/365/ 335/ 304/274/ 243
Sound Pressure (H / M / L)	dBA	36.9/35.2/33.7/ 31.9/30.2/28.8/ 27.6
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Indoor Fan Motor Rated Motor (Output)	W	20
Minimum Circuit Amps	A	0.74
Maximum Overcurrent Protection	A	15
Motor Type		DC

PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	1/4
Pipe Connection Size - Suction	in.	1/2
Pipe Connection Size - Drain	in.	5/8
Refrigerant		R-454B
Unit Width	in.	37-3/8
Unit Height	in.	11-5/8
Unit Depth	in.	10-7/16
Unit Net Weight	lb	27.5

ACCESSORIES (Optional)

- ☐ Wireless Remote Controller 45VM900001
☐ Wired Remote Controller - Non-Prog. 45VM900002

DIMENSIONAL DRAWING

INDOOR UNIT HIGH WALL 45VMW015---3

