

**SMMSe / SHRMe VRF Indoor Unit
MMD-AP0364H2UL—HIGH STATIC DUCT**

TOSHIBA
Carrier

Submittal Data

Job Data _____ Location _____
 Buyer _____ Buyer PO # _____ Carrier # _____
 Unit Number _____ Model Number _____
 Performance Data Certified By _____ Date _____



SMMSe / SHRMe VRF High Static Ducted Features

- R-410A refrigerant
- Five sizes from 30,000 to 96,000 Btu/h
- Rear return
- 208/230 V PSC (Permanent Split Capacitor) motor
- Optional wired or wireless controls
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMD-AP0364H2UL	
PERFORMANCE			
Cooling Rated Capacity	Btu/h	36,000	
Heating Rated Capacity	Btu/h	40,000	
Fan Type (Qty)		Centrifugal (2)	
Airflow, Standard Range	CFM	755-1133	
Sound Pressure, 208V (L / M / H)	dBA	41 / 45 / 49.5	
Sound Pressure, 230V (L / M / H)	dBA	43 / 47 / 51	
External Static Pressure, 208 V (L / M / H*)	in.wg	0.287 / 0.641 / 1.075	
External Static Pressure, 230 V (L / M / H*)	in.wg	0.506 / 0.814 / 1.175	
ELECTRICAL			
Power Supply	V/Ph/Hz	208-230/1/60	
Power Consumption (208/230 V)	kW	0.38 / 0.41	
Full Load Amps (FLA)	A	2.34	
Minimum Circuit Amps (MCA)	A	2.93	
Maximum Overcurrent Protection	A	15	

MOTOR		
Motor Type	208/230 V, 3 Tap, PSC	
Motor Watts	W	260
PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1-1/4
Pipe Connection Size - Drain (ID)	in.	1
Refrigerant	R-410A	
External Finish	Zinc Hot Dipped Steel Plate	
Unit Width	in.	33-1/2
Unit Height	in.	15
Unit Depth	in.	26
Net Weight	lb	128

* Low, Medium, High Taps. Medium Tap set from factory.

ACCESSORIES

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL

DIMENSIONAL DRAWING

INDOOR UNIT HIGH STATIC DUCT MMD-AP0364H2UL

