



Turn to the experts



WeatherMaker® Commercial Packaged Rooftops



Gas Heating / Electric Cooling Models – 48FC

Nominal Cooling Ton Size	Cooling Stages	AHRI Efficiency (SEER) IEER	Dimensions (in) L x W x H	Gas Heat - Heating Input (Btuh)			Approx. Unit Weight (lbs)
				Low	Medium	High	
3	1	(14.0)	74 x 47 x 33	67	110	–	482
4	1	(14.0)	74 x 47 x 33	67	110	150	543
5	1	(14.0)	74 x 47 x 33	67	110	150	556
6	2	15.0	74 x 47 x 41	67	110	150	607

Electric Heat / Electric Cooling & Cooling Only Models – 50FC

Nominal Cooling Ton Size	Cooling Stages	AHRI Efficiency (SEER) IEER	Dimensions (in) L x W x H	Electrical Heat Nominal kW Range	Approx. Unit Weight (lbs)
3	1	(14.0)	74 x 47 x 33	4.0 to 15.0	437
4	1	(14.0)	74 x 47 x 33	4.0 to 21.0	498
5	1	(14.0)	74 x 47 x 33	6.5 to 24.0	511
6	2	15.2	74 x 47 x 41	6.5 to 24.0	562

WeatherMaster® Commercial Packaged Rooftops – High Efficiency



Gas Heating / Electric Cooling Models – High Efficient 48GC

Nominal Cooling Ton Size	Cooling Stages	AHRI Efficiency SEER	Dimensions (in) L x W x H	Gas Heat - Heating Input (Btuh)			Approx. Unit Weight (lbs)
				Low	Medium	High	
3	2	16.0	74 x 47 x 33	67	110	–	513
4	2	16.0	74 x 47 x 33	67	110	150	555
5	2	16.0	74 x 47 x 41	67	110	150	600

Electric Heat / Electric Cooling & Cooling Only Models – High Efficient 50GC

Nominal Cooling Ton Size	Cooling Stages	AHRI Efficiency SEER	Dimensions (in) L x W x H	Electrical Heat Nominal kW Range	Approx. Unit Weight (lbs)
3	2	16.0	74 x 47 x 33	4.0 to 15.0	468
4	2	16.0	74 x 47 x 33	4.0 to 21.0	510
5	2	16.0	74 x 47 x 41	6.5 to 24.0	555

Full Range of pre-certified, factory-installed options include:

- Temperature Sensing EconoMi\$er with relief
- Enthalpy Sensing EconoMi\$er with relief
- Humidi-MiZer® Adaptive Dehumidification System
- Multiple Gas Heat Sizes
- Stainless Steel Gas Heat Exchangers
- Return Air Smoke Detector
- Supply Air Smoke Detector
- CO₂ Sensor
- Condensate Overflow Protection
- Multiple Static Fan Capabilities
- Phase Monitor/Protection
- Thru-The-Base Utility Connections
- Louvered Hail Guards
- Non-Fused Disconnect Switch
- HACR Breaker (GC models)
- Electric Heaters (GC Models)
- Low Ambient Controls (GC Models)
- Foil Face Insulation (GC Models)
- MERV-8 Return Air Filters
- Hinged Access Panels
- Unpowered Convenience Outlet
- Powered Convenience Outlet
- Coated Coils:
 - Pre-Coat
 - E-Coat
 - Copper/Copper
- Electrical Mechanical Controls
- SystemVu™ Integrated Communicating Controls
- RTU-Open Communicating Controls
- Extended Warranty Protection Plans
- Financing Available

